MATERIAL SAFETY DATA SHEET

Canadian Headquarters

Diversey, Inc. - Canada, Inc.

Oakville, Ontario L6H 6P1

Phone: 1-800-668-3131

2401 Bristol Circle



J-Works Hurricane Force

| HMIS NFPA | | 1 | Personal protective equipment | |
|-------------|---|--------------|-------------------------------|------------|
| Health | 3 | Health | 3 | ma shill a |
| Fire Hazard | 0 | Flammability | 0 | |
| Reactivity | 0 | Instability | 0 | |

Version Number: 3

Preparation date: 2010-03-01

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

J-Works Hurricane Force

MSDS #: Product Code: Recommended use:

MS0300063 5002128, 5002136, 5002187, 5002195, 5124635, 5386037 Cleaning product. This product is intended to be diluted prior to use.

Manufacturer, importer, supplier: US Headquarters Diversey, Inc. 8310 16th St. Sturtevant, Wisconsin 53177-1964 Phone: 1-888-352-2249

MSDS Internet Address: www.johnsondiversey.com Emergency telephone number:

1-800-851-7145 (U.S.)

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER. CORROSIVE. CAUSES SKIN AND EYE BURNS. HARMFUL OR FATAL IF SWALLOWED.

| Principle routes of exposure: | Eye contact. Skin contact. Inhalation. |
|-------------------------------|---|
| Eye contact: | Corrosive. Causes permanent eye damage, including blindness. |
| Skin contact: | Corrosive. Causes permanent damage. |
| Inhalation: | May cause irritation and corrosive effects to nose, throat and respiratory tract. |
| Ingestion: | Corrosive. Causes burns to mouth, throat and stomach. |

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Ingredient(s) | CAS # | Weight % | LD50 Oral - Rat (mg/kg) | LD50 Dermal - Rabbit | LC50 Inhalation - Rat |
|---------------------|-----------|----------|----------------------------|-------------------------|-----------------------------------|
| 2-butoxyethanol | 111-76-2 | 1 - 5% | 470 | 220 mg/kg | 2.21 mg/L (4 h); 450 ppm (4 h) |
| Sodium metasilicate | 6834-92-0 | 1 - 5% | 600 | Not available | Not available |

4. FIRST AID MEASURES

| Eye contact: | Immediately flush eyes with running water for at least 15-20 minutes, keeping eyelids open. Get medical attention immediately. |
|--|---|
| Skin contact: Inhalation: Ingestion: | Flush immediately with plenty of water for at least 15-20 minutes. Get medical attention immediately. If breathing is affected, remove to fresh air. Get medical attention immediately. If swallowed, give a cupful of water or milk. THEN IMMEDIATELY CONTACT A PHYSICIAN OR POISON CENTER. DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. |
| Aggravated Medical Conditions: | Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects |

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: Specific hazards: Unusual hazards: Specific methods: The product is not flammable. Extinguish fire using agent suitable for surrounding fire. None known. Corrosive material (See sections 8 and 10). No special methods required.

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Extinguishing media which must not be used for safety reasons: No information available.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Environmental precautions and clean-up methods: Use personal protective equipment. Use appropriate containment to avoid environmental contamination. Soak up with inert absorbent material. Shovel into suitable container for disposal.

7. HANDLING AND STORAGE

Handling:

Avoid contact with skin, eyes and clothing. Do not taste or swallow. Avoid breathing vapors or mists. Use only with adequate ventilation. Remove and wash contaminated clothing and footwear before re-use. Wash thoroughly after handling. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

Storage:

Protect from freezing. Keep tightly closed in a dry, cool and well-ventilated place. KEEP OUT OF REACH OF CHILDREN.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels Respiratory protection is not required if good ventilation is maintained

| Personal Protective Equipment | |
|-------------------------------|--|
| Eye protection: | Chemical-splash goggles. |
| Hand protection: | Chemical-resistant gloves |
| Skin and body protection: | Protective footwear. If major exposure is possible, wear suitable protective clothing and footwear. |
| Respiratory protection: | In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. |
| Hygiene measures: | Handle in accordance with good industrial hygiene and safety practice. |

| Ingredient(s) | CAS # | ACGIH | OSHA | Mexico |
|-----------------|----------|--------------|---|--|
| 2-butoxyethanol | 111-76-2 | 20 ppm (TWA) | Skin 240 mg/m³ (TWA) 50 ppm (TWA) | 75 ppm (STEL) 360 mg/m ³ (STEL) 26 ppm (TWA) 120 mg/m ³ (TWA) |

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid Bulk density: No information available Appearance: Liquid Evaporation Rate No information available Specific gravity: 1.07 Vapor density: No information available Color: Red Odor: Solvent Boiling point/range: Not determined Melting point/range: No information available Decomposition temperature: No information available Autoignition temperature: No information available Solubility: Completely Soluble Solubility in other solvents: No information available Density: 8.93 lbs/gal 1.07 Kg/L Flash point: > 200 °F > 93.4 °C Viscosity: No information available Partition coefficient (n-octanol/water): No information available Elemental Phosphorus: 0 % by wt. VOC: 3.8 %* pH: 12.63 Dilution pH: No information available.

Explosion limits: - upper: Not determined - lower: Not determined

* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

10. STABILITY AND REACTIVITY

Stability: Polymerization: Hazardous decomposition products: Conditions to avoid: The product is stable Hazardous polymerization does not occur. None reasonably foreseeable. Do not freeze.

11. TOXICOLOGICAL INFORMATION

| Acute toxicity: Component Information: | Oral LD50 estimated to be greater than 5000 mg/kg. Dermal LD50 estimated to be > 2000 mg/kg See Section 3. |
|--|--|
| Chronic toxicity: | None known |
| Specific effects Carcinogenic effects: Mutagenic effects: Reproductive toxicity: Target organ effects: | None known None known None known None known |

12. ECOLOGICAL INFORMATION

Environmental Information:

No data available.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products:

Dispose of according to all federal, state and local applicable regulations. **RCRA Hazard Class:** D002

14. TRANSPORT INFORMATION

DOT/TDG: Please refer to the Bill of Lading/receiving documents for up to date shipping information .

15. REGULATORY INFORMATION

International Inventories

All components of this product are listed on the following inventories: U.S.A. (TSCA)

U.S. Regulations

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65.

RIGHT TO KNOW (RTK)

| Ingredient(s) | CAS # | MARTK: | NJRTK: | PARTK: | RIRTK: |
|-------------------------|------------|--------|--------|--------|--------|
| 2-butoxyethanol | 111-76-2 | Х | Х | Х | Х |
| Sodium xylene sulfonate | 1300-72-7 | - | - | - | - |
| Sodium metasilicate | 6834-92-0 | - | - | - | - |
| Alcohol ethoxylates | 68439-46-3 | - | - | - | - |
| Water | 7732-18-5 | - | - | - | - |

CERCLA/ SARA

| Ingredient(s) | CAS # | Weight % | CERCLA/SARA RQ (lbs) | Section 302 TPQ (lbs) | Section 313 |
|-----------------|----------|----------|-------------------------|-----------------------|-------------|
| 2-butoxyethanol | 111-76-2 | 1 - 5% | \$ <i>L</i> | | Х |

| Ingredient(s) | CAA HAP | CAA ODS | CWA Priority Pollutants |
|-----------------|---------|---------|-------------------------|
| 2-butoxyethanol | Х | | |

SARA 311/312 Hazard Categories

| Immediate: | Х |
|------------|---|
| Delayed: | - |

Fire: Reactivity: Sudden Release of Pressure:

Canada



WHMIS hazard class: E Corrosive material

16. OTHER INFORMATION

Reason for revision: Prepared by: Additional advice: Not applicable NAPRAC None.

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.