

ATTAC

National Fire
Protection
Association (NFPA)

Health
Reactivity

Fire Hazard
Information System
(HMIS)

Reactivity

Specific Hazard

Protective Clothing







Emergency Overview

Clear White to yellowish. Liquid. See Section 9. DANGER. CORROSIVE. CAUSES EYE AND SKIN BURNS. HARMFUL OR FATAL IF SWALLOWED.

Section 1. Chemical Product and Company Identification				
Product Name	ATTAC		Code	54260 & 54261
Product Use	Product Use Industrial/Institutional: Floor care.		PMS#	453189
MSDS# 126414001			Validation Date	12/19/2001
U.S. Headquarters		Canadian Headquarters	Print Date	12/19/2001
Johnson Wax Professional 8310 16th Street		Johnson Wax Professional 100 Matheson Blvd. East, Suite 203	Supersedes	12/19/2001.
Sturtevant, Wisconsin 53177-0902 Phone: (888) 352-2249 MSDS Internet Address: www.jwp.com		Mississauga, Ontario L4Z 2G7 Phone: (905) 755-0913 or (888) 746-5971	In Case of Emergency	(800) 851-7145

Section 2. Composition and Information on Ingredients				
Ingredients	CAS#	% by Weight	Exposure Limits	LC50/LD50
Sodium Hydroxide	1310-73-2	1-5	OSHA (United States). CEIL: 2 mg/m³ ACGIH (United States). STEL: 2 mg/m³	Not available.
Ethylene Glycol Phenyl Ether	122-99-6	1-5	Not available.	ORAL (LD50): Acute: 1260 mg/kg [Rat].
Sodium Xylene Sulfonate	1300-72-7	1-5	Not available.	Not available.
Monoethanolamine	141-43-5	10-30	OSHA (United States). TWA: 8 mg/m³ STEL: 15 mg/m³ ACGIH (United States). TWA: 7.5 mg/m³ STEL: 15 mg/m³	ORAL (LD50): Acute: 1720 mg/kg [Rat]. DERMAL (LD50): Acute: 1018 mg/kg [Rabbit].
2-Butoxyethanol	111-76-2	10-30	OSHA (United States). TWA: 120 mg/m³ ACGIH (United States). TWA: 97 mg/m³	ORAL (LD50): Acute: 506 mg/kg [Rat]. DERMAL (LD50): Acute: 406 mg/kg [Rabbit]. VAPOR (LC50): Acute: 450 ppm 4 hour(s) [Rat].
Water	7732-18-5	30-60	Not available.	Not available.

Section 3. Hazards Identification				
Routes of Entry	Inhalation. Skin contact. Eye contact.			
Potential Acute Health	Effects			
	Eyes Corrosive. May cause permanent damage including blindness.			
Skin Corrosive. May cause permanent damage.				
Inhalation May cause irritation and corrosive effects to nose, throat and respiratory tract.				
In	ngestion Corrosive. May cause burns to mouth, throat, and stomach.			
Medical Conditions Aggravated by Overex	Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may posure: be more susceptible to irritating effects.			
See Toxicological Infor	rmation (section 11)			



ATTAC

Section 4. First	Section 4. First Aid Measures		
Eye Contact	Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention immediately.		
Skin Contact	Flush immediately with plenty of water for at least 15 minutes. Get medical attention immediately.		
Inhalation	If breathing is difficult: Remove to fresh air. Get medical attention immediately.		
Ingestion	Do not induce vomiting! Immediately drink plenty of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.		

Section 5. Fire Fighti	Section 5. Fire Fighting Measures			
Flammability of the Product Flash Points	None known. Not available.			
Products of Combustion	None known.			
Fire Fighting Media and Instructions	Extinguish with water spray or carbon dioxide, dry chemical powder or appropriate foam. Normal fire fighting procedure may be used.			
Protective Clothing (Fire)	Put on appropriate personal protective equipment (see Section 8).			
Special Remarks on Fire and Explosion Hazards	• • • • • • • • • • • • • • • • • • • •			

Section 6. Accidental Release Measures		
Personal Precautions	Put on appropriate personal protective equipment (see Section 8).	
Environmental Precautions and Clean-up Methods	In the event of major spillage: Use appropriate containment to avoid environmental contamination. Sweep or scrape up material. Place in suitable clean, dry containers for disposal by approved methods. Use a water rinse for final clean-up.	

Section 7. Ha	Section 7. Handling and Storage		
Handling	Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Avoid breathing vapors or spray mists. Wash thoroughly after handling. Remove and wash contaminated clothing and footwear before re-use. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR INDUSTRIAL USE ONLY.		
Storage	Store in a dry, cool and well-ventilated area. Protect from freezing. Keep container tightly closed. KEEP OUT OF REACH OF CHILDREN.		

,	Controls/Personal Protection
Engineering Controls	Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.
Personal Protection	
Eyes	Chemical splash goggles.
Hands	Chemical resistant gloves. Includes: Neoprene gloves.
	If mists/vapors are not adequately controlled by ventilation, use appropriate respiratory protection to avoid over exposure. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.
Feet	Protective footwear.
Body	If major exposure is possible, wear suitable protective clothing and footwear.

Section 9. Physical and Chemical Properties

Physical State and

Appearance

Liquid.

Odor Mild.

Color Clear White to yellowish.

pH >13 [Basic.]

Specific Gravity 1.02

 $\begin{tabular}{ll} \textbf{Boiling/Condensation Point} & >82^{\circ}C \ (179.6^{\circ}F) \\ \textbf{Melting/Freezing Point} & <0^{\circ}C \ (32^{\circ}F) \\ \end{tabular}$



Solubility in water Complete.

ATTAC

Section 10. Stability and Reactivity			
Stability and Reactivity	The product is stable.		
Conditions of Instability	None known.		
Incompatibility with Various Substances	Reactive with oxidizing agents, acids.		
Hazardous Decomposition Products	Produces normal products of combustion. Toxic decomposition products include: Oxides of nitrogen.		
Hazardous Polymerization	Will not occur.		

Section 11	. Tox	icologic	al Inf	ormation
------------	-------	----------	--------	----------

Acute toxicity Corrosive.

Effects of Chronic Exposure None known.

Other Toxic Effects Not available.

Section 12. Ecological Information

Not available.

Section 13. Disposal Considerations

Waste Information Undiluted product is regulated under environmental and transportation laws as a corrosive waste. Dispose of according to all federal, state and local regulations.

Section 14. Transport Information

DOT Classification

DOT Proper Shipping Name

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

TDG Classification

TDG Proper Shipping Name TDG Class

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

Section 15. Regulatory Information

Reporting in this section is based on ingredients disclosed in Section 2

US Regulations

Federal Not applicable.

State Not applicable.

This product is not subject to the reporting requirements under California's Proposition 65.

Registered Product Information Not applicable.

Canadian Regulations

Canadian NPRI Canadian NPRI: 2-Butoxyethanol.
WHMIS Classification WHMIS Class E: Corrosive liquid.

WHMIS Icon



Registered Product Information Not applicable.

Chemical Inventory Status All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical

Substance Inventory



Section 16. Other Information			
Other Special Considerations	Not available.		
Version	1.01		

Notice to Reader

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.