

Material Safety Data Sheet

(800) 851-7145

BREAK-UP

National Fire	Fire Ha	Fire Hazard		Material	Health	3
Protection	NFPA) Health			n System	Fire Hazard	0
Association (NF	(FPA) Health (3) Reactivity		(HMIS)	Reactivity	0	
	Specific	Hazard				
Clothing View DANGER. C		DANGER. CO		uid. See Section 9. JSES EYE AND SH ALLOWED.	KIN BURNS	
Section 1. C	hemical Product and Co	mpany Identification	1			
Product Name	BREAK-UP			Code	4498	
Product Use	Industrial/Institutional: Cleaning product. This product is intended to be diluted prior to use.		ct is intended	PMS#	461918	
MSDS#	114490011			Validation Date	8/2/2000	
MSDS# U.S. Headquarters		Canadian Headquarters		Validation Date Print Date	e 8/2/2000 8/2/2000	

100 Matheson Blvd. East, Suite 203

Mississauga, Ontario L4Z 2G7

Phone: (905) 755-0913 or

(888) 746-5971

Supersedes

In Case of

Emergency

Johnson Wax Professional 8310 16th Street Sturtevant, Wisconsin 53177-0902 Phone: (888) 352-2249 **MSDS Internet Address:** www.jwp.com

Section 2. Composition and Information on Ingredients				
Ingredients	CAS #	% by Weight	Exposure Limits	LC50/LD50
Potassium Salt of Dibasic Fatty Acid	68127-33-3	1-5	Not available.	Not available.
Potassium Hydroxide	1310-58-3	1-5	CEIL: 2 (mg/m ³) from OSHA (PEL) [United States] STEL: 2 (mg/m ³) from ACGIH (TLV) [United States]	ORAL (LD50): Acute: 365 mg/kg [Rat]. 273 mg/kg [Male. Rat].
Sodium silicate	1344-09-8	1-5	Not available.	Not available.
Tripotassium Salt of EDTA	17572-97-3	1-5	Not available.	Not available.
Tetrapotassium Pyrophosphate	7320-34-5	1-5	Not available.	DERMAL (LD50): Acute: >4640 mg/kg [Rabbit].
Water	7732-18-5	60-100	Not available.	Not applicable.

Section 3. Hazards Identification

Routes of Entry	Inhalation. Skin contact. Eye contact.
Potential Acute Health Effects	
Eyes	Corrosive. May cause permanent damage including blindness.
Skin	Corrosive. May cause permanent damage.
Inhalation	May cause irritation and corrosive effects to nose, throat and respiratory tract.
Ingestion	Corrosive. May cause burns to mouth, throat, and stomach.
Medical Conditions Aggravated by Overexposure:	Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects.
See Toxicological Information	(section 11)

Section 4. First Aid Measures

ONDSON WAX PROFESSIONAL

Eye Contact	Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention immediately.
Skin Contact	Flush immediately with plenty of water for at least 15 minutes. Get medical attention immediately.
Inhalation	If breathing is difficult: Remove to fresh air. Get medical attention immediately.
Ingestion	Do not induce vomiting! Immediately drink plenty of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

Flammability of the Product Flash Points	None known. None known.
Products of Combustion	None known.
Fire Fighting Media and Instructions	Extinguish with water spray or carbon dioxide, dry chemical powder or appropriate foam. Normal fire fighting procedure may be used.
Protective Clothing (Fire)	Put on appropriate personal protective equipment (see Section 8.).
Special Remarks on Fire and Explosion Hazards	Corrosive material (See sections 8 and 10).

Section 6. Accidental Release Measures

Personal Precautions	Put on appropriate personal protective equipment (see Section 8.).
Environmental Precautions and Clean-up Methods	In the event of major spillage: Use appropriate containment to avoid environmental contamination. Sweep or scrape up material. Place in suitable clean, dry containers for disposal by approved methods. Use a water rinse for final clean-up.

Section 7. Handling and Storage

Handling	Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Avoid breathing vapors or spray mists. Wash thoroughly after handling. Remove and wash contaminated clothing and footwear before re-use. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR INDUSTRIAL USE ONLY.
Storage	Store in a dry, cool and well-ventilated area. Protect from freezing. Keep container tightly closed. KEEP OUT OF REACH OF CHILDREN.

Section 8. Exposure Controls/Personal Protection

Engineering Controls	Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.
Personal Protection	
Eyes	Chemical splash goggles.
Hands	Chemical resistant gloves. Includes: Neoprene gloves.
Respiratory	If mists/vapors are not adequately controlled by ventilation, use appropriate respiratory protection to avoid over exposure. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.
Feet	Protective footwear.
Body	If major exposure is possible, wear suitable protective clothing and footwear.

Section 9. Physical and Chemical Properties

Physical State and Appearance	Liquid.
Odor	Bland.
Color	Clear Pale color. Yellow.
рН	>13 [Basic.]
Specific Gravity	1.09
Boiling/Condensation Point	>93°C (200°F)
Melting/Freezing Point	0°C (32°F)

Continued on Next Page

Johnson wax PROFESSIONAL

BREAK-UP

Viscosity

Solubility in water

<10 cP (Dynamic). Complete.

Section 10. Stability and Reactivity		
Stability and Reactivity	The product is stable.	
Conditions of Instability	None known.	
Incompatibility with Various Substances	Reactive with oxidizing agents, acids. Avoid mixing with: Non-ferrous metal.	
Hazardous Decomposition Products	When exposed to fire: Produces normal products of combustion.	
Hazardous Polymerization	Will not occur.	

 Section 11. Toxicological Information

 Acute toxicity
 Corrosive.

Effects of Chronic ExposureNone known.Other Toxic EffectsNone known.

Section 12. Ecological Information

Not available.

Section 13. Disposal Considerations


 Waste Information
 Undiluted product is regulated under environmental and transportation laws as a corrosive waste. Dispose of according to all federal, state and local regulations.

Section 14. Transport Information

DOT Classification	
DOT Proper Shipping Name	Corrosive liquid, basic, inorganic, n.o.s. (Potassium hydroxide , Sodium silicate)
DOT Class	Class 8: Corrosive material
UN/NA	UN3266
Packing Group	III
TDG Classification	
TDG Proper Shipping Name	Corrosive liquid, basic, inorganic, n.o.s. (Potassium hydroxide , Sodium silicate)
TDG Class	Class 8: Corrosive material
PIN/NIP	UN3266
Packing Group	III

Section 15. Regulatory Information

Reporting in this section	is based on ingredients disclosed in Section 2
US Regulations	
Federal	Clean Water Act (CWA) 311: Potassium Hydroxide CERCLA: Hazardous substances.: Potassium Hydroxide
State	New Jersey spill list: Potassium Hydroxide New Jersey: Potassium Hydroxide Massachusetts spill list: Potassium Hydroxide Massachusetts RTK: Potassium Hydroxide Pennsylvania RTK: Potassium Hydroxide
	This product is not subject to the reporting requirements under California's Proposition 65.
Registered Product Information	Not applicable.
Canadian Regulations	



Section 16. Other Information	
Other Special Considerations	Not available.
Version	1.01
as to the accuracy of	been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to ble information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws

and regulations.