

CONCENTRATED FLOOR STRIPPER

National Fire Protection Association (Fire Haz	Reactivity	Hazardous Informatio (HMIS)		Health3Fire Hazard0Reactivity0
		Specific H	lazard			
Protective Clothing			Emer Overv	view DANGER. CO	ORROSIVE.). CAUSES EYE AND SKIN BURNS SWALLOWED.
Section 1. C	hemical Produ	uct and Con	npany Identific	ation		
Product Name	CONCENT		OR STRIPPER		Code	5244
Product Use	Industrial/Insti	tutional: Floor	care.		PMS#	438465
MSDS#	126848001				Validation E	Date 12/6/2000
U.S. Headquarters	5		Canadian Headquarters		Print Date	12/6/2000
Johnson Wax Professional 8310 16th Street			Johnson Wax Professional 100 Matheson Blvd. East, Suite 203		Supersedes	9/11/2000.
Sturtevant, Wisconsin 53177-0902 Phone: (888) 352-2249 MSDS Internet Address: www.jwp.com		Mississauga, Ontario L4Z 2G7 Phone: (905) 755-0913 or (888) 746-5971		In Case of Emergency	(800) 851-7145	
Section 2. C	omposition ar	nd Informati	on on Ingredie	ents		
Ingredients		CAS #	% by Weight	Exposure Li	mits	LC50/LD50
Sodium Xylene S Sodium Hydroxid		1300-72-7 1310-73-2	0.5-5 1-5	Not available. CEIL: 2 (mg/m ³) fro (PEL) [United States STEL: 2 (mg/m ³) fro	;] om ACGIH	Not available. Not available.

Monoethanolamine	141-43-5	1-5	(PEL) [United States] STEL: 2 (mg/m ³) from ACGIH (TLV) [United States] TWA: 8 STEL: 15 (mg/m ³) from OSHA (PEL) [United States] TWA: 7.5 STEL: 15 (mg/m ³)	ORAL (LD50): Acute: 1720 mg/kg [Rat]. DERMAL (LD50): Acute: 1018 mg/kg [Rabbit].
			from ACGIH (TLV) [United States]	Acute. 1010 mg/kg [Nabbil].
2-Butoxyethanol	111-76-2	7-13	TWA: 120 (mg/m ³) from OSHA (PEL) [United States] TWA: 97 (mg/m ³) from ACGIH (TLV) [United States]	ORAL (LD50): Acute: 506 mg/kg [Rat]. DERMAL (LD50): Acute: 406 mg/kg [Rabbit]. VAPOR (LC50): Acute: 450 ppm 4 hours [Rat].
Water	7732-18-5	60-100	Not available.	Not available.

Section 3. Hazards Identification

Routes of Entry	Inhalation. Skin contact. Eye contact.
Potential Acute Health Effects	
Eyes	Corrosive. May cause permanent damage including blindness.
Skin	Corrosive. May cause permanent damage.
Inhalation	May cause irritation and corrosive effects to nose, throat and respiratory tract.
Ingestion	Corrosive. May cause burns to mouth, throat, and stomach.
Medical Conditions Aggravated by Overexposure:	Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects.
See Toxicological Information	(section 11)

Section 4. First Aid Measures

Eye Contact	Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention immediately.
Skin Contact	Flush immediately with plenty of water for at least 15 minutes. Get medical attention immediately.
Inhalation	If breathing is difficult: Remove to fresh air. Get medical attention immediately.
Ingestion	Do not induce vomiting! Immediately drink plenty of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

Flammability of the Product Flash Points	None known. CLOSED CUP: >93°C (200°F).
Products of Combustion	None known.
Fire Fighting Media and Instructions	Extinguish with water spray or carbon dioxide, dry chemical powder or appropriate foam. Normal fire fighting procedure may be used.
Protective Clothing (Fire)	Put on appropriate personal protective equipment (see Section 8.).
Special Remarks on Fire and Explosion Hazards	Corrosive material (See sections 8 and 10).

Section 6. Accidental Release Measures

Personal Precautions	Put on appropriate personal protective equipment (see Section 8.).
Environmental Precautions and Clean-up Methods	In the event of major spillage: Use appropriate containment to avoid environmental contamination. Sweep or scrape up material. Place in suitable clean, dry containers for disposal by approved methods. Use a water rinse for final clean-up.

Section 7. Handling and Storage

Handling	Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Avoid breathing vapors or spray mists. Wash thoroughly after handling. Remove and wash contaminated clothing and footwear before re-use. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR INDUSTRIAL USE ONLY.
Storage	Store in a dry, cool and well-ventilated area. Protect from freezing. Keep container tightly closed. KEEP OUT OF REACH OF CHILDREN.

Section 8. Exposure Controls/Personal Protection

Engineering Controls	Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.
Personal Protection	
Eyes	Chemical splash goggles.
Hands	Chemical resistant gloves. Includes: Neoprene gloves.
	If mists/vapors are not adequately controlled by ventilation, use appropriate respiratory protection to avoid over exposure. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.
Feet	Protective footwear.
Body	If major exposure is possible, wear suitable protective clothing and footwear.

Section 9. Physical and Chemical Properties

Physical State and Appearance	Liquid.
Odor	Characteristic.
Color	Clear
рН	>13 [Basic.]
Specific Gravity	1.01
Boiling/Condensation Point	>100°C (212°F)
Melting/Freezing Point	<-16°C (32°F)

Continued on Next Page

Johnson wax PROFESSIONAL

CONCENTRATED FLOOR STRIPPER

VOC15 %Viscosity0-30 cpsSolubility in waterComplete.

Stability and Reactivity	The product is stable.
Conditions of Instability	None known.
Incompatibility with Various Substances	Reactive with acids.
Hazardous Decomposition Products	When exposed to fire: Produces normal products of combustion.
Hazardous Polymerization	Will not occur.

Section 11. Toxicological Information

Acute toxicity	001103140.
Effects of Chronic Exposure	None known.
Other Toxic Effects	None known.

Section 12. Ecological Information

Not available.

Section 13. Disposal Considerations

Waste Information

Undiluted product is regulated under environmental and transportation laws as a corrosive waste. Dispose of according to all federal, state and local regulations.

Section 14. Transport Information

DOT Classification	
DOT Proper Shipping Name	Corrosive liquid, basic, inorganic, n.o.s. (Sodium hydroxide , Monoethanolamine)
DOT Class	Class 8: Corrosive material
UN/NA	UN3266
Packing Group	11
TDG Classification	
TDG Class	Not applicable.
PIN/NIP	

Section 15. Regulatory Information

Reporting in this section is based on ingredients disclosed in Section 2	
US Regulations	
Federal	Clean Water Act (CWA) 311: Sodium Hydroxide CERCLA: Hazardous substances.: Sodium Hydroxide, 2-Butoxyethanol
State	New Jersey spill list: Sodium Hydroxide, 2-Butoxyethanol New Jersey: Monoethanolamine, Sodium Hydroxide, 2-Butoxyethanol Massachusetts spill list: Monoethanolamine, Sodium Hydroxide, 2-Butoxyethanol Massachusetts RTK: Monoethanolamine, Sodium Hydroxide, 2-Butoxyethanol Pennsylvania RTK: Monoethanolamine, Sodium Hydroxide, 2-Butoxyethanol
	This product is not subject to the reporting requirements under California's Proposition 65.
Registered Product Information	Not applicable.
Canadian Regulations	

Canadian NPRI Not applicable.



CONCENTRATED FLOOR STRIPPER

WHMIS Classification Not applicable.

WHMIS Icon

Registered Product Not applicable. Information

Chemical Inventory Status

All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Section 16. Other Information	
Other Special Considerations	Not available.
Version	1.02
Notice to Reader	

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.