

Fire Hazard **National Fire Hazardous Material** Health 1 Protection **Information System Fire Hazard** 4 Health Reactivity **Association (NFPA)** (HMIS) 0 Reactivity Specific Hazard

 Protective None required.
 Emergency Overview
 Colorless. Aerosol. See Section 9.

 Clothing
 Overview
 CAUTION: CONTENTS UNDER PRESSURE. May be mildly irritating to eyes. May be mildly irritating to skin.

Section 1. Chemical Product and Company Identification				
Product Name	END BAC II DISINFECTANT SPRAY		Code	14742
Product Use	Industrial/Institutional: Disinfectant.		PMS#	433113
MSDS#	114740006	006		04/19/2000
U.S. Headquarters		Canadian Headquarters	Print Date	04/19/2000
Johnson Wax Professional 8310 16th Street		Johnson Wax Professional 100 Matheson Blvd. East, Suite 203	Supersedes	04/12/2000.
Sturtevant, Wisconsin 53177-0902 Phone: (888) 352-2249 MSDS Internet Address: www.jwp.com		Mississauga, Ontario L4Z 2G7 Phone: (905) 755-0913 or (888) 746-5971	In Case of Emergency	(800) 851-7145

Section 2. Composition and Information on Ingredients				
Ingredients	CAS#	% by Weight	Exposure Limits	LC50/LD50
n-Alkyl Dimethyl Ethylbenzyl Ammonium Chlorides	68956-79-6	0.072	Not available.	Not available.
n-Alkyl Dimethyl Benzyl Ammonium Chlorides	68391-01-5	0.072	Not available.	Not available.
Propane	74-98-6	1-5	TWA: 1800 (mg/m³) from OSHA (PEL) [United States] TWA: 4508 (mg/m³) from ACGIH (TLV) [United States]	Not available.
Isobutane	75-28-5	10-30	Not available.	VAPOR (LC50): Acute: 0.0057 ppm 0.25 hours [Rat].
Ethyl Alcohol	64-17-5	30-60	TWA: 1900 (mg/m³) from OSHA (PEL) [United States] TWA: 1880 (mg/m³) from ACGIH (TLV) [United States]	ORAL (LD50): Acute: 7060 mg/kg [Rat]. VAPOR (LC50): Acute: 20000 ppm 10 hours [Rat].

Section 3. Hazards Identification		
Routes of Entry	Inhalation. Skin contact. Eye contact.	
Potential Acute Health Effects		
Eyes	May be mildly irritating to eyes.	
Skir	May be mildly irritating to skin.	
Inhalation	May be irritating to nose, throat, and respiratory tract.	
Ingestion	None known.	
Medical Conditions Aggravated by Overexposure:	Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects.	
See Toxicological Information	(section 11)	

Section 4. First Aid Measures		
Eye Contact	Flush immediately with plenty of water. Get medical attention if irritation occurs.	
Skin Contact	Flush immediately with plenty of water. Get medical attention if irritation occurs.	
Inhalation	If breathing is difficult: Remove to fresh air. Get medical attention.	
Ingestion	Have conscious person drink several glasses of water or milk. Immediately get medical attention.	

Section 5. Fire Fighting Measures		
Flammability of the Product Flash Points	None known. CLOSED CUP: <-7°C (19.4°F).	
Products of Combustion	None known.	
Fire Fighting Media and Instructions	Use water spray to keep fire-exposed containers cool. Dry chemical, carbon dioxide. Fight fire from protected location or maximum possible distance. In case of fire and/or explosion do not breathe fumes	
Protective Clothing (Fire)	Put on appropriate personal protective equipment (see Section 8).	
Special Remarks on Fire and Explosion Hazards	Aerosol product - Containers may rocket or explode in heat of fire.	

Section 6. Accidental Release Measures		
Personal Precautions	Put on appropriate personal protective equipment (see Section 8).	
Environmental Precautions and Clean-up Methods	Eliminate all ignition sources. In the event of major spillage: Use appropriate containment to avoid environmental contamination. Take up with sand or other non-combustible material. Place in suitable clean, dry containers for disposal by approved methods.	

Section 7. Handling and Storage		
Handling	Avoid contact with skin and eyes. Avoid breathing vapors or spray mists. FOR INDUSTRIAL USE ONLY. Use only in well-ventilated areas. Do not puncture or incinerate.	
Storage	Store in a dry, cool and well-ventilated area. Protect from freezing. Keep away from heat, sparks and flame. Pressurized container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. KEEP OUT OF REACH OF CHILDREN.	

Section 8. Exposure Controls/Personal Protection		
Engineering Controls	No special ventilation requirements. General room ventilation is adequate.	
Personal Protection		
	Eyes No special protective clothing is required.	
H	Ands No special protective clothing is required.	
Respir	ratory No special protective clothing is required.	
	Feet No special protective clothing is required.	
	Body No special protective clothing is required.	

Section 9. Physical and Chemical Properties		
Physical State and Appearance	Liquid. (Aerosol.)	
Odor	Mild.	
Color	Colorless.	
pН	9.35 [Basic.]	
Specific Gravity	0.9	
Vapor Pressure	60 mm of Hg	
Solubility in water	Complete.	



Section 10. Stability and Reactivity		
Stability and Reactivity	The product is stable.	
Conditions of Instability	Excessive heat.	
Incompatibility with Various Substances	None known.	
Hazardous Decomposition Products	When exposed to fire: Produces normal products of combustion.	
Hazardous Polymerization	Will not occur.	

Section 11. Toxicological Information	
Acute toxicity	Not available.
Effects of Chronic Exposure	None known.
Other Toxic Effects	Not available.

Section 12. Ecological Information

Not available.

Section 13. Disposal Considerations

Waste Information If possible, recycle empty aerosol cans to the nearest steel recycling center. Use up package or give to someone who can. Dispose of according to all federal, state and local regulations.

Section 14. Transport Information

DOT Classification

Not regulated

TDG Classification

Not regulated

Section 15. Regulatory Information

Reporting in this section is based on ingredients disclosed in Section 2

US Regulations

Federal Clean air act (CAA) 112 regulated flammable substances: Isobutane, Propane

CERCLA: Hazardous substances.: Isobutane, Propane, Ethyl Alcohol

State New Jersey: Isobutane, Propane, Ethyl Alcohol

Massachusetts spill list: Isobutane, Propane, Ethyl Alcohol Massachusetts RTK: Isobutane, Propane, Ethyl Alcohol Pennsylvania RTK: Isobutane, Propane, Ethyl Alcohol

This product is not subject to the reporting requirements under California's Proposition 65.

Registered Product EPA Registration Number: 11525-30-4822

Information

Canadian Regulations

WHMIS Classification Not controlled under WHMIS (Canada).

WHMIS Icon



Registered Product Not applicable. Information

Chemical Inventory Status

All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.



Section 16. Other Information		
Other Special Considerations	MSDS Serial Range: 006-007	
Version	1	
N.C. (D. I		

Notice to Reader

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.