

# **Material Safety Data Sheet**

# **FREEDOM SC**

National Fire Protection Association (N		1 Reactivity	Hazardous M Information S (HMIS)	System F	lealth 3 ire Hazard 0 leactivity 0
Protective Clothing		Emergency Overview	Yellow. Liquid. S DANGER. COR HARMFUL OR I	ROSIVE. CAUS	SES EYE AND SKIN BURNS. LOWED.
Section 1. Cl	Section 1. Chemical Product and Company Identification				
Product Name	roduct Name FREEDOM SC		(	Code	7833
Product Use	roduct Use Industrial/Institutional: Floor care.		I	PMS#	433204
MSDS#	126060001		V	Validation Date	8/2/2001
U <b>.S. Headquarters</b> Johnson Wax Professional 8310 16th Street		Canadian Headquarters	I	Print Date	8/2/2001
		Johnson Wax Professio 100 Matheson Blvd. East		Supersedes	No Previous Validation.
Sturtevant, Wisconsin 53177-0902 Phone: (888) 352-2249 MSDS Internet Address: www.jwp.com		Mississauga, Ontario L4 Phone: (905) 755-0913 (888) 746-5971	IZ 2G7	In Case of Emergency	(800) 851-7145

# Section 2. Composition and Information on Ingredients

Ingredients	CAS #	% by Weight	Exposure Limits	LC50/LD50
Surfactant Tall Oil Fatty Acid	173536-74-8 61790-12-3	1-5 1-5	Not available. Not available.	Not available. Not available.
Glycol Ether	112-25-4	10-30	Not available.	ORAL (LD50): Acute: 830 mg/kg [Rat]. DERMAL (LD50): Acute: 810 mg/kg [Rabbit].
Solvent	100-51-6	10-30	Not available.	ORAL (LD50): Acute: 1230 mg/kg [Rat]. DERMAL (LD50): Acute: 2000 mg/kg [Rabbit].
Monoethanolamine	141-43-5	30-60	OSHA (United States). TWA: 8 mg/m <sup>3</sup> STEL: 15 mg/m <sup>3</sup> ACGIH (United States). TWA: 7.5 mg/m <sup>3</sup> STEL: 15 mg/m <sup>3</sup>	ORAL (LD50): Acute: 1720 mg/kg [Rat]. DERMAL (LD50): Acute: 1018 mg/kg [Rabbit].

Section 3. Hazards Identification				
Routes of Entry	Inhalation. Skin contact. Eye contact.			
Potential Acute Health Effec	Potential Acute Health Effects			
Ey	es Corrosive. May cause permanent damage including blindness.			
Sk	in Corrosive. May cause permanent damage.			
Inhalatio	m May cause irritation and corrosive effects to nose, throat and respiratory tract.			
Ingestic	<i>n</i> Corrosive. May cause burns to mouth, throat, and stomach.			
Medical Conditions Aggravated by Overexposure	Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects.			
See Toxicological Informatio	n (section 11)			

#### Section 4. First Aid Measures

Eye Contact	re Contact Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get med attention immediately.	
Skin Contact	htact Flush immediately with plenty of water for at least 15 minutes. Get medical attention immediately.	
Inhalation	If breathing is difficult: Remove to fresh air. Get medical attention immediately.	
Ingestion	Do not induce vomiting! Immediately drink plenty of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.	

# Section 5. Fire Fighting Measures

Flammability of the Product Flash Points	None known. CLOSED CUP: >93.3°C (199.9°F).
Products of Combustion	None known.
Fire Fighting Media and Instructions	Extinguish with water spray or carbon dioxide, dry chemical powder or appropriate foam. Normal fire fighting procedure may be used.
<b>Protective Clothing (Fire)</b>	Put on appropriate personal protective equipment (see Section 8).
Special Remarks on Fire and Explosion Hazards	Corrosive material (See sections 8 and 10).

# Section 6. Accidental Release Measures

Personal Precautions	Put on appropriate personal protective equipment (see Section 8).
Environmental Precautions and Clean-up Methods	In the event of major spillage: Use appropriate containment to avoid environmental contamination. Sweep or scrape up material. Place in suitable clean, dry containers for disposal by approved methods. Use a water rinse for final clean-up.

# Section 7. Handling and Storage

Handling Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Avoid breathing mists. Wash thoroughly after handling. Remove and wash contaminated clothing and re-use. Product residue may remain on/in empty containers. All precautions for handling be used in handling the empty container and residue. FOR INDUSTRIAL USE ONLY.	
Storage	Store in a dry, cool and well-ventilated area. Protect from freezing. Keep container tightly closed. KEEP OUT OF REACH OF CHILDREN.

## Section 8. Exposure Controls/Personal Protection

	Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.
Personal Protection	
Eyes	Chemical splash goggles.
Hands	Chemical resistant gloves. Includes: Neoprene gloves.
	If mists/vapors are not adequately controlled by ventilation, use appropriate respiratory protection to avoid over exposure. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.
Feet	Protective footwear.
Body	If major exposure is possible, wear suitable protective clothing and footwear.

# Section 9. Physical and Chemical Properties

Physical State and	Liquid.
Appearance	
Odor	Mild.
Color	Yellow. (Light.)
рН	12 [Basic.]
Specific Gravity	0.98
Solubility in water	Complete.

#### Material Safety Data Sheet

FREEDOM SC

# Section 10. Stability and Reactivity

150N WAX

Stability and Reactivity	The product is stable.	
<b>Conditions of Instability</b>	None known.	
Incompatibility with Various Substances	Reactive with oxidizing agents, acids. Do not mix with any other chemicals or products unless specified by label.	
Hazardous Decomposition Products	When exposed to fire: Produces normal products of combustion. Toxic decomposition products include: Oxides of nitrogen.	
Hazardous Polymerization	Will not occur.	

#### Section 11. Toxicological Information

Acute toxicity Corrosive. Effects of Chronic Exposure None known. Other Toxic Effects Not available.

#### Section 12. Ecological Information

Not available.

### Section 13. Disposal Considerations

Waste Information

Undiluted product is regulated under environmental and transportation laws as a corrosive waste. Dispose of according to all federal, state and local regulations.


#### Section 14. Transport Information

DOT C	assification			
	DOT Proper Shipping Name DOT Class	Please refer to the Bill of Lading/receiving documents for up to date shipping information.		
	UN/NA			
	DOT Special Considerations			
TDG C	TDG Classification			
	TDG Proper Shipping Name TDG Class	Please refer to the Bill of Lading/receiving documents for up to date shipping information.		
	PIN/NIP			
	TDG Special Considerations			

#### Section 15. Regulatory Information

Reporting in this section is based on ingredients disclosed in Section 2 **US Regulations** State New Jersey: Monoethanolamine Massachusetts spill list: Monoethanolamine Massachusetts RTK: Monoethanolamine, Benzyl Alcohol Pennsylvania RTK: Monoethanolamine, Benzyl Alcohol This product is not subject to the reporting requirements under California's Proposition 65. Registered Product Not applicable. Information **Canadian Regulations** 

WHMIS Classification CLASS E: Corrosive liquid.



Version
<u>Notice to Reader</u>

1

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.