

National Fire
Protection
Association (NFPA)

Fire Hazard
Information System
(HMIS)

Health

The Hazard
Information System
(HMIS)

Reactivity

Health

Reactivity

O

Reactivity

Protective Sclothing







Specific Hazard

Emergency Overview

y Clear Liquid. See Section 9.

DANGER. CORROSIVE. CAUSES EYE AND SKIN BURNS. HARMFUL OR FATAL IF SWALLOWED.

Section 1. Chemical Product and Company Identification				
Product Name	FREEDOM SPEED STRIPPER		Code	54579
Product Use	Industrial/Institutional: Floor care.		PMS#	432233
MSDS#	114575003	114575003		04/19/2000
U.S. Headquarters		Canadian Headquarters	Print Date	04/19/2000
Johnson Wax Professional 8310 16th Street		Johnson Wax Professional 100 Matheson Blvd. East, Suite 203	Supersedes	04/12/2000.
Sturtevant, Wisconsin 53177-0902 Phone: (888) 352-2249 MSDS Internet Address: www.jwp.com		Mississauga, Ontario L4Z 2G7 Phone: (905) 755-0913 or (888) 746-5971	In Case of Emergency	(800) 851-7145

Section 2. Composition and Information on Ingredients				
Ingredients	CAS#	% by Weight	Exposure Limits	LC50/LD50
Diethylene Glycol Ethyl Ether	111-90-0	1-5	Not available.	ORAL (LD50): Acute: 5540 to 9740 mg/kg [Rat].
Monoethanolamine	141-43-5	1-5	TWA: 8 STEL: 15 (mg/m³) from OSHA (PEL) [United States] TWA: 7.5 STEL: 15 (mg/m³) from ACGIH (TLV) [United States]	ORAL (LD50): Acute: 1720 mg/kg [Rat]. DERMAL (LD50): Acute: 1018 mg/kg [Rabbit].
Sodium Metasilicate	6834-92-0	1-5	Not available.	ORAL (LD50): Acute: 770 mg/kg [Rat].
Ethylene Glycol Phenyl Ether	122-99-6	5-10	Not available.	ORAL (LD50): Acute: 1260 mg/kg [Rat].
Sodium Xylene Sulfonate Water	1300-72-7 7732-18-5	5-10 60-100	Not available. Not available.	Not available. Not applicable.

Water	1702 To C To To Total available.		
Section 3. Hazards Identification			
Routes of Entry	Inhalation. Skin contact. Eye contact.		
Potential Acute Health Effec	is a second of the second of t		
Ey	es Corrosive. May cause permanent damage including blindness.		
Sk	in Corrosive. May cause permanent damage.		
Inhalatio	Inhalation May cause irritation and corrosive effects to nose, throat and respiratory tract.		
Ingestic	on Corrosive. May cause burns to mouth, throat, and stomach.		
Medical Conditions Aggravated by Overexposure	Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects.		
See Toxicological Informatio	n (section 11)		

Section 4. First Aid Measures		
Eye Contact	Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention immediately.	
Skin Contact	Flush immediately with plenty of water for at least 15 minutes. Get medical attention immediately.	
Inhalation	If breathing is difficult: Remove to fresh air. Get medical attention immediately.	
Ingestion	Do not induce vomiting! Immediately drink plenty of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.	

Section 5. Fire Fighting Measures		
Flammability of the Product Flash Points	None known. Not available.	
Products of Combustion	None known.	
Fire Fighting Media and Instructions	Extinguish with water spray or carbon dioxide, dry chemical powder or appropriate foam. Normal fire fighting procedure may be used.	
Protective Clothing (Fire)	Put on appropriate personal protective equipment (see Section 8.).	
Special Remarks on Fire and Explosion Hazards	Corrosive material (See sections 8 and 10).	

Section 6. Accidental Release Measures		
Personal Precautions	Put on appropriate personal protective equipment (see Section 8.).	
Environmental Precautions and Clean-up Methods	In the event of major spillage: Use appropriate containment to avoid environmental contamination. Sweep or scrape up material. Place in suitable clean, dry containers for disposal by approved methods. Use a water rinse for final clean-up.	

Section 7. Had	Section 7. Handling and Storage		
Handling	Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Avoid breathing vapors or spray mists. Wash thoroughly after handling. Remove and wash contaminated clothing and footwear before re-use. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR INDUSTRIAL USE ONLY		
Storage	Store in a dry, cool and well-ventilated area. Protect from freezing. Keep container tightly closed. KEEP OUT OF REACH OF CHILDREN.		

Section 8. Exposure Controls/Personal Protection		
Engineering Controls	Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.	
Personal Protection		
Eyes	Chemical splash goggles.	
Hands Chemical resistant gloves. Includes: Neoprene gloves.		
	If mists/vapors are not adequately controlled by ventilation, use appropriate respiratory protection to avoid over exposure. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.	
Feet Protective footwear.		
Body	If major exposure is possible, wear suitable protective clothing and footwear.	

Section 9. Physical and Chemical Properties		
Physical State and Appearance	Liquid.	
Odor	Pleasant.	
Color	Clear	
pН	13 to 13.5 [Basic.]	
Specific Gravity	1.09	
Solubility in water	Complete.	

Section 10. Stability and Reactivity		
Stability and Reactivity	The product is stable.	
Conditions of Instability	None known.	
Incompatibility with Various Substances	Reactive with acids.	
Hazardous Decomposition Products	Produces normal products of combustion.	
Hazardous Polymerization	Will not occur.	

Section 11. Toxicological Information		
Acute toxicity	Corrosive.	
Effects of Chronic Exposure	None known.	
Other Toxic Effects	Not available.	

Section 12. Ecological Information

Not available.

Section 13. Disposal Considerations

Waste Information Undiluted product is regulated under environmental and transportation laws as a corrosive waste. Dispose of according to all federal, state and local regulations.

Section 14. Transport Information

DOT Classification

DOT Proper

Shipping Name

Corrosive liquids, n.o.s. (Sodium metasilicate , Monoethanolamine)

Shipping Name

DOT Class Class 8: Corrosive material

UN/NA UN1760
Packing Group II

TDG Classification

TDG Proper Shipping Name Corrosive liquids, n.o.s. (Sodium metasilicate , Monoethanolamine)

TDG Class Class 8: Corrosive material

PIN/NIP UN1760
Packing Group ||

Section 15. Regulatory Information

Reporting in this section is based on ingredients disclosed in Section 2

US Regulations

Federal SARA 313 toxic chemical notification and release reporting: Diethylene Glycol Ethyl Ether

CERCLA: Hazardous substances.: Diethylene Glycol Ethyl Ether

State New Jersey spill list: Diethylene Glycol Ethyl Ether

New Jersey: Monoethanolamine, Diethylene Glycol Ethyl Ether

Massachusetts spill list: Monoethanolamine Massachusetts RTK: Monoethanolamine

Pennsylvania RTK: Monoethanolamine, Diethylene Glycol Ethyl Ether

This product is not subject to the reporting requirements under California's Proposition 65.

Registered Product Not applicable.

Information

Canadian Regulations

WHMIS Classification CLASS D-2B: Material causing other toxic effects (TOXIC).

CLASS E: Corrosive liquid.



WHMIS Icon



Registered Product Not applicable.
Information

Chemical Inventory Status

All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Section 16. Other Information		
Other Special Considerations	Not available.	
Version	1	

Notice to Reader

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.