

Material Safety Data Sheet

J-SHOP 600 CLEANER

National Fire Protection Association (N	Fire Ha IFPA) Health 3 Specific I	0 Reactivity	Hazardous M Information (HMIS)	System	Health3Fire Hazard0Reactivity0	
Protective Clothing		Emergency Overview	DANGER. CO	uid. See Section RROSIVE. CAL FATAL IF SWA	JSES EYE AND SKIN BUF	RNS.
Section 1. Cl	nemical Product and Cor	npany Identification				
Product Name	J-SHOP 600 CLEANER Code 5144					
Product Use	Industrial/Institutional: Floor	care.		PMS#	433460	
MSDS#	115140006	115140006		Validation Date	04/19/2000	
U.S. Headquarters	U.S. Headquarters			Print Date	04/20/2000	
Johnson Wax Prof 8310 16th Street	Johnson Wax Professional 8310 16th Street		nal st, Suite 203	Supersedes	04/12/2000.	
Sturtevant, Wisconsin 53177-0902 Phone: (888) 352-2249 MSDS Internet Address: www.jwp.com		Mississauga, Ontario L4 Phone: (905) 755-0913 (888) 746-5971		<u>In Case of</u> Emergency	(800) 851-7145	

Section 2. Composition and Information on Ingredients

Ingredients	CAS #	% by Weight	Exposure Limits	LC50/LD50
Sodium Hydroxide	1310-73-2	1-5	CEIL: 2 (mg/m ³) from OSHA (PEL) [United States] STEL: 2 (mg/m ³) from ACGIH (TLV) [United States]	Not available.
Sodium silicate	1344-09-8	1-5	Not available.	Not available.
Tetrasodium Salt of EDTA	64-02-8	1-5	Not available.	Not available.
Alkylphenoxy Polyethoxyethanol	26027-38-3	1-5	Not available.	Not available.
Sodium Xylene Sulfonate	1300-72-7	1-5	Not available.	Not available.
2-Butoxyethanol	111-76-2	5-10	TWA: 120 (mg/m ³) from OSHA	ORAL (LD50): Acute: 3000
			(PEL) [United States]	mg/kg [Male. Rat]. 506 mg/kg
			TWA: 97 (mg/m ³) from ACGIH	[Male. Rat]. DERMAL (LD50):
			(TLV) [United States]	Acute: 406 mg/kg [Male. Rabbit].
				VAPOR (LC50): Acute: 450 ppm
				4 hours [Female. Rat]. 486 ppm
				4 hours [Male. Rat].
Water	7732-18-5	60-100	Not available.	Not applicable.

Section 3. Hazards Identification

Routes of Entry	Inhalation. Skin contact. Eye contact.
Potential Acute Health Effects	
Eyes	Corrosive. May cause permanent damage including blindness.
Skin	Corrosive. May cause permanent damage.
Inhalation	May cause irritation and corrosive effects to nose, throat and respiratory tract.
Ingestion	Corrosive. May cause burns to mouth, throat, and stomach.
	Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects.
See Toxicological Information	(section 11)

J-SHOP 600 CLEANER

Section 4. First Aid Measures

Ohnson wax PROFESSIONAL

Eye Contact	Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention immediately.
Skin Contact	Flush immediately with plenty of water for at least 15 minutes. Get medical attention immediately.
Inhalation	If breathing is difficult: Remove to fresh air. Get medical attention immediately.
Ingestion	Do not induce vomiting! Immediately drink plenty of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

Flammability of the Product Flash Points	None known. Not available.
Products of Combustion	None known.
Fire Fighting Media and Instructions	Extinguish with water spray or carbon dioxide, dry chemical powder or appropriate foam. Normal fire fighting procedure may be used.
Protective Clothing (Fire)	Put on appropriate personal protective equipment (see Section 8).
Special Remarks on Fire and Explosion Hazards	Corrosive material (See sections 8 and 10).

Section 6. Accidental Release Measures

Personal Precautions	Put on appropriate personal protective equipment (see Section 8).
Environmental Precautions and Clean-up Methods	In the event of major spillage: Use appropriate containment to avoid environmental contamination. Sweep or scrape up material. Place in suitable clean, dry containers for disposal by approved methods. Use a water rinse for final clean-up.

Section 7. Handling and Storage

Handling	Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Avoid breathing vapors or spray mists. Wash thoroughly after handling. Remove and wash contaminated clothing and footwear before re-use. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR INDUSTRIAL USE ONLY.
Storage	Store in a dry, cool and well-ventilated area. Protect from freezing. Keep container tightly closed. KEEP OUT OF REACH OF CHILDREN.

Section 8. Exposure Controls/Personal Protection

Engineering Controls	Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.
Personal Protection	
Eyes	Chemical splash goggles.
Hands	Chemical resistant gloves. Includes: Neoprene gloves.
Respiratory	If mists/vapors are not adequately controlled by ventilation, use appropriate respiratory protection to avoid over exposure. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.
Feet	Protective footwear.
Body	If major exposure is possible, wear suitable protective clothing and footwear.

Section 9. Physical and Chemical Properties

Physical State and Appearance	Liquid.
Odor	Mild.
Color	Clear Red.
рН	12 [Basic.]
Specific Gravity	1
Boiling/Condensation Point	100°C (212°F)
VOC	8.33 ±

Continued on Next Page

Johnson wax

J-SHOP 600 CLEANER

Solubility in water

Complete.

Section 10. Stability and Reactivity		
Stability and Reactivity	The product is stable.	
Conditions of Instability	None known.	
Incompatibility with Various Substances	Reactive with oxidizing agents, acids. Avoid mixing with: Non-ferrous metal.	
Hazardous Decomposition Products	When exposed to fire: Produces normal products of combustion.	
Hazardous Polymerization	Will not occur.	

Section 11. Toxicological Information

Acute toxicityCorrosive.Effects of Chronic ExposureNone known.Other Toxic EffectsNot available.

Section 12. Ecological Information

Not available.

Section 13. Disposal Considerations

 Waste Information
 Undiluted product is regulated under environmental and transportation laws as a corrosive waste. Dispose of according to all federal, state and local regulations.

Section 14. Transport Information

DOT Classification DOT Proper Corrosive liquid, basic, inorganic, n.o.s. (Sodium hydroxide , Sodium silicate) **Shipping Name DOT Class** Class 8: Corrosive material UN3266 UN/NA **Packing Group** Ш **TDG** Classification **TDG Proper** Corrosive liquid, basic, inorganic, n.o.s. (Sodium hydroxide , Sodium silicate) **Shipping Name TDG Class** Class 8: Corrosive material

Packing Group ||


UN3266

PIN/NIP

Section 15. Regulatory Information

Reporting in this section	is based on ingredients disclosed in Section 2
US Regulations	
Federal	Clean Water Act (CWA) 311: Sodium Hydroxide CERCLA: Hazardous substances.: Sodium Hydroxide, 2-Butoxyethanol
State	New Jersey spill list: Sodium Hydroxide, 2-Butoxyethanol New Jersey: Sodium Hydroxide, 2-Butoxyethanol Massachusetts spill list: Sodium Hydroxide, 2-Butoxyethanol Massachusetts RTK: Sodium Hydroxide, 2-Butoxyethanol Pennsylvania RTK: Sodium Hydroxide, 2-Butoxyethanol
	This product is not subject to the reporting requirements under California's Proposition 65.
Registered Product Information	Not applicable.
Canadian Regulations	

Canadian NPRI Canadian NPRI: Alkylphenoxy Polyethoxyethanol, 2-Butoxyethanol.



Section 16.	Section 16. Other Information		
Other Special Considerations	Not available.		
Version	1		
as to the accuracy of	been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to le information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws		

and regulations.