

J-SHOP 650

National Fire Protection Association (NFPA)	Fire Hazard Health Reactivity 031	Hazardous Material Information System (HMIS)	<table><tr><td>Health</td><td>3</td></tr><tr><td>Fire Hazard</td><td>0</td></tr><tr><td>Reactivity</td><td>1</td></tr></table>	Health	3	Fire Hazard	0	Reactivity	1
Health	3								
Fire Hazard	0								
Reactivity	1								
Specific Hazard									
Protective Clothing		Emergency Overview	Clear Red. Liquid. See Section 9. DANGER. CORROSIVE. CAUSES EYE AND SKIN BURNS. HARMFUL OR FATAL IF SWALLOWED.						

Section 1. Chemical Product and Company Identification

Product Name	J-SHOP 650	Code	5145
Product Use	Industrial/Institutional: Floor care.	PMS#	433144
MSDS#	115145002	Validation Date	04/19/2000
U.S. Headquarters Johnson Wax Professional 8310 16th Street Sturtevant, Wisconsin 53177-0902 Phone: (888) 352-2249 MSDS Internet Address: www.jwp.com	Canadian Headquarters Johnson Wax Professional 100 Matheson Blvd. East, Suite 203 Mississauga, Ontario L4Z 2G7 Phone: (905) 755-0913 or (888) 746-5971	Print Date	04/20/2000
		Supersedes	04/12/2000.
		In Case of Emergency	(800) 851-7145

Section 2. Composition and Information on Ingredients

Ingredients	CAS #	% by Weight	Exposure Limits	LC50/LD50
Anionic Surfactant Sodium Hydroxide	1310-73-2	1-5 1-5	Not available. CEIL: 2 (mg/m ³) from OSHA (PEL) [United States] STEL: 2 (mg/m ³) from ACGIH (TLV) [United States]	Not available. Not available.
Sodium Xylene Sulfonate 1-Butoxypropanol	1300-72-7 5131-66-8	1-5 1-5	Not available. Not available.	Not available. ORAL (LD50): Acute: 5660 mg/kg [Rat]. DERMAL (LD50): Acute: 3100 mg/kg [Rabbit]. ORAL (LD50): Acute: 506 mg/kg [Rat]. DERMAL (LD50): Acute: 406 mg/kg [Rabbit]. VAPOR (LC50): Acute: 450 ppm 4 hours [Rat]. Not available.
2-Butoxyethanol	111-76-2	5-10	TWA: 120 (mg/m ³) from OSHA (PEL) [United States] TWA: 97 (mg/m ³) from ACGIH (TLV) [United States]	
Water	7732-18-5	60-100	Not available.	

Section 3. Hazards Identification

Routes of Entry	Skin contact. Eye contact.
Potential Acute Health Effects	
<i>Eyes</i>	Corrosive. May cause permanent damage including blindness.
<i>Skin</i>	Corrosive. May cause permanent damage.
<i>Inhalation</i>	May cause irritation and corrosive effects to nose, throat and respiratory tract.
<i>Ingestion</i>	Corrosive. May cause burns to mouth, throat, and stomach.
Medical Conditions Aggravated by Overexposure:	Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects.
See Toxicological Information (section 11)	

Section 4. First Aid Measures

Eye Contact	Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention immediately.
Skin Contact	Flush immediately with plenty of water for at least 15 minutes. Get medical attention immediately.
Inhalation	If breathing is difficult: Remove to fresh air. Get medical attention immediately.
Ingestion	Do not induce vomiting! Immediately drink plenty of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

Flammability of the Product	None known.
Flash Points	Not available.
Products of Combustion	None known.
Fire Fighting Media and Instructions	Extinguish with water spray or carbon dioxide, dry chemical powder or appropriate foam. Normal fire fighting procedure may be used.
Protective Clothing (Fire)	Put on appropriate personal protective equipment (see Section 8).
Special Remarks on Fire and Explosion Hazards	Corrosive material (See sections 8 and 10).

Section 6. Accidental Release Measures

Personal Precautions	Put on appropriate personal protective equipment (see Section 8).
Environmental Precautions and Clean-up Methods	In the event of major spillage: Use appropriate containment to avoid environmental contamination. Sweep or scrape up material. Place in suitable clean, dry containers for disposal by approved methods. Use a water rinse for final clean-up.

Section 7. Handling and Storage

Handling	Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Avoid breathing vapors or spray mists. Wash thoroughly after handling. Remove and wash contaminated clothing and footwear before re-use. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR INDUSTRIAL USE ONLY.
Storage	Store in a dry, cool and well-ventilated area. Protect from freezing. Keep container tightly closed. KEEP OUT OF REACH OF CHILDREN.

Section 8. Exposure Controls/Personal Protection

Engineering Controls	Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.
Personal Protection	
<i>Eyes</i>	Chemical splash goggles.
<i>Hands</i>	Chemical resistant gloves. Includes: Neoprene gloves. Rubber gloves.
<i>Respiratory</i>	If mists/vapors are not adequately controlled by ventilation, use appropriate respiratory protection to avoid over exposure. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.
<i>Feet</i>	Protective footwear.
<i>Body</i>	If major exposure is possible, wear suitable protective clothing and footwear.

Section 9. Physical and Chemical Properties

Physical State and Appearance	Liquid.
Odor	Characteristic.
Color	Clear Red.
pH	12 [Basic.]
Specific Gravity	1.04
Solubility in water	Complete.

Section 10. Stability and Reactivity

Stability and Reactivity	The product is stable.
Conditions of Instability	None known.
Incompatibility with Various Substances	Reactive with oxidizing agents, acids.
Hazardous Decomposition Products	When exposed to fire: Produces normal products of combustion.
Hazardous Polymerization	Will not occur.

Section 11. Toxicological Information

Acute toxicity	Corrosive.
Effects of Chronic Exposure	None known.
Other Toxic Effects	Not available.

Section 12. Ecological Information

Not available.

Section 13. Disposal Considerations

Waste Information	Undiluted product is regulated under environmental and transportation laws as a corrosive waste. Dispose of according to all federal, state and local regulations.
--------------------------	--

Section 14. Transport Information
DOT Classification

DOT Proper Shipping Name	Corrosive liquid, basic, inorganic, n.o.s. (Sodium hydroxide)
DOT Class	Class 8: Corrosive material
UN/NA	UN3266
Packing Group	II

TDG Classification
Section 15. Regulatory Information
Reporting in this section is based on ingredients disclosed in Section 2
US Regulations

Federal	Clean Water Act (CWA) 311: Sodium Hydroxide CERCLA: Hazardous substances.: Sodium Hydroxide, 2-Butoxyethanol
State	New Jersey spill list: Sodium Hydroxide, 2-Butoxyethanol New Jersey: Sodium Hydroxide, 2-Butoxyethanol Massachusetts spill list: Sodium Hydroxide, 2-Butoxyethanol Massachusetts RTK: Sodium Hydroxide, 2-Butoxyethanol Pennsylvania RTK: Sodium Hydroxide, 2-Butoxyethanol This product is not subject to the reporting requirements under California's Proposition 65.

Registered Product Information Not applicable.

Canadian Regulations

Canadian NPRI	Not applicable.
WHMIS Classification	Not applicable.
WHMIS Icon	
Registered Product Information	Not applicable.

Chemical Inventory Status	All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.
----------------------------------	---

Continued on Next Page

Section 16. Other Information

Other Special Considerations Not available.

Version 1

Notice to Reader

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.