

PRO STRIP

National Fire Protection Association (NFPA)



Hazardous Material Information System (HMIS)

Health	3	
Fire Hazard	0	
Reactivity	0	

Protective Clothing



Emergency Overview Colorless to light yellow. Liquid. See Section 9. DANGER. CORROSIVE. CAUSES EYE AND SKIN BURNS. HARMFUL OR FATAL IF SWALLOWED.

Section 1. Chemical Product and Company Identification				
Product Name	PRO STRIP		Code	3700 & 4158 & 4167
Product Use	Industrial/Institutional: Floor care. This product is intended to be diluted prior to use.		PMS#	452944
MSDS#	114156005		Validation Date	11/27/2001
U.S. Headquarters		Canadian Headquarters	Print Date	11/27/2001
Johnson Wax Professional 8310 16th Street		Johnson Wax Professional 100 Matheson Blvd. East, Suite 203	Supersedes	11/27/2001.
Sturtevant, Wisconsin 53177-0902 Phone: (888) 352-2249		Mississauga, Ontario L4Z 2G7 Phone: (905) 755-0913 or (888) 746-5971	In Case of Emergency	(800) 851-7145

Section 2. Composition and Information on Ingredients				
Ingredients	CAS#	% by Weight	Exposure Limits	LC50/LD50
Sodium Xylene Sulfonate	1300-72-7	1-5	Not available.	Not available.
Benzyl Alcohol	100-51-6	5-10	Not available.	ORAL (LD50): Acute: 1230 mg/kg [Rat]. DERMAL (LD50): Acute: 2000 mg/kg [Rabbit].
2-Butoxyethanol	111-76-2	10-30	OSHA (United States). TWA: 120 mg/m³ ACGIH (United States). TWA: 97 mg/m³	ORAL (LD50): Acute: 506 mg/kg [Rat]. DERMAL (LD50): Acute: 406 mg/kg [Rabbit]. VAPOR (LC50): Acute: 450 ppm 4 hour(s) [Rat].
Monoethanolamine	141-43-5	10-30	OSHA (United States). TWA: 8 mg/m³ STEL: 15 mg/m³ ACGIH (United States). TWA: 7.5 mg/m³ STEL: 15 mg/m³	ORAL (LD50): Acute: 1720 mg/kg [Rat]. DERMAL (LD50): Acute: 1018 mg/kg [Rabbit].
Water	7732-18-5	60-100	Not available.	Not available.

Section 3. Hazards Identification		
Routes of Entry	Eye contact. Skin contact Inhalation.	
Potential Acute Health Effects		
Eyes	Corrosive. May cause permanent damage including blindness.	
Skin	Corrosive. May cause permanent damage.	
Inhalation	May cause irritation and corrosive effects to nose, throat and respiratory tract.	
Ingestion	Corrosive. May cause burns to mouth, throat, and stomach.	
	Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects.	
See Toxicological Information	(section 11)	



Section 4. First	t Aid Measures
Eye Contact	Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention immediately.
Skin Contact	Flush immediately with plenty of water for at least 15 minutes. Get medical attention immediately.
Inhalation	If breathing is difficult: Remove to fresh air. Get medical attention immediately.
Ingestion	Do not induce vomiting! Immediately drink 1-2 glasses of water or milk. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures		
Flammability of the Product Flash Points	None known. CLOSED CUP: >93.3°C (200°F).	
Products of Combustion	None known.	
Fire Fighting Media and Instructions	Extinguish with water spray or carbon dioxide, dry chemical powder or appropriate foam. Normal fire fighting procedure may be used.	
Protective Clothing (Fire)	Put on appropriate personal protective equipment (see Section 8).	
Special Remarks on Fire and Explosion Hazards	Corrosive material (See sections 8 and 10).	

Section 6. Accidental Release Measures		
Personal Precautions	Put on appropriate personal protective equipment (see Section 8.).	
Environmental Precautions and Clean-up Methods	In the event of major spillage: Use appropriate containment to avoid environmental contamination. Sweep or scrape up material. Place in suitable clean, dry containers for disposal by approved methods. Use a water rinse for final clean-up.	

Section 7. Handling and Storage		
Handling	Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Avoid breathing vapors or spray mists. Wash thoroughly after handling. Remove and wash contaminated clothing and footwear before re-use. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR INDUSTRIAL USE ONLY. Use with adequate ventilation.	
Storage	Store in a dry, cool and well-ventilated area. Protect from freezing. KEEP OUT OF REACH OF CHILDREN.	

Section 8. Exposure Controls/Personal Protection		
0 0	Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.	
Personal Protection		
Eyes	Chemical splash goggles.	
Hands	Chemical resistant gloves. Includes: Neoprene gloves.	
	If mists/vapors are not adequately controlled by ventilation, use appropriate respiratory protection to avoid over exposure. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.	
Feet	Protective footwear.	
Body	If major exposure is possible, wear suitable protective clothing and footwear.	

Section 9. Physical and Chemical Properties		
Physical State and Appearance	Liquid.	
Odor	Glycol ether (Slight.)	
Color	Colorless to light yellow.	
pН	12.1 [Basic.]	
Specific Gravity	1.01	
Solubility in water	Complete.	



PRO STRIP

Section 10. Stability and Reactivity		
Stability and Reactivity	The product is stable.	
Conditions of Instability	None known.	
Incompatibility with Various Substances	Reactive with acids.	
Hazardous Decomposition Products	When exposed to fire: Produces normal products of combustion.	
Hazardous Polymerization	Will not occur.	

Section 11. Toxicological Information		
Acute toxicity	ORAL (LD50) Corrosive. DERMAL (LD50) Corrosive.	
Effects of Chronic Exposure	None known.	
Other Toxic Effects	None known.	

Section 12. Ecological Information

Not available.

Section 13. Disposal Considerations Waste Information Undiluted product is regulated under environmental and transportation laws as a corrosive waste. Dispose of according to all federal, state and local regulations.

Section 14. Transport Information DOT Classification			
TDG Classification			
TDG Proper Shipping Name TDG Class	Please refer to the Bill of Lading/receiving documents for up to date shipping information.		

Section 15. Regulatory Information

Reporting in this section is based on ingredients disclosed in Section 2

US Regulations

Federal CERCLA: Hazardous substances.: 2-Butoxyethanol

State New Jersey spill list: 2-Butoxyethanol

New Jersey: Monoethanolamine, 2-Butoxyethanol

Massachusetts spill list: Monoethanolamine, 2-Butoxyethanol

Massachusetts RTK: Monoethanolamine, 2-Butoxyethanol, Benzyl Alcohol

Pennsylvania RTK: Monoethanolamine, 2-Butoxyethanol, Benzyl Alcohol

This product is not subject to the reporting requirements under California's Proposition 65.

Registered Product Not applicable.

Information

Canadian Regulations

WHMIS Classification Class E: Corrosive liquid.

WHMIS Icon



Registered Product Not applicable.

Information



PRO STRIP

Chemical Inventory Status

All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory. All the ingredients are on the DSL list.

Section 16. Other Information		
Other Special Considerations	Not available.	
Version	1.01	

Notice to Reader

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.