

SNAPBACK SPRAY BUFF LIQUID

National Fire Protection Association (NFPA)	<div><div><div>Fire Hazard</div><div>Health</div><div>Reactivity</div><div>120</div></div></div>	Hazardous Material Information System (HMIS)	<table><tr><td>Health</td><td>1</td></tr><tr><td>Fire Hazard</td><td>2</td></tr><tr><td>Reactivity</td><td>0</td></tr></table>	Health	1	Fire Hazard	2	Reactivity	0
Health	1								
Fire Hazard	2								
Reactivity	0								
Specific Hazard									
Protective Clothing	None required.	Emergency Overview	Opaque Off-white. Liquid. See Section 9. CAUTION: May be mildly irritating to eyes. May be mildly irritating to skin. COMBUSTIBLE. Aspiration into the lungs may cause chemical pneumonitis.						

Section 1. Chemical Product and Company Identification

Product Name	SNAPBACK SPRAY BUFF LIQUID	Code	4116
Product Use	Industrial/Institutional: Floor care.	PMS#	433050
MSDS#	114110008	Validation Date	04/19/2000
U.S. Headquarters Johnson Wax Professional 8310 16th Street Sturtevant, Wisconsin 53177-0902 Phone: (888) 352-2249 MSDS Internet Address: www.jwp.com	Canadian Headquarters Johnson Wax Professional 100 Matheson Blvd. East, Suite 203 Mississauga, Ontario L4Z 2G7 Phone: (905) 755-0913 or (888) 746-5971	Print Date	04/19/2000
		Supersedes	04/12/2000.
		In Case of Emergency	(800) 851-7145

Section 2. Composition and Information on Ingredients

Ingredients	CAS #	% by Weight	Exposure Limits	LC50/LD50
Acrylic Polymers		1-5	Not available.	Not available.
Sorbitan Monooleate	1338-43-8	1-5	Not available.	Not available.
Alkylphenoxy Polyethoxyethanol	26027-38-3	1-5	Not available.	Not available.
Diethylene Glycol Ethyl Ether	111-90-0	1-5	Not available.	ORAL (LD50): Acute: 5540 to 9740 mg/kg [Rat].
Isoparaffinic Hydrocarbon Solvent	64742-48-9	10-30	Not available.	Not available.
Water	7732-18-5	60-100	Not available.	Not available.

Section 3. Hazards Identification

Routes of Entry	Inhalation. Skin contact. Eye contact.
Potential Acute Health Effects	
<i>Eyes</i>	May be mildly irritating to eyes.
<i>Skin</i>	May be mildly irritating to skin.
<i>Inhalation</i>	May be irritating to nose, throat, and respiratory tract.
<i>Ingestion</i>	Aspiration during ingestion or vomiting can result in serious lung damage. May be irritating to mouth, throat and stomach.
Medical Conditions Aggravated by Overexposure:	Persons with pre-existing skin disorders may be more susceptible to irritating effects.
See Toxicological Information (section 11)	

Section 4. First Aid Measures

Eye Contact	Flush immediately with plenty of water. Get medical attention if irritation occurs.
Skin Contact	Flush immediately with plenty of water. Get medical attention if irritation occurs.
Inhalation	If breathing is difficult: Remove to fresh air. Get medical attention.
Ingestion	Do not induce vomiting! Immediately drink plenty of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

Flammability of the Product	COMBUSTIBLE.
Flash Points	CLOSED CUP: 67°C (152.6°F).
Products of Combustion	None known.
Fire Fighting Media and Instructions	Use water spray to keep fire-exposed containers cool. Dry chemical, carbon dioxide.
Protective Clothing (Fire)	Put on appropriate personal protective equipment (see Section 8).
Special Remarks on Fire and Explosion Hazards	Material may burn in heat of fire.

Section 6. Accidental Release Measures

Personal Precautions	Put on appropriate personal protective equipment (see Section 8).
Environmental Precautions and Clean-up Methods	Eliminate all ignition sources. In the event of major spillage: Use appropriate containment to avoid environmental contamination. Take up with sand or other non-combustible material. Place in suitable clean, dry containers for disposal by approved methods.

Section 7. Handling and Storage

Handling	Avoid contact with skin and eyes. Do not taste or swallow. Avoid breathing vapors or spray mists. FOR INDUSTRIAL USE ONLY. Use only in well-ventilated areas.
Storage	Store in a dry, cool and well-ventilated area. Protect from freezing. Keep away from heat, sparks and flame. KEEP OUT OF REACH OF CHILDREN.

Section 8. Exposure Controls/Personal Protection

Engineering Controls	No special ventilation requirements. General room ventilation is adequate.
Personal Protection	
<i>Eyes</i>	No special protective clothing is required.
<i>Hands</i>	No special protective clothing is required.
<i>Respiratory</i>	No special protective clothing is required.
<i>Feet</i>	No special protective clothing is required.
<i>Body</i>	No special protective clothing is required.

Section 9. Physical and Chemical Properties

Physical State and Appearance	Liquid.
Odor	Mild.
Color	Opaque Off-white.
pH	7.9 to 8.8 [Basic.]
Specific Gravity	0.97
Solubility in water	Dispersible.

Section 10. Stability and Reactivity

Stability and Reactivity	The product is stable.
Conditions of Instability	Excessive heat.
Incompatibility with Various Substances	Reactive with oxidizing agents.
Hazardous Decomposition Products	When exposed to fire: Produces normal products of combustion.
Hazardous Polymerization	Will not occur.

Section 11. Toxicological Information

Acute toxicity ORAL (LD50) Greater than 5000 mg/kg (rat).

Effects of Chronic Exposure None known.

Other Toxic Effects Not available.

Section 12. Ecological Information

Not available.

Section 13. Disposal Considerations

Waste Information No special precautions. Dispose of according to all federal, state and local regulations.

Section 14. Transport Information

DOT Classification

Not regulated

TDG Classification

Not regulated

Section 15. Regulatory Information

Reporting in this section is based on ingredients disclosed in Section 2

US Regulations

Federal SARA 313 toxic chemical notification and release reporting: Diethylene Glycol Ethyl Ether
CERCLA: Hazardous substances.: Diethylene Glycol Ethyl Ether

State New Jersey spill list: Diethylene Glycol Ethyl Ether
New Jersey: Diethylene Glycol Ethyl Ether
Pennsylvania RTK: Diethylene Glycol Ethyl Ether

This product is not subject to the reporting requirements under California's Proposition 65.

Registered Product Information Not applicable.

Canadian Regulations

Canadian NPRI Canadian NPRI: Alkylphenoxy Polyethoxyethanol.

WHMIS Classification CLASS B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).

WHMIS Icon



Registered Product Information Not applicable.

Chemical Inventory Status All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Section 16. Other Information

Other Special Considerations MSDS Serial Range: 008-012

Version 1

Notice to Reader

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.