


SPITFIRE SC/TOP SECRET

National Fire Protection Association (NFPA)	<div><div><div>Fire Hazard</div><div>Health</div><div>Reactivity</div><div><div>0</div><div>3</div><div>0</div></div></div></div>	Hazardous Material Information System (HMIS)	<table><tr><td>Health</td><td>3</td></tr><tr><td>Fire Hazard</td><td>0</td></tr><tr><td>Reactivity</td><td>0</td></tr></table>	Health	3	Fire Hazard	0	Reactivity	0
Health	3								
Fire Hazard	0								
Reactivity	0								
Specific Hazard									
Protective Clothing		Emergency Overview	Clear Orange. Red. Liquid. See Section 9. DANGER. CORROSIVE. CAUSES EYE AND SKIN BURNS. HARMFUL OR FATAL IF SWALLOWED.						

Section 1. Chemical Product and Company Identification

Product Name	SPITFIRE SC/TOP SECRET	Code	48066
Product Use	Industrial/Institutional: Cleaning product. This product is intended to be diluted prior to use.	PMS#	433382
MSDS#	126438001	Validation Date	04/19/2000
<div>U.S. Headquarters</div> <div>Johnson Wax Professional</div> <div>8310 16th Street</div> <div>Sturtevant, Wisconsin 53177-0902</div> <div>Phone: (888) 352-2249</div> <div>MSDS Internet Address:</div> <div>www.jwp.com</div>	<div>Canadian Headquarters</div> <div>Johnson Wax Professional</div> <div>100 Matheson Blvd. East, Suite 203</div> <div>Mississauga, Ontario L4Z 2G7</div> <div>Phone: (905) 755-0913 or</div> <div>(888) 746-5971</div>	Print Date	04/20/2000
		Supersedes	04/12/2000.
		In Case of Emergency	(800) 851-7145

Section 2. Composition and Information on Ingredients

Ingredients	CAS #	% by Weight	Exposure Limits	LC50/LD50
Tetrasodium Salt of EDTA	64-02-8	1-5	Not available.	Not available.
Sodium Hydroxide	1310-73-2	1-5	CEIL: 2 (mg/m ³) from OSHA (PEL) [United States]	Not available.
Cocamide Diethanolamine	68603-42-9	1-5	STEL: 2 (mg/m ³) from ACGIH (TLV) [United States]	Not available.
2-Butoxyethanol	111-76-2	5-10	Not available.	ORAL (LD50): Acute: 506 mg/kg [Rat].
Water	7732-18-5	60-100	TWA: 120 (mg/m ³) from OSHA (PEL) [United States]	DERMAL (LD50): Acute: 406 mg/kg [Rabbit].
				VAPOR (LC50): Acute: 450 ppm 4 hours [Rat].
				Not available.

Section 3. Hazards Identification

Routes of Entry	Inhalation. Skin contact. Eye contact.
Potential Acute Health Effects	<div>Eyes</div> <div>Corrosive. May cause permanent damage including blindness.</div>
<div>Skin</div>	Corrosive. May cause permanent damage.
<div>Inhalation</div>	May cause irritation and corrosive effects to nose, throat and respiratory tract.
<div>Ingestion</div>	Corrosive. May cause burns to mouth, throat, and stomach.
<div>Medical Conditions</div> <div>Aggravated by Overexposure:</div>	Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects.
See Toxicological Information (section 11)	

Section 4. First Aid Measures

Eye Contact	Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention immediately.
Skin Contact	Flush immediately with plenty of water for at least 15 minutes. Get medical attention immediately.
Inhalation	If breathing is difficult: Remove to fresh air. Get medical attention immediately.
Ingestion	Do not induce vomiting! Immediately drink plenty of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

Flammability of the Product	None known.
Flash Points	Not available.
Products of Combustion	None known.
Fire Fighting Media and Instructions	Extinguish with water spray or carbon dioxide, dry chemical powder or appropriate foam. Normal fire fighting procedure may be used.
Protective Clothing (Fire)	Put on appropriate personal protective equipment (see Section 8.).
Special Remarks on Fire and Explosion Hazards	Corrosive material (See sections 8 and 10).

Section 6. Accidental Release Measures

Personal Precautions	Put on appropriate personal protective equipment (see Section 8.).
Environmental Precautions and Clean-up Methods	In the event of major spillage: Use appropriate containment to avoid environmental contamination. Sweep or scrape up material. Place in suitable clean, dry containers for disposal by approved methods. Use a water rinse for final clean-up.

Section 7. Handling and Storage

Handling	Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Avoid breathing vapors or spray mists. Wash thoroughly after handling. Remove and wash contaminated clothing and footwear before re-use. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR INDUSTRIAL USE ONLY.
Storage	Store in a dry, cool and well-ventilated area. Protect from freezing. Keep container tightly closed. KEEP OUT OF REACH OF CHILDREN.

Section 8. Exposure Controls/Personal Protection

Engineering Controls	Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.
Personal Protection	
<i>Eyes</i>	Chemical splash goggles.
<i>Hands</i>	Chemical resistant gloves. Includes: Neoprene gloves.
<i>Respiratory</i>	If mists/vapors are not adequately controlled by ventilation, use appropriate respiratory protection to avoid over exposure. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.
<i>Feet</i>	Protective footwear.
<i>Body</i>	If major exposure is possible, wear suitable protective clothing and footwear.

Section 9. Physical and Chemical Properties

Physical State and Appearance	Liquid.
Odor	Mild.
Color	Clear Orange. Red.
pH	13.4 [Basic.]
Specific Gravity	1.03
Boiling/Condensation Point	100°C (212°F)
Melting/Freezing Point	0°C (32°F)

Solubility in water

Complete.

Section 10. Stability and Reactivity

Stability and Reactivity The product is stable.

Conditions of Instability None known.

Incompatibility with Various Substances Reactive with oxidizing agents, acids.

Hazardous Decomposition Products When exposed to fire: Produces normal products of combustion. Toxic decomposition products include: Oxides of sodium.

Hazardous Polymerization Will not occur.

Section 11. Toxicological Information

Acute toxicity Corrosive.

Effects of Chronic Exposure None known.

Other Toxic Effects Not available.

Section 12. Ecological Information

Not available.

Section 13. Disposal Considerations

Waste Information Undiluted product is regulated under environmental and transportation laws as a corrosive waste. Dispose of according to all federal, state and local regulations.

Section 14. Transport Information

DOT Classification

DOT Proper Shipping Name	Corrosive liquid, basic, inorganic, n.o.s. (Sodium hydroxide , Tetrasodium Salt of EDTA)
DOT Class	Class 8: Corrosive material
UN/NA	UN3266
Packing Group	III

TDG Classification

TDG Proper Shipping Name	Corrosive liquid, basic, inorganic, n.o.s. (Sodium hydroxide , Tetrasodium Salt of EDTA)
TDG Class	Class 8: Corrosive material
PIN/NIP	UN3266
Packing Group	III
TDG Special Considerations	Previously included in a transborder consignment, classified in accordance with 49 CFR.

Section 15. Regulatory Information

Reporting in this section is based on ingredients disclosed in Section 2
US Regulations

Federal	Clean Water Act (CWA) 311: Sodium Hydroxide CERCLA: Hazardous substances.: Sodium Hydroxide, 2-Butoxyethanol
----------------	-----------------------------------------------------------------------------------------------------------------

State	New Jersey spill list: Sodium Hydroxide, 2-Butoxyethanol New Jersey: Sodium Hydroxide, 2-Butoxyethanol Massachusetts spill list: Sodium Hydroxide, 2-Butoxyethanol Massachusetts RTK: Sodium Hydroxide, 2-Butoxyethanol Pennsylvania RTK: Sodium Hydroxide, 2-Butoxyethanol
--------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

This product is not subject to the reporting requirements under California's Proposition 65.

Registered Product Information	Not applicable.
---------------------------------------	-----------------

Canadian Regulations

Continued on Next Page

Canadian NPRI Canadian NPRI: 2-Butoxyethanol.

WHMIS Classification CLASS E: Corrosive liquid.

WHMIS Icon



Registered Product Information Not applicable.

Chemical Inventory Status All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Section 16. Other Information

Other Special Considerations MSDS Serial Range: 001-002.

Version 1

Notice to Reader

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.