

Material Safety Data Sheet

UHS CLEANER

National Fire Protection Association (1	NFPA) Health	Hazard Reactivity	Hazardous I Information (HMIS)	System	Health Fire Hazard Reactivity	3 0 0
Protective Clothing	Specifi	c Hazard Emergency Overview	DANGER. CO	reen. Liquid. Se RROSIVE. CAU FATAL IF SWA	JSES EYE AND SKI	N BURNS.
	hemical Product and Co	ompany Identification	1	Colo	4005	
Product Name	UHS CLEANER			Code	4685	
Product Use	Industrial/Institutional: Floor care.			PMS#	433453	
MSDS#	114680003			Validation Date	. 12/7/2000	
U.S. Headquarters	U.S. Headquarters			Print Date	12/7/2000	
Johnson Wax Professional 8310 16th Street Sturtevant, Wisconsin 53177-0902 Phone: (888) 352-2249 MSDS Internet Address:		Johnson Wax Professio 100 Matheson Blvd. Ea Mississauga, Ontario L Phone: (905) 755-0913 (888) 746-5971	st, Suite 203 4Z 2G7	Supersedes <u>In Case of</u> <u>Emergency</u>	4/19/2000. (800) 851-7145	
www.jwp.com						

Ingredients	CAS #	% by Weight	Exposure Limits	LC50/LD50
Ammonium Hydroxide	1336-21-6	0.5-1.5	Not available.	ORAL (LD50): Acute: 350 mg/kg [Rat].
2-Butoxyethanol	111-76-2	1-5	TWA: 120 (mg/m ³) from OSHA (PEL) [United States] TWA: 97 (mg/m ³) from ACGIH (TLV) [United States]	ORAL (LD50): Acute: 506 mg/kg [Rat]. DERMAL (LD50): Acute: 406 mg/kg [Rabbit]. VAPOR (LC50): Acute: 450 ppm 4 hours [Rat].
Monoethanolamine	141-43-5	3-7	TWA: 8 STEL: 15 (mg/m ³) from OSHA (PEL) [United States] TWA: 7.5 STEL: 15 (mg/m ³) from ACGIH (TLV) [United States]	
Water	7732-18-5	60-100	Not available.	Not available.

Section 3. Hazards Identification

Routes of Entry

Inhalation. Skin contact. Eye contact.

Potential Acute Health Effects

Eyes Corrosive. May cause permanent damage including blindness.

Skin Corrosive. May cause permanent damage.

Inhalation May cause irritation and corrosive effects to nose, throat and respiratory tract.

Ingestion Corrosive. May cause burns to mouth, throat, and stomach.

Medical ConditionsIndividuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., mayAggravated by Overexposure:be more susceptible to irritating effects.

See Toxicological Information (section 11)

Johnson Wax PROFESSIONAL UHS CLEANER

Section 4. First Aid Measures

Eye Contact	Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention immediately.
Skin Contact	Flush immediately with plenty of water for at least 15 minutes. Get medical attention immediately.
Inhalation	If breathing is difficult: Remove to fresh air. Get medical attention immediately.
Ingestion	Do not induce vomiting! Immediately drink plenty of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

Flammability of the Product Flash Points	None known. None.
Products of Combustion	None known.
Fire Fighting Media and Instructions	Extinguish with water spray or carbon dioxide, dry chemical powder or appropriate foam. Normal fire fighting procedure may be used.
Protective Clothing (Fire)	Put on appropriate personal protective equipment (see Section 8).
Special Remarks on Fire and Explosion Hazards	Corrosive material (See sections 8 and 10).

Section 6. Accidental Release Measures

Personal Precautions	Put on appropriate personal protective equipment (see Section 8).
Environmental Precautions and Clean-up Methods	In the event of major spillage: Use appropriate containment to avoid environmental contamination. Sweep or scrape up material. Place in suitable clean, dry containers for disposal by approved methods. Use a water rinse for final clean-up.

Section 7. Handling and Storage

Handling	Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Avoid breathing vapors or spray mists. Wash thoroughly after handling. Remove and wash contaminated clothing and footwear before re-use. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR INDUSTRIAL USE ONLY.
Storage	Store in a dry, cool and well-ventilated area. Protect from freezing. Keep container tightly closed. KEEP OUT OF REACH OF CHILDREN.

Section 8. Exposure Controls/Personal Protection

0 0	Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.
Personal Protection	
Eyes	Chemical splash goggles.
Hands	Chemical resistant gloves. Includes: Rubber gloves. Neoprene gloves. Butyl gloves.
	If mists/vapors are not adequately controlled by ventilation, use appropriate respiratory protection to avoid over exposure. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.
Feet	Protective footwear.
Body	If major exposure is possible, wear suitable protective clothing and footwear.

Section 9. Physical and Chemical Properties

Physical State and Appearance	Liquid.
Odor	Ammoniacal.
Color	Clear Blue. Green.
рН	11.2 to 12 [Basic.]
Specific Gravity	1
Melting/Freezing Point	<0°C (32°F)
Solubility in water	Complete.

Johnson wax PROFESSIONAL UH

UHS CLEANER

Section 10. Stability and Reactivity			
Stability and Reactivity	The product is stable.		
Conditions of Instability	None known.		
Incompatibility with Various Substances	Reactive with acids.		
Hazardous Decomposition Products	When exposed to fire: Produces normal products of combustion. Toxic decomposition products include: Oxides of nitrogen.		
Hazardous Polymerization	Will not occur.		

Section 11. Toxicological Information

Acute toxicityCorrosive.Effects of Chronic ExposureNone known.Other Toxic EffectsNone known.

Section 12. Ecological Information

Not available.

Section 13. Disposal Considerations

Waste Information

Undiluted product is regulated under environmental and transportation laws as a corrosive waste. Dispose of according to all federal, state and local regulations.

Section 14. Transport Information

DOT	Classification
-----	----------------

DOLC	lassification	
	DOT Proper Shipping Name	Corrosive liquid, basic, organic, n.o.s. (Monoethanolamine , Ammonium hydroxide)
	DOT Class	Class 8: Corrosive material
	UN/NA	UN3267
	Packing Group	II
TDG (Classification	
	TDG Proper Shipping Name	Corrosive liquid, basic, organic, n.o.s. (Monoethanolamine , Ammonium hydroxide)
	TDG Class	Class 8: Corrosive material
	PIN/NIP	UN3267
1	Packing Group	II

Section 15. Regulatory Information

•	-		
Reporting in this section is based on ingredients disclosed in Section 2			
US Regulations			
Federal	CERCLA: Hazardous substances.: 2-Butoxyethanol		
State	New Jersey spill list: 2-Butoxyethanol New Jersey: Monoethanolamine, 2-Butoxyethanol Massachusetts spill list: Monoethanolamine, 2-Butoxyethanol Massachusetts RTK: Monoethanolamine, 2-Butoxyethanol Pennsylvania RTK: Monoethanolamine, 2-Butoxyethanol		
	This product is not subject to the reporting requirements under California's Proposition 65.		
Registered Product Information	Not applicable.		
Canadian Regulations			
Canadian NPRI	Canadian NPRI: 2-Butoxyethanol.		
WHMIS Classification	CLASS E: Corrosive liquid.		



UHS CLEANER



Registered Product Not applicable.

WHMIS Icon

 Information

 Chemical Inventory Status
 All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Section 16. Other Information		
Other Special Considerations	Not available.	
Version	1.01	
Notice to Reader		

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.