MSDS

Material Safety Data Sheet Conforms to ANSI Z-400.1-1993 4010

Las Vegas, NV 89118 (800) 293-4698

1 Chemical Product and Company Identification

Product:Penetrating Stone Sealer Classification: Floor Care F43

2 Composition/Information on Hazardous Ingredients

MaterialCAS#% OSHA(PEL)TLV(ppm)OtherPotassium Methyl Siliconate31795-24-1<10</td>N/AN/AN/A

3 Hazards Identification

Emergency Overview: May cause skin and eye irritation. Avoid skin and eye contact.

Contact with Eyes: Mild irritant.

Contact with Skin: Contact with concentrate may be an irritant for sensitive skin.

Skin Absorption: No data.

Ingestion Symptoms: Irritation, nausea, vomiting and diarrhea.

Inhalation Symptoms: N/A

Chronic Effects: No data.

It is important to determine whether exposure is to concentrated or dilute product. The information in this document is intended to deal with exposure to concentrated product. Generally, exposure to diluted product will result in substantially less risk of injury than described herein.

4 First Aid Measures

Eyes: If eyes are contacted, flush with water for 15 minutes. If irritation persists seek medical attention.

Skin: If skin is contacted, wash affected area with soap and water. If irritation persists, seek medical attention.

Inhalation: If discomfort is experienced after prolonged exposure to mists/vapors, remove to fresh air. If breathing is difficult,

give oxygen and seek medical attention.

Ingestion: If ingested, do NOT induce vomiting. Give moderate amounts of water to wash out mouth area and dilute

remaining residue. Seek medical attention.

5 Fire Fighting Measures

Flash Point(F° TCC): >200°F Flammable Limits: LEL No Data UEL No Data

Auto Ignition Temperature: No Data

Extinguishing Media: Water Spray, Foam, Carbon Dioxide, Dry Chemical

Special Fire Fighting Procedures:

Firefighters should wear a positive pressure NIOSH approved self-contained breathing apparatus.

Unusual Fire and Explosion Hazards:

Containers exposed to heat from fires should be cooled with water fog to prevent container rupture.

6 Accidental Release Measures

Large Spills (55 gallons or more):

Wear rubber boots, gloves and appropriate protective clothing. Shut off source of leak if safe to do so. Dike and contain spill.

Small Spills:

Mop up spill and rinse area.

7 Handling and Storage

Handling: Keep out of reach of children. Follow appropriate hygiene practices.

Storage: Store in a cool, dry place.

8 Exposure Controls/Personal Protection

Ventilation and Engineering Controls:

Local exhaust

Respiratory Protection:

If used according to directions respirator not required.

Protective Gloves:

Rubber Gloves

Eye Protection:

Chemical Splash Goggles

Other Protective Equipment:

3/6/	2006	0001	4010

Boiling Point(F°)>212°F	Solubility	in WaterSoluble	Odor: Neutral			
Specific Gravity:1.02	Volatiles(%	by Wt.)95	pH : 11.5 - 12.5			
Appearance:Clear	Vapor	Density:>1	VOC: N/A			
Evaporation Rate:<1	Vapor I	Pressure:<17 mm Hg	Freezing Point(F°)≿32°F			
	> means less	than < means greater tha	n			
			vary from sample to sample. specific lot or as specific items.			
10 Stability and Reactivity						
Stability: Stable Conditions to Avoid: Temp. Extremes						
Materials to Avoid: Strong Oxidizers						
Hazardous Decomposition Products:						
Oxides of carbon and nitrogen						
Hazardous Polymerization:						
Will Not Occur						
11 Toxicological Information						
No Toxicology Information is available.						
12 Ecological Information						
No data available.						
13 Disposal Considerations						
Waste Disposal Method: Dispose of waste in accordance with federal, state and local regulations						
14 Transport Information						
HAZMAT: No Hazard	Code: N/A	ID Number: N/A	Hazard Class: N/A			
Hazardous Division: None			Packaging Group:N/A			
Hazardous Contents:None						
15 Regulatory Information						
Proposition 65: Not Listed.						
1 Toposition 53. Not Listed.						
EPA: No						
16 Other Information						
HMIS/NFPA Hazard Rating: Health 1 Flammability 0 Reactivity 0						
The information contained herein is based on the data available to us. It is believed to be correct. No warranty, expressed or implied, is made regarding the accuracy of this data or the results to be obtained from the use thereof. For further information consult distributor, Brady Industries, HQ						
MSDS Approval Date: 2/28/2006						
3/6/2006 0001 4010						
3/6/2006 0001 4010			Penetrating Stone Sealer Page 3 of 3			

9 Physical and Chemical Properties