

DIVER-SLIP

MSDS ID: 00226

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: DIVER-SLIP

Product Descriptor: ASPHALT RELEASE AGENT

MANUFACTURER: JOHNSON DIVERSEY, INC.
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

EMERGENCY PHONE NUMBER: (800)851-7145

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
DODECYLBENZENE SULFONIC ACID	27176-87-0	1 - 5%	None est.	
2-BUTOXY ETHANOL	111-76-2	1 - 5%	TLV 20 (Skin) PEL 50 (Skin)	PPM PPM

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

CORROSIVE MATERIAL - Causes severe burns to skin and eyes. Harmful if swallowed. Do not contact eyes, skin or clothing. Avoid breathing any dust, spray mist or vapors in spill area. Wash thoroughly after handling product. Wear eye protection, clothing and footwear to prevent skin contact.

POSSIBLE ROUTES OF ENTRY: All Routes of Entry/Exposure

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Severe burns or irritation with pain, redness, swelling, and blurred or impaired vision. SKIN: Burns, blisters or rash with pain and swelling. INGESTION: Burns or irritation to mouth, throat with pain, nausea and vomiting. INHALATION: Spray or mist causes severe irritation with pain, choking, and breathing difficulty.

CHRONIC: Same as acute effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis or sensitive skin.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes, skin and respiratory tract.

IV. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Hold eyelids apart to completely flush all chemicals from entire eye surface. Get immediate medical attention.

SKIN: Flush thoroughly with plenty of water. Wash with mild soap and water. Remove contaminated clothes and shoes and clean before reuse. Get medical attention for any painful, red or injured skin.

INGESTION: If swallowed, rinse mouth with water. Dilute by drinking several glasses of water. DO NOT induce vomiting. If patient vomits, rerinse mouth. Get immediate medical attention. NOTE: Never give fluids by mouth to an unconscious person.

DIVER-SLIP

MSDS ID: 00226

IV. FIRST AID MEASURES (Cont.)

INHALATION: If inhaled, move to fresh air. If patient is not breathing, give artificial respiration. If breathing is difficult, give oxygen under the direction of trained personnel or a physician. Get immediate medical attention.

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): NONE FLAME EXTENSION: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: N/A UEL: N/A
UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Toxic fumes or vapor may form during fire.
EXTINGUISHING MEDIA: Water spray, CO2, foam or dry powder.
FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus SCBA) in fire area.
SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:
Contain spill. Wear protective clothing. Soak up or absorb liquid on suitable absorbent material. Collect and place in chemical waste container. Dispose of in accordance with local, State and Federal regulations. Flush spill area with water.
This product does not contain a reportable quantity (RQ) under CERCLA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Store in a cool, dry area, keep away from acids. Keep container closed when not in use. Wear protective gear when handling or using. Do not pressurize container to empty.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Chemical goggles if contact or splash hazard exists. Face shields.
PROTECTIVE GLOVES: Alkali resistant.
RESPIRATORY PROTECTION: Use NIOSH/MSHA approved respirator where TLV/PEL may be exceeded.
OTHER PROTECTIVE CLOTHING/EQUIPMENT: Rubber boots and chemical resistant apron if contact or splash hazard exists.
ENGINEERING CONTROLS:
VENTILATION: Good general ventilation should be sufficient to control airborne levels.

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: CLEAR, LIGHT YELLOW LIQUID, SLIGHT ODOR.

BOILING POINT (DEG F): 212

FREEZING POINT: 0 C

SPECIFIC GRAVITY/BULK DENSITY: 1.0300

Page	3 of 4
Revised	2/02/04
Replaces	8/14/03
Printed	2/03/04

MSDS ID: 00226

pH: 13.4	pH 1% SOLUTION: 11.92
VOLATILE BY VOLUME: 92	
SOLUBILITY IN WATER: Soluble	
VAPOR PRESSURE(mmHg): 17.5	at 20 C
	VAPOR DENSITY: 17.3

CHEMICAL STABILITY: Product stable.
INCOMPATIBILITY WITH OTHER MATERIALS: Acids; Oxidizing agents
HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms; oxides of sulfur; oxides of carbon
HAZARDOUS POLYMERIZATION: None known.

TOXICOLOGICAL TESTING: Toxicological testing has not been performed on the product. Listed below is the available toxicology test data for components of the product.

Sodium Tripolyphosphate:		
Acute Oral LD50 (rat)	4100	mg/kg
2-Butoxy Ethanol:		
Acute Oral LD50 (rat)	1.48	gm/kg
Acute Oral LD50 (mouse)	1.2	gm/kg
Acute Oral LD50 (rabbit)	0.32	gm/kg
Acute Oral LD50 (guinea pig)	1.2	gm/kg
Acute Dermal LD50 (rabbit)	400	mg/kg
Sodium Silicate:		
Acute Oral LD50 (rat)	1.1-1.6	gm/kg
Acute Oral LD50 (mouse)	1100	mg/kg

ECOTOXICITY TEST DATA:
No data available.
ENVIRONMENTAL FATE: No data available.

RCRA REGULATED: CONCENTRATED PRODUCT WOULD BE CONSIDERED D002-CORROSIVE, IF
DECLARED HAZARDOUS WASTE.
Spent or excess product is hazardous waste. Do not discharge to sewer or
environment. Arrange disposal through a licensed disposal company or treat by
special Waste Disposal Sheet. Recycle or dispose of containers by product
labeling or governmental regulations.

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 8/14/03
Printed 2/03/04

DIVER-SLIP**MSDS ID: 00226**

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: 2-BUTOXY ETHANOL @ 1.5% IS A HAZARDOUS AIR POLLUTANT UNDER THE GENERAL LISTING OF GLYCOL ETHERS.

VOC CONTENT (EPA Method 24A): % VOC: 1.5 Lb/Gal VOC: 0.13

CERCLA/EPCRA:

Section 313 Toxic Chemicals:

2-BUTOXY ETHANOL @ 1.5% IS SARA REPORTABLE AS A GLYCOL ETHER.

SARA Section 311/312:

ACUTE: YES CHRONIC: NO FIRE: NO REACTIVITY: NO
SUDDEN RELEASE OF PRESSURE: NO

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 3 FIRE: 0 REACTIVITY: 0
PERSONAL PROTECTIVE EQUIPMENT: D

NFPA RATING: HEALTH: 3 FIRE: 0 REACTIVITY: 0 SPECIAL: ALKALINE

STATE RIGHT-TO-KNOW INFORMATION:

WATER - CAS #7732-18-5

SODIUM SILICATE - CAS #1344-09-8

2-BUTOXYETHANOL - CAS #111-76-2

SODIUM TRIPOLYPHOSPHATE - CAS #7758-29-4

DODECYLBENZENE SULFONIC ACID - CAS #27176-87-0

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

Disclaimer: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.