
MATERIAL SAFETY DATA SHEET

Page 1 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

DUJEL 1200**MSDS ID: 00261**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: DuJEL 1200

Product Descriptor: ALKALINE GEL

MANUFACTURER: JOHNSON DIVERSEY, INC.
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

EMERGENCY PHONE NUMBER: (800)851-7145

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
ISOPROPYL ALCOHOL	67-63-0	< 1.0 %	TWA 400 STEL 500	PPM
SODIUM HYDROXIDE	1310-73-2	5 - 15%	TLV-C 2	MG/M3

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

CORROSIVE MATERIAL-Causes severe burns to skin and eyes. Harmful if swallowed. Do not contact eyes, skin or clothing. Avoid breathing any dust, spray mist or vapors in spill area. Wash thoroughly after handling product. Wear eye protection, clothing and footwear to prevent skin contact.

POSSIBLE ROUTES OF ENTRY: Ingestion, Skin and Inhalation.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Severe burns or irritation with pain, redness, swelling, and blurred sight. SKIN: Burns, blisters or rash with pain and swelling. INGESTION: Burns or irritation to mouth, throat with pain, nausea and vomiting. INHALATION: Spray or mist causes pain, choking, and breathing difficulty.

CHRONIC: None known.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis and sensitive skin.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes and skin.

IV. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Hold eyelids apart to completely flush all chemicals from entire eye surface. Gently flush contact lens from eye surface if easily removed. Get immediate medical attention.

SKIN: Promptly flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and footwear. Launder contaminated clothing and discard or thoroughly clean shoes before reuse. Get medical attention for painful, red or injured skin areas.

INGESTION: If swallowed, rinse mouth with water. Dilute by drinking several glasses of water. DO NOT induce vomiting. If patient vomits, rerinse mouth with water. Get prompt medical attention. NOTE:

MATERIAL SAFETY DATA SHEET

Page 2 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

DUJEL 1200**MSDS ID: 00261**

IV. FIRST AID MEASURES (Cont.)

Never give fluids by mouth to an unconscious person.
INHALATION: If inhaled, move to fresh air. If patient is not breathing, give artificial respiration. If breathing is difficult, give oxygen under the direction of trained personnel or a physician. Get medical attention.

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): 135 F **FLAME EXTENSION:** N/A
FLAMMABLE LIMITS IN AIR BY VOLUME: **LEL:** ND **UEL:** ND
UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Toxic fumes or vapor may form during fire.
EXTINGUISHING MEDIA: Water spray, CO2, foam or dry powder.
FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus (SCBA) in fire area.
SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:
Contain spill. Absorb with sand or clay. Collect material and place in suitable waste container. Neutralize solids and spill area with dilute mineral acids or bicarbonate of soda. Dispose of by environmental regulations.
The Reportable Quantity (RQ) of Sodium Hydroxide, CAS #1310-73-2 is 1480 gallons or 13,333 lbs.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Store in a cool, dry area away from acids. Keep container closed when not in use. Wear protective gear when handling or using. Do not pressurize container to empty.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Chemical goggles if contact or splash hazard exists. Eye wash in use area.
PROTECTIVE GLOVES: Alkali resistant.
OTHER PROTECTIVE CLOTHING/EQUIPMENT: Rubber boots, chemical apron and safety shower in use area if contact or splash hazard exists.
ENGINEERING CONTROLS:
VENTILATION: Normal room ventilation should be sufficient to control airborne levels.

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Viscous yellow liquid, mild odor.

BOILING POINT (DEG F): >200 **FREEZING POINT:** ND
SPECIFIC GRAVITY/BULK DENSITY: 1.08
pH: 13.8 **pH 1% SOLUTION:** 12.1

MATERIAL SAFETY DATA SHEET

Page 3 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

DUJEL 1200

MSDS ID: 00261

IX. PHYSICAL AND CHEMICAL PROPERTIES (Cont.)

VOLATILE BY VOLUME: 88.5

SOLUBILITY IN WATER: Soluble

VAPOR PRESSURE(mmHg): ND at ND VAPOR DENSITY: ND

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: Strong acids, strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms oxides of carbon and nitrogen.

HAZARDOUS POLYMERIZATION: None known.

XI. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL TESTING: Contains Corrosive and Irritating alkaline chemicals.
See Section II for amounts and identity. Acute toxicology tests are listed below.

TOXICITY TEST DATA:

Sodium hydroxide: Acute Oral LD50 (rat) - 500 mg/kg (RTECS)
Acute Skin LD50 (rabbit) - 1350 mg/kg (MSI)

XII. ECOLOGICAL INFORMATION

When handled and disposed of as directed, this product should not cause adverse effects in the environment.

ECOTOXICITY TEST DATA:

No data available.

ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: RCRA Regulated Hazardous Waste - Corrosivity Characteristic D002.

Adjust pH of diluted product and discharge to industrial sewer. Use product in container until empty. Triple rinse container with water and add to process. Recycle or dispose of container by product labeling or governmental regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: Contains no hazardous air pollutants.

VOC CONTENT (EPA Method 24A): % VOC: <1 Lb/Gal VOC: <0.08

CERCLA/EPCRA:

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

DUJEL 1200

MSDS ID: 00261

XV. REGULATORY INFORMATION (Cont.)

Section 313 Toxic Chemicals:

None

SARA Section 311/312:

ACUTE: YES CHRONIC: NO FIRE: NO REACTIVITY: NO
SUDDEN RELEASE OF PRESSURE: NO

LISTED CARCINOGEN: None

NTP: No IARC: No OSHA: No

HMIS RATINGS: HEALTH: 3 FIRE: 2 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: D

NFPA RATING: HEALTH: 3 FIRE: 2 REACTIVITY: 0 SPECIAL: Corrosive

STATE RIGHT-TO-KNOW INFORMATION:

Proprietary

SODIUM HYDROXIDE - CAS #1310-73-2

ISOPROPANOL - CAS #67-63-0

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

Disclaimer: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.