1 of 4 Page Revised 2/02/04 Replaces 8/12/03

Printed

2/03/04

MSDS ID: 00262

DUJEL 700

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: DUJEL 700

Product Discriptor: NON-CAUSTIC GEL CLEANER

JOHNSONDIVERSEY, INC. MANUFACTURER: EMERGENCY PHONE NUMBER: (800)851-7145

> 3630 E. KEMPER ROAD CINCINNATI, OH. 45241

II. HAZARDOUS COMPONENTS			
Component Name	CAS Number	%	Exposure Limits Units
DIPROPYLENE GLYCOL METHYL ETHER	34590-94-8	5 - 15%	TWA 606 STEL 909 MG/M3 (skin)
TRIETHANOLAMINE	102-71-6	1 - 5%	TWA 5 MG/M3

#### III. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW:

WARNING-Contains chemicals that may cause irritation to eyes and skin. May be harmful if swallowed. Wear eye protection such as goggles or side shield safety glasses, clothing and rubber gloves to prevent prolonged skin contact. Wash after handling. Contain spills and runoff which may harm the environment. POSSIBLE ROUTES OF ENTRY: Skin and Inhalation.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Severe irritation with redness, pain and swelling. SKIN: ACUTE:

Dryness or itching may develop with pain and redness. INGESTION: If

swallowed, gastric distress, diarrhea and vomiting may occur.

CHRONIC: None known.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis and sensitive

skin.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes

#### IV. FIRST AID MEASURES

Immediately flush with plenty of water. Get medical attention. EYES:

Rinse off product and wash with mild soap and water. SKIN:

If swallowed, drink several glasses of water. Do not induce INGESTION:

vomiting. Consult a physician or poison control center. NOTE:

Never give fluids by mouth to an unconscious person.

INHALATION: Remove to fresh air. If breathing difficulties continue, get

medical attention.

DUJEL 700

Page 2 of 4 Revised 2/02/04 Replaces 8/12/03

Printed 2/03/04

MSDS ID: 00262

# V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): None FLAME EXTENSION: N/A FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: NA UEL: NA

UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Toxic fumes or vapor may form during fire.

EXTINGUISHING MEDIA: Water, water spray, CO2, foam or dry powder.

FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure

breathing apparatus (SCBA) in fire area.

SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

# VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:

Contain spill. Wear protective clothing. Soak up or absorb liquid on sand or clay. Collect and place in chemical waste container. Dispose of in accordance with governmental regulations. Flush spill area with water.

This product does not contain a reportable quantity (RQ) under CERCLA.

### VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Store in a cool, dry area away from acids. Keep container closed when not in use. Wear protective gear when handling or using. Do not pressurize container to empty.

### VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Safety glasses with side shields. Eye wash in use area if contact or splash hazard exists.

PROTECTIVE GLOVES: Alkali resistant.

RESPIRATORY PROTECTION: Not normally required.

OTHER PROTECTIVE CLOTHING/EQUIPMENT: Protective clothing to cover exposed skin if contact or splash hazard exists.

ENGINEERING CONTROLS:

MECHANICAL VENTILATION: Normal room ventilation should be sufficient to

control airborne levels.

LOCAL VENTILATION: Not usually required.

# IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear to light yellow viscous liquid; mild odor.

BOILING POINT (DEG F): 212 FREEZING POINT: ND

SPECIFIC GRAVITY/BULK DENSITY: 1.054

pH: 10.5 pH 1% SOLUTION: 9.5

VOLATILE BY VOLUME: 90

SOLUBILITY IN WATER: Soluble

VAPOR PRESSURE(mmHg): ND at ND VAPOR DENSITY: ND

DUJEL 700

Page 3 of 4 Revised 2/02/04 Replaces 8/12/03

Printed

2/03/04

MSDS ID: 00262

# X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: Acids

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and dioxide.

HAZARDOUS POLYMERIZATION: None known.

#### XI. TOXICOLOGICAL INFORMATION

No data available. TOXICITY TEST DATA: No data available.

#### XII. ECOLOGICAL INFORMATION

ECOTOXICITY DATA: When handled and disposed of as directed, this product

should not cause adverse effects in the environment.

ECOTOXICITY TEST DATA: No data available. ENVIRONMENTAL FATE: No data available.

# XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Not RCRA Regulated Hazardous Waste.

Discharge diluted product to industrial sewer. Use product in container until empty. Triple rinse container with water and add to process. Recycle or dispose of container by product labeling or governmental regulations.

# XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

# XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: Contains no hazardous air pollutants.

Lb/Gal VOC: 0.787 VOC CONTENT (EPA Method 24A): % VOC: 8.95

CERCLA/EPCRA:

Section 313 Toxic Chemicals: None

SARA Section 311/312:

CHRONIC:NO FIRE:NO REACTIVITY:NO ACUTE:YES

SUDDEN RELEASE OF PRESSURE: NO

LISTED CARCINOGEN: None

IARC: No NTP: No OSHA: No

HMIS RATINGS: HEALTH: 2 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: B

NFPA RATING: HEALTH: 2 FIRE: 0 REACTIVITY: 0 SPECIAL:-

STATE RIGHT-TO-KNOW INFORMATION:

WATER - CAS #7732-18-5

DIPROPYLENE GLYCOL METHYL ETHER - CAS #34590-94-8

TRIETHANOLAMINE - CAS #102-71-6

4 of 4 Page Revised 2/02/04 Replaces 8/12/03

Printed

2/03/04

MSDS ID: 00262

DUJEL 700

XV. REGULATORY INFORMATION (Cont.)

TETRASODIUM EDTA - CAS #64-02-8 ACRYLATE POLYMER - CAS #PROPRIETARY CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

# XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.