

# MATERIAL SAFETY DATA SHEET



MSDS ID: 0031

I - PRODUCT IDENTIFICATION AND USE

PRODUCT NAME: SU 340 LIQUID CHLORINE SANITIZER

**USE:** Sanitizer/Disinfectant

SUPPLIER: EMERGENCY PHONE:

JohnsonDiversey Canada, Inc.

2401 Bristol Circle

Oakville Ontario, L6H 6P1, Canada

1-800-668-7171

WHMIS CLASSIFICATION: D2B E TRADE NAME / SYNONYMS: not applicable
CHEMICAL FAMILY: Chlorinated alkali CHEMICAL NAME: Sodium hypochlorite solution

**II - HAZARDOUS INGREDIENTS** 

HAZARDOUS INGREDIENT % w/w CAS # LD50 / LC50 Route / Species

Sodium hypochlorite (10.5%-solution) 60-100 007681-52-9 LD50 4445 mg/kg oral/rat

#### **III - HANDLING AND DISPOSAL PROCEDURES**

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: Natural Rubber, Neoprene or Nitrile Eye: safety goggles Footwear: not applicable

**Respiratory:** If mists are generated, use NIOSH approved **Other:** impermeable apron

mask

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Avoid eye and skin contact.

**VENTILATION REQUIREMENTS:** mechanical exhaust

INCOMPATIBILITY (Material to Avoid): Acids, oxidizable materials, ammonia, urea, other nitrogenous materials, and metals.

SPILL PROCEDURES: Contain the spill. Do not allow the spilled product to go to drain. Neutralize with sodium sulfite, sodium bisulphite,

or dilute hydrogen peroxide. Mop up or soak up with absorbent clay for disposal. Wash spill area with large

volumes of water.

WASTE DISPOSAL: Dispose according to municipal, provincial and federal regulations.

STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container. Keep away from oxidizable materials.

## **IV - PHYSICAL PROPERTIES**

APPEARANCE / ODOUR: Clear, yellow-green liquid - chlorine odour

S.G. / BULK DENSITY(g/cc): 1.18 pH: (1% solution): 10.8

VAPOUR PRESSURE (mmHg): 17.5 VAPOUR DENSITY (air=1): not applicable

ODOUR THRESHOLD: not available BOILING POINT: approx. 100°C

FREEZING POINT: -25°C PERCENT VOLATILE: 85%

SOLUBILITY IN WATER: soluble EVAPORATION RATE (water=1): not available

#### **V - TOXICOLOGICAL PROPERTIES**

## **EFFECTS OF ACUTE EXPOSURE TO MATERIAL:**

EYES: Corrosive. May cause severe irritation. May cause permanent damage if not treated promptly.

SKIN: Corrosive. May cause severe irritation. May cause temporary or permanent damage if not treated promptly.

INGESTION: Corrosive. May cause severe irritation of the digestive tract. May cause permanent damage if not treated promptly. May lead

to convulsions, coma and death.

INHALATION: May cause irritation of the nose and throat, coughing, difficulty breathing; may cause pulmonary edema.

LD50 (calculated): 4445 mg/kg LC50 (calculated): not available OTHER TOXIC EFFECTS: TLV - TWA (CI2) 0.5 ppm; STEL (CI2) 1.0 ppm EFFECTS OF CHRONIC none known **EXPOSURE TO MATERIAL: VI - FIRST AID MEASURES** EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eye lids open while rinsing. Contact a physician immediately. SKIN: Flush affected area thoroughly with water. If irritation persists, contact a physician. INGESTION: Drink large volumes of water . Never give anything by mouth to an unconscious person. Do not induce vomiting. Contact a physician immediately. INHALATION: Remove patient to fresh air. If breathing difficulty occurs, get medical attention. VII - FIRE AND EXPLOSION DATA FLAMMABLE: No FLASH POINT, °C: not applicable **AUTO IGNITION TEMPERATURE,°C:** N/Ap **EXTINGUISHING MEDIA:** Water [X] Dry Chemical [X] Carbon Dioxide [X] Foam [X] Other [ ] SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus and full protective equipment. **HAZARDOUS COMBUSTION PRODUCTS:** chlorine gas **EXPLOSIVE SENSITIVITY TO:** not applicable **VIII - REACTIVITY DATA** STABILITY: Stable [ ] Unstable [X] CONDITIONS TO AVOID: Decomposes slowly. Do not expose to temperatures above 40°C (104°F), sunlight, or metals. INCOMPATIBILITY (Material to Avoid): Acids, oxidizable materials, ammonia, urea, metals. HAZARDOUS DECOMPOSITION PRODUCTS: Chlorine gas is released by contact with acids; oxygen is released by contact with metals. Contact with ammonia and urea produce nitrogen gas and chloramines. Contact with oxidizable materials produces heat which may generate chlorine gas. REACTIVITY: not applicable IX - MSDS PREPARATION

SOURCES USED: RTECS PREPARED BY: Johnson Diversey Canada, Inc.

Regulatory Department

Regulatory Department Food Division

PREPARATION DATE: April 15, 2003 Phone (905) 829-1200

Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.