
MATERIAL SAFETY DATA SHEET

Page 1 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

IRX-7**MSDS ID: 00333**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: IRX-7
PRODUCT DESCRIPTOR: CIP REFINERY CLEANER
MANUFACTURER: JOHNSON DIVERSEY, INC. EMERGENCY PHONE NUMBER: (800) 851-7145
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

II. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME(CAS NUMBER)	% EXPOSURE LIMITS	UNITS
KEROSENE (8008-20-6)	<80 TLV 400; PEL 400	PPM

III. HAZARDS IDENTIFICATION

ROUTES OF ENTRY: INHALATION: YES
SKIN: NO
INGESTION: YES
SIGNS AND SYMPTOMS OF EXPOSURE:
ACUTE: DEFATS SKIN; IRRITATES EYES, MAY CAUSE DIZZINESS.
CHRONIC: SAME AS ACUTE.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
SENSITIVE SKIN AND EYES.

IV. FIRST AID MEASURES

EYES: FLUSH THOROUGHLY WITH FRESH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.
SKIN: FLUSH WITH FRESH WATER, WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHES AND SHOES.
INGESTION: IF SWALLOWED DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
INHALATION: REMOVE TO FRESH AIR AND SEEK MEDICAL ATTENTION.

V. FIRE FIGHTING MEASURES

FLASH POINT: 145 DEG F	FLAME EXTENSION: N/A	IN.
FLAMMABLE LIMITS IN AIR BY VOLUME:	LEL: 1%	UEL: 6%
UNUSUAL FIRE OR EXPLOSION HAZARDS:	NONE KNOWN	
EXTINGUISHING MEDIA:	CO2, DRY CHEMICALS	
FIRE FIGHTING INSTRUCTIONS:	WEAR PROTECTIVE GEAR AND SELF-CONTAINED BREATHING APPARATUS IN FIRE AREA. USE WATER SPRAY TO COOL DOWN.	

MATERIAL SAFETY DATA SHEET

Page 2 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

IRX-7

MSDS ID: 00333

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED: ABSORB AND DISPOSE TO WASTE; COLLECT AND RETURN TO CONTAINER.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: KEEP CONTAINER CLOSED. DOES NOT FREEZE. DO NOT PRESSURE CONTAINER TO EMPTY.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: SAFETY GLASSES
PROTECTIVE GLOVES: SOLVENT RESISTANT
RESPIRATORY PROTECTION: NONE
OTHER PROTECTIVE CLOTHING/EQUIPMENT: CLOTHING TO PREVENT PROLONGED SKIN CONTACT.
EXPOSURE GUIDELINES: SEE SECTION II FOR DETAILED INFORMATION.

IX. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (F): >300 SPECIFIC GRAVITY: 0.8300
VOLATILE BY VOLUME: 75 SOLUBILITY IN WATER: 10.0
VAPOR PRESSURE (MMHG): N/A AT
APPEARANCE AND ODOR: YELLOW AMBER LIQUID, TYPICAL SOLVENT ODOR

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE
INCOMPATIBILITY WITH OTHER MATERIALS: STRONG OXIDIZERS.
HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF CARBON, HYDROGEN.
HAZARDOUS POLYMERIZATION: NONE

XI. TOXICOLOGICAL INFORMATION

NO DATA AVAILABLE

XII. ECOLOGICAL INFORMATION

NO DATA AVAILABLE

XIII. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: USE UNTIL LESS THAN ONE INCH REMAINS IN CONTAINER, EMPTY CONTAINER. TRIPLE RINSE WITH KEROSENE OR AVAILABLE SOLVENT, BURN LIQUID. DISPOSE AS WASTE OIL OR SOLVENT. REMOVE OR DEFACE LABEL BEFORE SELLING CONTAINER OR DISPOSAL.

MATERIAL SAFETY DATA SHEET

Page 3 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

IRX-7

MSDS ID: 00333

XIV. TRANSPORT INFORMATION

HAZARDOUS MATERIALS DESCRIPTION/PROPER SHIPPING NAME:

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CERCLA/EPCRA:SECTION 313 TOXIC CHEMICALS:

ALL CHEMICAL INGREDIENTS ARE LISTED ON THE TSCA INVENTORY.

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 2 FIRE: 2 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: B

STATE RIGHT-TO-KNOW INFORMATION:

KEROSENE - CAS #8008-20-6

NONIONIC SURFACTANT - 68155-20-4

AROMATIC HYDROCARBONS - CAS #64742-94-5

PINE OIL - CAS #8002-09-3

XVI. OTHER INFORMATION

THE INFORMATION IN THIS MSDS RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED OTHER THAN AS RECOMMENDED BY DIVERSEY LEVER OR IN COMBINATION WITH OTHER MATERIALS. IT IS THE USER'S RESPONSIBILITY TO EVALUATE THE APPLICABILITY OF THIS INFORMATION FOR HIS PARTICULAR CONDITIONS OF STORAGE, HANDLING AND USE.