



I - PRODUCT IDENTIFICATION AND USE

MSDS ID: 92075

PRODUCT NAME: TASKI VISION STAR**USE:** Floor Sealer**SUPPLIER:**

JohnsonDiversey Canada, Inc.
2401 Bristol Circle
Oakville Ontario, L6H 6P1, Canada

EMERGENCY PHONE:

1-800-668-7171

WHMIS CLASSIFICATION: D2B**CHEMICAL FAMILY:** Acrylic**TRADE NAME / SYNONYMS:** not applicable**CHEMICAL NAME:** not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS #	LD50 / LC50	Route / Species
Tributoxyethyl phosphate	1-5	000078-51-3	LD50 3000 mg/kg	oral/rat
Styrene/Acrylic Copolymer	1-5	Proprietary	not available	oral/rat
Diethylene Glycol Ethyl Ether	3-7	000111-90-0	LD50 5500 mg/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: Natural Rubber, Neoprene or Nitrile **Eye:** safety glasses **Footwear:** not required

Respiratory: not required **Other:** not applicable

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Avoid eye and skin contact.**VENTILATION REQUIREMENTS:** general ventilation**INCOMPATIBILITY (Material to Avoid):** none known

SPILL PROCEDURES: Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal. Wash spill area with large volumes of water.

WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.**STORAGE / SHIPPING REQUIREMENT:** Store in a cool dry area in a closed container. Avoid freezing.

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: White emulsion; mild solvent odour**S.G. / BULK DENSITY(g/cc):** 1.050**pH:** 8.3**VAPOUR PRESSURE (mmHg):** not available**VAPOUR DENSITY (air=1):** not available**ODOUR THRESHOLD:** not available**BOILING POINT:** approx. 100°C**FREEZING POINT:** approx. 0°C**PERCENT VOLATILE:** approx. 85%**SOLUBILITY IN WATER:** dispersable**EVAPORATION RATE (water=1):** not available

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:**EYES:** May cause irritation.**SKIN:** Repeated or prolonged contact may result in irritation.**INGESTION:** Irritation of the digestive tract.**INHALATION:** Excessive exposure may cause headache and nausea.

LD50 (calculated): 3,000 mg/kg		LC50 (calculated): not applicable	
OTHER TOXIC EFFECTS: TLV (Diethylene glycol monoethyl ether): 100 mg/m3; TLV-STEL (Tributoxyethyl phosphate): 1 mg/m3.			
EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: none known			
VI - FIRST AID MEASURES			
EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.			
SKIN: Flush affected area thoroughly with water. If irritation develops, contact a physician.			
INGESTION: Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician.			
INHALATION: Remove patient to fresh air. Get medical attention for any breathing difficulty.			
VII - FIRE AND EXPLOSION DATA			
FLAMMABLE: No.			
FLASH POINT, °C: not applicable		AUTO IGNITION TEMPERATURE, °C: N/Ap	
EXTINGUISHING MEDIA: Water [X] Dry Chemical [X] Carbon Dioxide [X] Foam [X] Other []			
SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus.			
HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon.			
EXPLOSIVE SENSITIVITY TO: not applicable			
VIII - REACTIVITY DATA			
STABILITY: Stable [X] Unstable []			
CONDITIONS TO AVOID: none known			
INCOMPATIBILITY (Material to Avoid) : none known			
HAZARDOUS DECOMPOSITION PRODUCTS: none known			
REACTIVITY: not dangerously reactive			
IX - MSDS PREPARATION			
SOURCES USED: RTECS, Raw Material MSDS		PREPARED BY: JohnsonDiversey Canada, Inc. Regulatory Department Institutional Division Phone (905) 829-1200	
PREPARATION DATE: May 26, 2003			
Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.			