



## **MATERIAL SAFETY DATA SHEET**



| I - PRODUCT IDENTIFICATION AND USE   |  |  |                               | MSDS ID: 11098                         |                 |  |
|--|--|--|-------------------------------|--|-----------------|--|
| PRODUCT NAME: CONFIDENCE 10 PBB  |  |  |                               |  |                 |  |
| USE: Boiler water treatment for nonsoftened makeup water   |  |  |                               |  |                 |  |
| SUPPLIER:  |  | EMERGE                                 | NCY PHONE:                    |  |                 |  |
| JohnsonDiversey Canada, Inc.<br>2401 Bristol Circle<br>Oakville Ontario, L6H 6P1, Canada   |  | 1-800-668-7171                         |                               |  |                 |  |
| WHMIS CLASSIFICATION: E<br>CHEMICAL FAMILY: caustic alkali   |  | TRADE N<br>CHEMICA                     | AME / SYNONYM                 | <b>S:</b> not applicable ot applicable |                 |  |
| II - HAZARDOUS INGREDIENTS   |  |  |                               |  |                 |  |
| HAZARDOUS INGREDIENT   | % w/w                                      | ı                                      | CAS #                         | LD50 / LC50                            | Route / Species |  |
| Sodium hydroxide   | 15-40                                      |  | 001310-73-2                   | LDLo 500 mg/kg                         | oral/rab        |  |
| Sodium carbonate   | 10-30<br>15-40                             |  | 000497-19-8<br>007757-83-7    | LD50 4090 mg/kg                        | oral/rat        |  |
| Sodium sulphite 15-40  |  |  |                               | LD50 820 mg/kg                         | oral/mou        |  |
| III - HANDLING AND DISPOSAL PROCEDURES   |  |  |                               |  |                 |  |
| PERSONAL PROTECTIVE EQUIPMENT:   Gloves: Natural Rubber, neoprene or nitrile Eye: Safety Goggles Footwear: Rubber boots as required   Respiratory: NIOSH approved dust mask. Other: Not normally required   SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Avoid eye and skin contact. Wear protective equipment. Rapid mixing of this product with water generates heat and dangerous boiling can result. Always add this product to cold water slowly and with good mixing.   VENTILATION REQUIREMENTS: General ventilation   INCOMPATIBILITY (Material to Avoid): Acidic and oxidizing materials, aluminum and other soft metals.   SPILL PROCEDURES: Contain the spill. Do not allow the spilled product to go to drain. Sweep or scoop up material for disposal. Wash spill area water. Wear protective clothing.   WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.   STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container. UN1823 |  |  |                               |  |                 |  |
| IV - Pł  | IYSICAL                                    | PROPER                                 | TIES                          |  |                 |  |
| APPEARANCE / ODOUR: Speckled yellow-cream granules   | s, mild organ                              | nic, light sulp                        | hite.                         |  |                 |  |
| S.G. / BULK DENSITY(g/cc): 0.93  |  | <b>pH:</b> (1% solution): 12.6         |                               |  |                 |  |
| VAPOUR PRESSURE (mmHg): not applicable   |  | VAPOUR DENSITY (air=1): not applicable |                               |  |                 |  |
| ODOUR THRESHOLD: not applicable  |  | BOILING                                | BOILING POINT: not applicable |  |                 |  |
| FREEZING POINT: not applicable   |  | PERCENT VOLATILE: not applicable       |                               |  |                 |  |
| SOLUBILITY IN WATER: soluble   | EVAPORATION RATE (water=1): not applicable |  |                               |  |                 |  |
| V - TOXICOLOGICAL PROPERTIES   |  |  |                               |  |                 |  |
| EFFECTS OF ACUTE EXPOSURE TO MATERIAL:EYES:Corrosive. May cause severe irritation. May cause permanent damage if not treated promptly.SKIN:Corrosive. May cause severe irritation. May cause temporary or permanent damage if not treated promptly.  |  |  |                               |  |                 |  |

| <b>INGESTION:</b> Corrosive. May cause severe irritation of the digestive tract. May cause temporary or permanent damage if not treated promptly.  |   |  |  |  |  |  |
|--|---|--|--|--|--|--|
| INHALATION: Breathing dust may cause respiratory irritation.   |   |  |  |  |  |  |
| LD50 (calculated): 950 mg/kg   | LC50 (calculated): not available            |  |  |  |  |  |
| OTHER TOXIC EFFECTS: Sodium hydroxide TLV: CL 2 mg/m3  |   |  |  |  |  |  |
| EFFECTS OF CHRONIC none known  |   |  |  |  |  |  |
| EXPOSURE TO MATERIAL:  |   |  |  |  |  |  |
| VI - FIRST AID MEASURES  |   |  |  |  |  |  |
| <b>EYES:</b> Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.  |   |  |  |  |  |  |
| <b>SKIN:</b> Flush affected area thoroughly with water. If irritation develops, contact a physician.   |   |  |  |  |  |  |
| <b>INGESTION:</b> Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately.  |   |  |  |  |  |  |
| INHALATION: Remove patient to fresh air. Get medical attention for any breathing difficulty.   |   |  |  |  |  |  |
| VII - FIRE AND EXPLOSION DATA  |   |  |  |  |  |  |
| FLAMMABLE: No  |   |  |  |  |  |  |
| FLASH POINT, °C: not applicable  | AUTO IGNITION TEMPERATURE,°C: N/Ap.         |  |  |  |  |  |
| EXTINGUISHING MEDIA: Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []   |   |  |  |  |  |  |
| SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus.   |   |  |  |  |  |  |
| HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon and sulphite.  |   |  |  |  |  |  |
| EXPLOSIVE SENSITIVITY TO: not applicable   |   |  |  |  |  |  |
| VIII - REACTIVITY DATA   |   |  |  |  |  |  |
| STABILITY: Stable [x] Unstable [ ]   |   |  |  |  |  |  |
| CONDITIONS TO AVOID: Excessive heat.   |   |  |  |  |  |  |
| <b>INCOMPATIBILITY (Material to Avoid) :</b> Acidic and oxidizing materials, aluminum and other soft metals.   |   |  |  |  |  |  |
| HAZARDOUS DECOMPOSITION PRODUCTS: Heat released on contact with acids. Contact with soft metals forms flammable hydrogen gas.  |   |  |  |  |  |  |
| REACTIVITY: Not dangerously reactive   |   |  |  |  |  |  |
| IX - MSDS PREPARATION  |   |  |  |  |  |  |
| SOURCES USED: RTECS  | PREPARED BY: JohnsonDiversev Canada. Inc.   |  |  |  |  |  |
|  | - Regulatory Department                     |  |  |  |  |  |
| PREPARATION DATE: April 15, 2003   | Industrial Division<br>Phone (905) 829-1200 |  |  |  |  |  |
| Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is<br>not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any<br>person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada<br>assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety<br>procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific<br>context of the intended use. |   |  |  |  |  |  |