
MATERIAL SAFETY DATA SHEET

Page 1 of 3
Revised 10/07/04
Replaces 2/02/04
Printed 12/21/04

LIQUID BUFFER NT

MSDS ID: 00407470

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: LIQUID BUFFER NT
PRODUCT DESCRIPTOR: PAINT BOOTH TREATMENT
MANUFACTURER: JOHNSON DIVERSEY, INC. EMERGENCY PHONE NUMBER: (800) 851-7145
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

II. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME(CAS NUMBER)	%	EXPOSURE LIMITS	UNITS

NONE			

III. HAZARDS IDENTIFICATION

ROUTES OF ENTRY: INHALATION: YES
SKIN: NO
INGESTION: YES
SIGNS AND SYMPTOMS OF EXPOSURE:
ACUTE: MAY IRRITATE EYES AND SKIN. MISTS MAY IRRITATE RESPIRATORY TRACT.
CHRONIC: SAME AS ACUTE.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
Sensitive skin

IV. FIRST AID MEASURES

EYES: FLUSH THOROUGHLY WITH FRESH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.
SKIN: FLUSH WITH FRESH WATER. REMOVE CONTAMINATED CLOTHES AND SHOES.
INGESTION: GIVE MILK OR WATER, INDUCE VOMITING. GET MEDICAL ATTENTION.
INHALATION: REMOVE TO FRESH AIR AND SEEK MEDICAL ATTENTION.

V. FIRE FIGHTING MEASURES

FLASH POINT: NONE	DEG F	FLAME EXTENSION: N/A	IN.
FLAMMABLE LIMITS IN AIR BY VOLUME:		LEL: N/A	UEL: N/A
UNUSUAL FIRE OR EXPLOSION HAZARDS:	NONE KNOWN		
EXTINGUISHING MEDIA:	CO2, DRY CHEMICALS, WATER		
FIRE FIGHTING INSTRUCTIONS:	NONE		

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED: FLUSH SMALL AMOUNTS OF MATERIAL TO THE DRAIN; COLLECT AND RETURN LARGE AMOUNTS TO ORIGINAL CONTAINER.

MATERIAL SAFETY DATA SHEET

Page 2 of 3
Revised 10/07/04
Replaces 2/02/04
Printed 12/21/04

LIQUID BUFFER NT**MSDS ID: 00407470**

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: KEEP BUNGS IN CONTAINER. STORE INSIDE OR OUTSIDE. IF FROZEN, THAW AND MIX TO MAKE USABLE.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: SAFETY GLASSES OR GOGGLES
PROTECTIVE GLOVES: ALKALI RESISTANT
RESPIRATORY PROTECTION: NONE
OTHER PROTECTIVE CLOTHING/EQUIPMENT: NONE
EXPOSURE GUIDELINES: SEE SECTION II FOR DETAILED INFORMATION.

IX. PHYSICAL AND CHEMICAL PROPERTIES

BOILIING POINT (F): 212 SPECIFIC GRAVITY: 1.1400
VOLATILE BY VOLUME: <87 SOLUBILITY IN WATER: 100
VAPOR PRESSURE (MMHG): 17.5 AT 20 C
APPEARANCE AND ODOR: CLEAR LIQUID; ODORLESS

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE
INCOMPATIBILITY WITH OTHER MATERIALS: STRONG ACIDS
HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF CARBON
HAZARDOUS POLYMERIZATION: NONE KNOWN

XI. TOXICOLOGICAL INFORMATION

NO DATA AVAILABLE

XII. ECOLOGICAL INFORMATION

NO DATA AVAILABLE

XIII. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: ADJUST PH. NO PHOSPHATES. USE UNTIL LESS THAN ONE INCH REMAINS IN CONTAINER, EMPTY CONTAINER. TRIPLE RINSE CONTAINER WITH WATER ADD TO OPERATION. REMOVE OR DEFACE CONTAINER LABEL BEFORE SELLING OR DISPOSAL.

XIV. TRANSPORT INFORMATION

HAZARDOUS MATERIALS DESCRIPTION/PROPER SHIPPING NAME:
Please refer to the Bill of Lading/receiving documents for up to date shipping information.

LIQUID BUFFER NTMSDS ID: 00407470

XV. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CERCLA/EPCRA:SECTION 313 TOXIC CHEMICALS:

N/A

LISTED CARCINOGEN: None

NTP: NO

IARC: NO

OSHA: NO

HMIS RATINGS: HEALTH: 2 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: B

STATE RIGHT-TO-KNOW INFORMATION:

SODIUM CARBONATE - CAS #497-19-8

WATER - CAS #7732-18-5

SODIUM SILICATE - CAS #1344-09-8

XVI. OTHER INFORMATION

THE INFORMATION IN THIS MSDS RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED OTHER THAN AS RECOMMENDED BY DIVERSEY LEVER OR IN COMBINATION WITH OTHER MATERIALS. IT IS THE USER'S RESPONSIBILITY TO EVALUATE THE APPLICABILITY OF THIS INFORMATION FOR HIS PARTICULAR CONDITIONS OF STORAGE, HANDLING AND USE.