
MATERIAL SAFETY DATA SHEET

Page 1 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

D-FILM IT**MSDS ID: 00656**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: D-FILM IT

Product Descriptor: ALKALINE TRUCK WASH

MANUFACTURER: JOHNSON DIVERSEY, INC.
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

EMERGENCY PHONE NUMBER: (800)851-7145

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
SODIUM HYDROXIDE	1310-73-2	< 1.0 %	TLV-C 2	MG/M3
SODIUM METASILICATE	6834-92-0	< 1.0 %	None established	

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

WARNING-Product contains irritating or harmful chemicals which may cause eye or skin irritation or burns. May be harmful if swallowed. Do not get product in eyes, on skin or clothing. Wear eye protection and rubber gloves to prevent skin contact when handling product. Wash after handling. Avoid breathing dust, vapors or product spray. Contain spill and runoff to prevent direct discharge to soil or surface waters.

POSSIBLE ROUTES OF ENTRY: Ingestion and Inhalation.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: May cause severe irritation with pain, swelling, blurred or impaired vision. Skin: May cause severe irritation with redness, swelling and possible pain. INGESTION: If swallowed, may cause gastric distress, diarrhea and vomiting. INHALATION: Spray or mists may cause irritation to nose, throat and respiratory tract with pain and breathing difficulty.

CHRONIC: Contact dermatitis or sensitization.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis and sensitive skin.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes, skin and respiratory tract.

IV. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for 15 minutes. Get medical attention.

SKIN: Flush skin with plenty of water. Remove and launder contaminated clothing before reuse. Get medical attention for irritation or injury.

INGESTION: If swallowed, rinse mouth with water. Dilute by drinking several glasses of water. Do not induce vomiting. Get prompt medical attention. NOTE: Never give fluids by mouth to an unconscious person.

MATERIAL SAFETY DATA SHEET

Page 2 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

D-FILM IT**MSDS ID: 00656**

IV. FIRST AID MEASURES (Cont.)

INHALATION: Remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention, immediately.

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): NONE **FLAME EXTENSION:** N/A
FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: N/A UEL: N/A
UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Toxic fumes or vapor may form during fire.
EXTINGUISHING MEDIA: Water spray, CO2, foam or dry powder.
FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus (SCBA) in fire area.
SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:
Contain spill. Absorb with sand or clay. Collect material and place in suitable waste container. Neutralize solids and spill area with dilute mineral acids or bicarbonate of soda. Dispose of by environmental regulations. This product does not contain a reportable quantity (RQ) under CERCLA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Store in a cool, dry area away from acids. Keep container closed when not in use. Wear protective gear when handling or using. Do not pressurize container to empty.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Chemical goggles if contact or splash hazard exists. Eye wash in use area.
PROTECTIVE GLOVES: Alkali resistant.
RESPIRATORY PROTECTION: Respirator protection required if PEL is exceeded. See Section II for information.
OTHER PROTECTIVE CLOTHING/EQUIPMENT: Rubber boots, chemical apron and safety shower in use area if contact or splash hazard exists.
ENGINEERING CONTROLS:
MECHANICAL VENTILATION: Normal room ventilation should be sufficient to control airborne levels.
LOCAL VENTILATION: Local exhaust ventilation may be necessary to control any air contaminants to within their Threshold Limit Values (TLV's) during the use of this product.

MATERIAL SAFETY DATA SHEET

Page 3 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

D-FILM IT

MSDS ID: 00656

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear water white to light yellow liquid; sweet odor.

BOILING POINT (DEG F): 215

FREEZING POINT: ND

SPECIFIC GRAVITY/BULK DENSITY: 1.035

pH: 13.3

pH 1% SOLUTION: 11.5

VOLATILE BY VOLUME: 94

SOLUBILITY IN WATER: Soluble

VAPOR PRESSURE(mmHg): ND at ND

VAPOR DENSITY: ND

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: Strong acids, strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms oxides of carbon, nitrogen and sulfur.

HAZARDOUS POLYMERIZATION: None known.

XI. TOXICOLOGICAL INFORMATION

Contains Corrosive and Irritating alkaline chemicals. See Section II for amounts and identity. Acute toxicology tests are listed below.

TOXICITY TEST DATA:

Sodium hydroxide: Acute Oral LD50 (rat) - 500 mg/kg (RTECS)

Acute Skin LD50 (rabbit) - 1350 mg/kg (MSI)

Sodium metasilicate: Acute Oral LD50 (rat) - 1153 mg/kg (RTECS)

XII. ECOLOGICAL INFORMATION

ECOTOXICITY DATA: When handled and disposed of as directed, this product should not cause adverse effects in the environment.

ECOTOXICITY TEST DATA: No data available.

ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: RCRA Regulated Hazardous Waste Corrosivity Characteristic D002.

Discharge diluted product to industrial sewer. Use product in container until empty. Triple rinse container with water and add to process. Recycle or dispose of container by product labeling or governmental regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

D-FILM IT**MSDS ID: 00656**

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: Contains no hazardous air pollutants.

VOC CONTENT (EPA Method 24A): % VOC: 0.0 Lb/Gal VOC: 0.0

CERCLA/EPCRA:

Section 313 Toxic Chemicals: None

SARA Section 311/312:

ACUTE: YES CHRONIC: NO FIRE: NO REACTIVITY: NO

SUDDEN RELEASE OF PRESSURE: NO

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 2 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: C

NFPA RATING: HEALTH: 2 FIRE: 0 REACTIVITY: 0 SPECIAL: -

STATE RIGHT-TO-KNOW INFORMATION:

WATER - CAS #7732-18-5

SODIUM HYDROXIDE - CAS #1310-73-2

SODIUM METASILICATE - CAS #6834-92-0

TETRASODIUM ETHYLENEDIAMINE TETRAACETATE - CAS #64-02-8

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.