



I - PRODUCT IDENTIFICATION AND USE				MSDS ID: 0076
PRODUCT NAME: LOW TEMPERATURE SANITIZER T20				
USE: Sanitizer/Disinfectant				
SUPPLIER: JohnsonDiversey Canada, Inc. 2401 Bristol Circle Oakville Ontario, L6H 6P1, Canada		EMERGENCY PHONE: 1-800-668-7171		
WHMIS CLASSIFICATION: D2B E CHEMICAL FAMILY: Chlorinated alkali		TRADE NAME / SYNONYMS: not applicable CHEMICAL NAME: Sodium hypochlorite solution		
II - HAZARDOUS INGREDIENTS				
HAZARDOUS INGREDIENT	% w/w	CAS #	LD50 / LC50	Route / Species
Sodium hypochlorite (10.5%-solution)	50	007681-52-9	LD50 4445 mg/kg	oral/rat
III - HANDLING AND DISPOSAL PROCEDURES				
PERSONAL PROTECTIVE EQUIPMENT:				
Gloves: Natural rubber, Neoprene or Nitrile		Eye: safety goggles		Footwear: not applicable
Respiratory: If mists are generated, use NIOSH approved mask		Other: impermeable apron		
SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Avoid eye and skin contact.				
VENTILATION REQUIREMENTS: mechanical exhaust				
INCOMPATIBILITY (Material to Avoid): Acids, oxidizable materials, ammonia, urea, other nitrogenous materials, and metals.				
SPILL PROCEDURES: Contain the spill. Do not allow the spilled product to go to drain. Neutralize with sodium sulfite, sodium bisulphite, or dilute hydrogen peroxide. Mop up or soak up with absorbent clay for disposal. Wash spill area with large volumes of water.				
WASTE DISPOSAL: Dispose according to municipal, provincial and federal regulations.				
STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container. Keep away from oxidizable materials. UN1791				
IV - PHYSICAL PROPERTIES				
APPEARANCE / ODOUR: Clear, yellow-green liquid - chlorine odour				
S.G. / BULK DENSITY(g/cc): 1.09		pH: (concentrate): 12.0		
VAPOUR PRESSURE (mmHg): 17.5		VAPOUR DENSITY (air=1): not applicable		
ODOUR THRESHOLD: not available		BOILING POINT: approx. 100°C		
FREEZING POINT: -25°C		PERCENT VOLATILE: approx. 95%		
SOLUBILITY IN WATER: soluble		EVAPORATION RATE (water=1): not available		
V - TOXICOLOGICAL PROPERTIES				
EFFECTS OF ACUTE EXPOSURE TO MATERIAL:				
EYES: Corrosive. May cause severe irritation. May cause permanent damage if not treated promptly.				
SKIN: Corrosive. May cause severe irritation. May cause temporary or permanent damage if not treated promptly.				
INGESTION: Corrosive. May cause severe irritation of the digestive tract. May cause permanent damage if not treated promptly. May lead to convulsions, coma and death.				
INHALATION: May cause irritation of the nose and throat, coughing, difficulty breathing; may cause pulmonary edema.				

LD50 (calculated): 8890 mg/kg.	LC50 (calculated): not available
OTHER TOXIC EFFECTS: TLV-TWA (Chlorine): 0.5 ppm; TLV-STEL (Chlorine): 1 ppm	
EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: none known	
VI - FIRST AID MEASURES	
EYES:	Flush eyes with plenty of water for at least 15 minutes. Hold eye lids open while rinsing. Contact a physician immediately.
SKIN:	Flush affected area thoroughly with water. If irritation persists, contact a physician.
INGESTION:	Drink large volumes of water . Never give anything by mouth to an unconscious person. Do not induce vomiting. Contact a physician immediately.
INHALATION:	Remove patient to fresh air. If breathing difficulty occurs, get medical attention.
VII - FIRE AND EXPLOSION DATA	
FLAMMABLE: No	
FLASH POINT, °C: not applicable	AUTO IGNITION TEMPERATURE, °C: N/Ap
EXTINGUISHING MEDIA: Water [X] Dry Chemical [X] Carbon Dioxide [X] Foam [X] Other []	
SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus and full protective equipment.	
HAZARDOUS COMBUSTION PRODUCTS: chlorine gas	
EXPLOSIVE SENSITIVITY TO: not applicable	
VIII - REACTIVITY DATA	
STABILITY: Stable [] Unstable [X]	
CONDITIONS TO AVOID: Decomposes slowly. Do not expose to temperatures above 40°C (104°F), sunlight, or metals.	
INCOMPATIBILITY (Material to Avoid) : Acids, oxidizable materials, ammonia, urea, metals.	
HAZARDOUS DECOMPOSITION PRODUCTS: Chlorine gas is released by contact with acids; oxygen is released by contact with metals. Contact with ammonia and urea produce nitrogen gas and chloramines. Contact with oxidizable materials produces heat which may generate chlorine gas.	
REACTIVITY: not applicable	
IX - MSDS PREPARATION	
SOURCES USED: RTECS	PREPARED BY: JohnsonDiversey Canada, Inc. Regulatory Department Institutional Division Phone (905) 829-1200
PREPARATION DATE: April 15, 2003	
<p>Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.</p>	