



I - PRODUCT IDENTIFICATION AND USE

MSDS ID: 57483

PRODUCT NAME: **DIVOS 124**

USE: Alkaline detergent for high pH tolerant MF & UF membranes.

SUPPLIER:

JohnsonDiversey Canada, Inc.
2401 Bristol Circle
Oakville Ontario, L6H 6P1, Canada

EMERGENCY PHONE:

1-800-668-7171

WHMIS CLASSIFICATION: E

CHEMICAL FAMILY: alkali

TRADE NAME / SYNONYMS: not applicable

CHEMICAL NAME: not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS #	LD50 / LC50	Route / Species
Potassium hydroxide	15-40	001310-58-3	LD50 365 mg/kg	oral/rat
Tetrasodium EDTA	5-10	000064-02-8	LD50 3200 mg/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: Natural rubber, Neoprene, Nitrile or PVC

Eye: Safety goggles

Footwear: As required

Respiratory: If mists are generated, use NIOSH approved mask

Other: Rubber apron

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Avoid eye and skin contact.

VENTILATION REQUIREMENTS: General ventilation

INCOMPATIBILITY (Material to Avoid): Acids

SPILL PROCEDURES: Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal. Wash spill area with large volumes of water.

WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.

STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container. Avoid freezing. UN1814

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Odourless, clear to hazy yellow liquid

S.G. / BULK DENSITY(g/cc): 1.42

pH: (1%) 12.6

VAPOUR PRESSURE (mmHg): not applicable

VAPOUR DENSITY (air=1): not applicable

ODOUR THRESHOLD: not available

BOILING POINT: 100°C

FREEZING POINT: not available

PERCENT VOLATILE: 55%

SOLUBILITY IN WATER: soluble

EVAPORATION RATE (water=1): not available

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:

EYES: Corrosive. May cause severe irritation. May cause permanent damage if not treated promptly.

SKIN: Corrosive. May cause severe irritation.

INGESTION: Corrosive. May cause severe irritation of the digestive tract.

INHALATION: Breathing spray or mist may cause respiratory irritation.

LD50 (calculated): 1014 mg/kg

LC50 (calculated): not available

OTHER TOXIC EFFECTS: Potassium hydroxide TLV - CL 2 mg/m3	
EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: not available	
VI - FIRST AID MEASURES	
EYES:	Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.
SKIN:	Flush affected area thoroughly with water. If irritation develops, contact a physician.
INGESTION:	Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately.
INHALATION:	Remove patient to fresh air.
VII - FIRE AND EXPLOSION DATA	
FLAMMABLE: No	
FLASH POINT, °C: not applicable	AUTO IGNITION TEMPERATURE, °C: N/Ap
EXTINGUISHING MEDIA: Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []	
SPECIAL FIRE FIGHTING PROCEDURES: not applicable	
HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, nitrogen.	
EXPLOSIVE SENSITIVITY TO: not applicable	
VIII - REACTIVITY DATA	
STABILITY: Stable [x] Unstable []	
CONDITIONS TO AVOID: not applicable	
INCOMPATIBILITY (Material to Avoid) : acids	
HAZARDOUS DECOMPOSITION PRODUCTS: Contact with acids will generate heat.	
REACTIVITY: not applicable	
IX - MSDS PREPARATION	
SOURCES USED: RTECS	PREPARED BY: JohnsonDiversey Canada. Inc. Regulatory Department Food Division Phone (905) 829-1200
PREPARATION DATE: April 15, 2003	
Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.	