

DUST-STOP

MSDS ID: 01282

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: DUST-STOP

Product Descriptor: DUST SUPPRESSANT

MANUFACTURER: JOHNSON DIVERSEY, INC.
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

EMERGENCY PHONE NUMBER: (800)851-7145

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
HEXYLENE GLYCOL	107-41-5	15 - 30%	TLV C 125 PEL C 1MG/M3 25	
SODIUM ALPHAOLEFIN SULPHONATE	68439-57-6	15 - 30%	None established	

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

WARNING - Contains chemicals that cause irritation to eyes and skin. May be harmful if swallowed. Wear eye protection, clothing and rubber gloves to prevent prolonged skin contact. Wash after handling.

POSSIBLE ROUTES OF ENTRY: Ingestion; Skin contact/absorption; Inhalation

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Severe irritation with redness, pain and swelling. SKIN: Irritation with dryness or itching may develop with pain and redness. INGESTION: If swallowed, gastric distress, diarrhea, nausea and vomiting may occur. INHALATION: May cause irritation of respiratory tract.

CHRONIC: Same as acute effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis or sensitive skin.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes and skin.

IV. FIRST AID MEASURES

EYES: Immediately flush with plenty of water. Get medical attention.
SKIN: Flush skin with plenty of water and wash with mild soap. If irritation develops, get medical attention.
INGESTION: If swallowed, rinse mouth with water. Dilute by drinking several glasses of water. DO NOT induce vomiting. If patient vomits, rerinse mouth. Get immediate medical attention. NOTE: Never give fluids by mouth to an unconscious person.
INHALATION: Remove to fresh air and seek medical attention.

MATERIAL SAFETY DATA SHEET

Page 2 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

DUST-STOP

MSDS ID: 01282

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): None FLAME EXTENSION: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: UEL: ND
UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Toxic fumes or vapor may form during fire.
EXTINGUISHING MEDIA: Water, water spray, CO2, foam or dry powder.
FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus (SCBA) in fire area.
SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:
Contain spill. Wear protective clothing. Soak up or absorb liquid on suitable absorbent material. Collect and place in chemical waste container. Dispose of in accordance with local, State and Federal regulations. Flush spill area with water.
This product does not contain a reportable quantity (RQ) under CERCLA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Store in a cool, dry area, keep away from acids. Keep container closed when not in use. Wear protective gear when handling or using. Do not pressurize container to empty.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Safety glasses with side shields.
PROTECTIVE GLOVES: Alkali resistant.
RESPIRATORY PROTECTION: Not normally required.
OTHER PROTECTIVE CLOTHING/EQUIPMENT: Eyewash and safety shower in area if contact or splash hazard exists.
ENGINEERING CONTROLS:
VENTILATION: Good general ventilation should be sufficient to control airborne levels.

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear, pale yellow liquid.

BOILING POINT (DEG F): 214 F	FREEZING POINT: ND
SPECIFIC GRAVITY/BULK DENSITY: 1.01	
pH: 7.7	pH 1% SOLUTION: ND
VOLATILE BY VOLUME: 90%	
SOLUBILITY IN WATER: Soluble	
VAPOR PRESSURE(mmHg): ND at ND	VAPOR DENSITY: ND

MATERIAL SAFETY DATA SHEET

Page 3 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

DUST-STOP

MSDS ID: 01282

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: Acids; Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms; oxides of carbon

HAZARDOUS POLYMERIZATION: None known.

XI. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL TESTING: No data available.

TOXICITY TEST DATA:

No data available.

XII. ECOLOGICAL INFORMATION

ECOTOXICITY TEST DATA:

No data available.

ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Not Regulated.

Discharge diluted product to industrial sewer in accordance with discharge permit or local POTW regulations. Use product in container until empty. Rinse container with water. Recycle or dispose of container according to product labeling or governmental regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: None

VOC CONTENT (EPA Method 24A): % VOC: 20 Lb/Gal VOC: 1.68

CERCLA/EPCRA:

Section 313 Toxic Chemicals:

None

SARA Section 311/312:

ACUTE: YES CHRONIC: NO FIRE: NO REACTIVITY: NO

SUDDEN RELEASE OF PRESSURE: NO

LISTED CARCINOGEN: None

NTP: No IARC: No OSHA: No

HMIS RATINGS: HEALTH: 2 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: B

NFPA RATING: HEALTH: 2 FIRE: 0 REACTIVITY: 0 SPECIAL: ---

STATE RIGHT-TO-KNOW INFORMATION:

WATER - CAS #7732-18-5

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

DUST-STOP

MSDS ID: 01282

XV. REGULATORY INFORMATION (Cont.)

HEXYLENE GLYCOL - CAS #107-41-5
SODIUM ALPHAOLEFIN - CAS #68439-57-6
CALIFORNIA PROPOSITION 65:
None

XVI. OTHER INFORMATION

Disclaimer: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.