
MATERIAL SAFETY DATA SHEET

Page 1 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

EGO 80/90**MSDS ID: 01885**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: EGO 80/90
PRODUCT DESCRIPTOR: GEAR LUBRICANT WITH EP ADDITIVE
MANUFACTURER: JOHNSON DIVERSEY, INC. EMERGENCY PHONE NUMBER: (800) 851-7145
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

II. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME(CAS NUMBER)	% EXPOSURE LIMITS	UNITS
PETROLEUM HYDROCARBON CAS#64742-65-0	<75 TLV E; STEL 10	MG/M3

III. HAZARDS IDENTIFICATION

ROUTES OF ENTRY: INHALATION: YES
SKIN: YES
INGESTION: YES
SIGNS AND SYMPTOMS OF EXPOSURE:
ACUTE: DEFATS SKIN, IRRITATES EYES
CHRONIC: SAME AS ACUTE
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
Sensitive skin

IV. FIRST AID MEASURES

EYES: FLUSH THOROUGHLY WITH FRESH WATER. GET MEDICAL ATTENTION.
SKIN: FLUSH WITH FRESH WATER, WASH WITH SOAP AND WATER. REMOVE
CONTAMINATED CLOTHES AND SHOES.
INGESTION: GIVE MILK OR WATER. DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.
NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
INHALATION: REMOVE TO FRESH AIR AND SEEK MEDICAL ATTENTION.

V. FIRE FIGHTING MEASURES

FLASH POINT: 400 DEG F	FLAME EXTENSION: N/A IN.
FLAMMABLE LIMITS IN AIR BY VOLUME:	LEL: NONE UEL: NONE
UNUSUAL FIRE OR EXPLOSION HAZARDS:	VAPORS MAY BE HEAVIER THAN AIR-MAY TRAVEL ALONG GROUND LEVEL
EXTINGUISHING MEDIA:	CO2 DRY CHEMICAL OR FOAM
FIRE FIGHTING INSTRUCTIONS:	STANDARD PROCEDURE FOR PETROLEUM PRODUCTS

MATERIAL SAFETY DATA SHEET

Page 2 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

EGO 80/90

MSDS ID: 01885

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED: CONTAIN THE SPILL. PREVENT SPILL FROM ENTERING SEWER. RECOVER FREE LIQUID AND/OR COLLECT WITH INERT OIL ABSORBENT. PLACE ABSORBENT INTO METAL CONTAINER FOR DISPOSAL. CLEAN SPILL AREA WITH DETERGENT OR SOLVENTIZED CLEANER.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: STORE CONTAINERS CLOSED IN A CLEAN, DRY AREA. KEEP AWAY FROM HEAT, OPEN FLAME, AND OXIDIZING AGENTS. DO NOT PRESSURIZE CONTAINER TO EMPTY.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: SAFETY GLASSES
PROTECTIVE GLOVES: NON-ABSORBENT
RESPIRATORY PROTECTION: NONE
OTHER PROTECTIVE CLOTHING/EQUIPMENT: GLOVES SHOULD BE USED BY PERSONS
HYPERSENSITIVE TO PETROLEUM OILS.
EXPOSURE GUIDELINES: SEE SECTION II FOR DETAILED INFORMATION.

IX. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (F): 600 SPECIFIC GRAVITY: 0.8950
VOLATILE BY VOLUME: 10% SOLUBILITY IN WATER: 0
VAPOR PRESSURE (MMHG): N/A AT
APPEARANCE AND ODOR: BROWN-GREEN LUBRICATING OIL; MILD SULFUR ODOR

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE
INCOMPATIBILITY WITH OTHER MATERIALS: NONE KNOWN
HAZARDOUS DECOMPOSITION PRODUCTS: (FIRE) SULFUR OXIDES; CO, CO2, H2S WITH
INCOMPLETE COMBUSTION.
HAZARDOUS POLYMERIZATION: NONE

XI. TOXICOLOGICAL INFORMATION

NO DATA AVAILABLE

XII. ECOLOGICAL INFORMATION

NO DATA AVAILABLE

XIII. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: APPROVED LANDFILL; ANY OTHER APPROPRIATE FOR PETROLEUM LUBRICANT. USE UNTIL LESS THAN ONE INCH REMAINS IN CONTAINER, EMPTY CONTAINER. TRIPLE RINSE WITH KEROSENE OR AVAILABLE SOLVENT, BURN LIQUID. REMOVE OR DEFACE LABEL BEFORE SELLING CONTAINER OR DISPOSAL. TOLUENE (CAS#108-8-3) 155PPM COL PROP 65

MATERIAL SAFETY DATA SHEET

Page 3 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

EGO 80/90

MSDS ID: 01885

XIV. TRANSPORT INFORMATION

HAZARDOUS MATERIALS DESCRIPTION/PROPER SHIPPING NAME:

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CERCLA/EPCRA:SECTION 313 TOXIC CHEMICALS:

ALL CHEMICAL INGREDIENTS ARE LISTED ON THE TSCA INVENTORY.

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 1 FIRE: 1 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: B

STATE RIGHT-TO-KNOW INFORMATION:

STATE RIGHT TO KNOW DATA:

NJ- PETROLEUM OIL (GREASE)

PA- FORMULA TRADE SECRET

XVI. OTHER INFORMATION

THE INFORMATION IN THIS MSDS RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED OTHER THAN AS RECOMMENDED BY DIVERSEY LEVER OR IN COMBINATION WITH OTHER MATERIALS. IT IS THE USER'S RESPONSIBILITY TO EVALUATE THE APPLICABILITY OF THIS INFORMATION FOR HIS PARTICULAR CONDITIONS OF STORAGE, HANDLING AND USE.