

ENVIRO LIFT AWAY

MSDS ID: 01912

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: ENVIRO LIFT AWAY

Product Descriptor: LIQUID CLEANER

MANUFACTURER: JOHNSON DIVERSEY, INC.
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

EMERGENCY PHONE NUMBER: (800) 851-7145

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
SODIUM XYLENE SULFONATE	1300-72-7	1 - 5%	None established	

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

CAUTION - Contains cleaning agents that may cause eye irritation. May be harmful if swallowed. Do not get in eyes. Do not take internally.

POSSIBLE ROUTES OF ENTRY: Inhalation and ingestion.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Causes eye irritation. SKIN: Irritation or dryness develops with long contact. INGESTION: If swallowed, pain, nausea and vomiting may result. INHALATION: May cause irritation of respiratory tract.

CHRONIC: None known

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis or sensitive skin.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes and skin.

IV. FIRST AID MEASURES

EYES: Immediately flush with plenty of water. Get medical attention.
SKIN: Rinse off product and wash with mild soap and water.
INGESTION: If swallowed, rinse mouth with water. Dilute by drinking several glasses of water. DO NOT induce vomiting. If patient vomits, rerinse mouth. Get immediate medical attention. NOTE: Never give fluids by mouth to an unconscious person.
INHALATION: Remove to fresh air and seek medical attention.

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): NONE

FLAME EXTENSION: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME:

LEL: NONE

UEL: NONE

UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Toxic fumes or vapor may form during fire.

EXTINGUISHING MEDIA: Water, water spray, CO2, foam or dry powder.

FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure

ENVIRO LIFT AWAY

MSDS ID: 01912

V. FIRE FIGHTING MEASURES (Cont.)

breathing apparatus SCBA) in fire area.

SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:

Contain spill. Wear protective clothing. Soak up or absorb liquid on suitable absorbent material. Collect and place in chemical waste container. Dispose of in accordance with local, State and Federal regulations. Flush spill area with water.

This product does not contain a reportable quantity (RQ) under CERCLA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Store in a cool, dry area, keep away from acids. Keep container closed when not in use. Wear protective gear when handling or using. Do not pressurize container to empty.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Safety glasses with side shields. Chemical goggles if contact or splash hazard exists.

PROTECTIVE GLOVES: Alkali resistant.

RESPIRATORY PROTECTION: Product does not have any established exposure limits. NIOSH/MSHA approved respirator recommended in enclosed or confined spaces where high air concentration or long exposure may occur.

OTHER PROTECTIVE CLOTHING/EQUIPMENT: Eyewash and safety shower in area if contact or splash hazard exists.

ENGINEERING CONTROLS:

VENTILATION: Good general ventilation should be sufficient to control airborne levels.

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear orange liquid, no odor.

BOILING POINT (DEG F): 215

FREEZING POINT: < 50 F

SPECIFIC GRAVITY/BULK DENSITY: 1.270

pH: 10.5-10.9

pH 1% SOLUTION: N/A

VOLATILE BY VOLUME: 80

SOLUBILITY IN WATER: Soluble

VAPOR PRESSURE(mmHg): 17.5 at 20 C

VAPOR DENSITY: 17.3

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: None known

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms; oxides of sulfur; oxides of carbon

MATERIAL SAFETY DATA SHEET

Page 3 of 4
Revised 2/02/04
Replaces 1/13/04
Printed 2/03/04

ENVIRO LIFT AWAY

MSDS ID: 01912

X. STABILITY AND REACTIVITY (Cont.)

HAZARDOUS POLYMERIZATION: None known.

XI. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL TESTING: No data available.

TOXICITY TEST DATA:

No data available.

XII. ECOLOGICAL INFORMATION

ECOTOXICITY TEST DATA:

No data available.

ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Not Regulated.

Adjust pH of diluted product and discharge to industrial sewer in accordance with discharge permit or local POTW regulations. Use product in container until empty. Triple rinse container with water and add to process. Recycle or dispose of container according to product labeling or Federal, State or local regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: NONE

VOC CONTENT (EPA Method 24A): % VOC: 2.7 Lb/Gal VOC: 0.285

CERCLA/EPCRA:

Section 313 Toxic Chemicals:

NONE

SARA Section 311/312:

ACUTE: YES CHRONIC: NO FIRE: NO REACTIVITY: NO

SUDDEN RELEASE OF PRESSURE: NO

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 1 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: B

NFPA RATING: HEALTH: 1 FIRE: 0 REACTIVITY: 0 SPECIAL: ALKALI

STATE RIGHT-TO-KNOW INFORMATION:

DIETHANOLAMINE AND COCONUT OIL - CAS #68603-92-9

WATER - CAS #7732-18-5

SODIUM XYLENE SULFONATE - CAS# 1300-72-7

TALL OIL FATTY ACID - CAS# 61790-12-3

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 1/13/04
Printed 2/03/04

ENVIRO LIFT AWAY

MSDS ID: 01912

XV. REGULATORY INFORMATION (Cont.)

ETHYLENEDIAMINE TETRAACETIC ACID, TETRASODIUM SALT - CAS# 64-02-8

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

Disclaimer: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.