
MATERIAL SAFETY DATA SHEET

Page 1 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

FELT BRITE 300 CI**MSDS ID: 01987**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: FELT BRITE 300 CI

Product Descriptor: Acidic Felt Cleaner

MANUFACTURER: JOHNSON DIVERSEY, INC.

EMERGENCY PHONE NUMBER: (800) 851-7145

3630 E. KEMPER ROAD

CINCINNATI, OH. 45241

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
-----	-----	-----	-----	-----
LINEAR ALCOHOL ETHOXYLATE	68439-46-3	1 - 5%	None est.	
SULFURIC ACID	7664-93-9	>30%	TWA 1	MG/M3

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

CORROSIVE-Contains strong acids. Causes severe burns to skin and eyes. May be fatal if swallowed. Do not contact eyes, skin or clothing. Wear goggles, face shield, rubber gloves and protective clothing and boots when handling product. Avoid breathing dust or spray mist. Contain spill and runoff which may cause environmental damage. Contact with iron and other metals may release hydrogen gas.

POSSIBLE ROUTES OF ENTRY: Ingestion and Inhalation.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Severe burns, tissue damage, or irritation with pain, swelling, blurred or impaired vision, blindness. SKIN: Severe burns, tissue destruction, blisters or rash with swelling and pain. Diluted product may cause redness or irritation. INGESTION: If swallowed, severe burns to mouth and throat may result with pain, gastric perforation and difficulty in swallowing or breathing. INHALATION: Spray or mists cause burns or irritation to nose, throat and respiratory tract with pain, choking, and difficulty in breathing.

CHRONIC: Same as Acute Effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis and sensitive skin.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes, skin and respiratory tract.

IV. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Hold eyelids apart to completely flush all chemicals from entire eye surface. Get immediate medical attention.

SKIN: Flush thoroughly with plenty of water. Wash with soap and water. Remove contaminated clothes and shoes and clean before reuse. Get medical attention for any painful, red or injured skin.

INGESTION: If swallowed, rinse mouth with water. Dilute by drinking several

FELT BRITE 300 CI

MSDS ID: 01987

IV. FIRST AID MEASURES (Cont.)

glasses of water. DO NOT induce vomiting. If patient vomits, rerinse mouth with water. Get prompt medical attention. NOTE: Never give fluids by mouth to an unconscious person.

INHALATION: If inhaled, move to fresh air. If patient is not breathing, give artificial respiration. If breathing is difficult, give oxygen under the direction of trained personnel or a physician. Get medical attention.

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): N/A FLAME EXTENSION: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: NONE UEL: N/A
UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Liquid produces hydrogen on contact with steel or active metals.
EXTINGUISHING MEDIA: Water spray, CO2, foam or dry powder.
FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus (SCBA) in fire area.
SPECIAL INSTRUCTIONS: Contain runoff. Prevent from entering sewer or storm drain.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:
Contain spill. Absorb with sand or clay. Collect material and place in suitable waste container. Neutralize solids and spill area with dilute mineral acids or bicarbonate of soda. Dispose of by environmental regulations.
Reportable Quantity (RQ) of Sulfuric acid - CAS #7664-93-9 is 272 gallons or 2,860 Lbs.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Store in a cool, dry area. Keep from freezing. If frozen, return to producing plant. Keep container closed when not in use. Wear protective gear when handling or using. Do not pressurize container to empty.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Chemical goggles and face shield if contact or splash hazard exists. Eye wash in use area.
PROTECTIVE GLOVES: Acid resistant.
RESPIRATORY PROTECTION: Not normally required.
OTHER PROTECTIVE CLOTHING/EQUIPMENT: Rubber boots, chemical apron and safety shower in use area if contact or splash hazard exists.
ENGINEERING CONTROLS:
MECHANICAL VENTILATION: Normal room ventilation should be sufficient to control airborne levels.
LOCAL VENTILATION: Not usually required.

MATERIAL SAFETY DATA SHEET

Page 3 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

FELT BRITE 300 CI

MSDS ID: 01987

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear amber liquid with mild odor.

BOILING POINT (DEG F): 215	FREEZING POINT: Not determined
SPECIFIC GRAVITY/BULK DENSITY: 1.26	
pH: 1.0	pH 1% SOLUTION: 1.5
VOLATILE BY VOLUME: 70	
SOLUBILITY IN WATER: Soluble	
VAPOR PRESSURE(mmHg): 17.5 at 20 C	VAPOR DENSITY: ND

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.
INCOMPATIBILITY WITH OTHER MATERIALS: Alkalis, carbonates and chlorinated compounds.
HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms oxides of carbon, nitrogen and sulfur.
HAZARDOUS POLYMERIZATION: None known.

XI. TOXICOLOGICAL INFORMATION

Contains Corrosive and Irritating acidic chemicals. See Section II for amounts and identity. Acute toxicology tests are listed below.
TOXICITY TEST DATA:
Sulfuric acid: Acute Oral LD50 (rat) - 2140 mg/kg (RTECS)

XII. ECOLOGICAL INFORMATION

ECOTOXICITY DATA: Product and waste are harmful to fish and aquatic forms. Discharge process waste and overflow to a sanitary sewer or on-site treatment process.
ECOTOXICITY TEST DATA: No data available.
ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Waste concentrate is considered D002 Corrosive. Adjust pH of diluted product and discharge to industrial sewer. Use product in container until empty. Triple rinse container with water and add to process. Recycle or dispose of container by product labeling or governmental regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

FELT BRITE 300 CI**MSDS ID: 01987**

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: Contains no hazardous air pollutants.

VOC CONTENT (EPA Method 24A): % VOC: None Lb/Gal VOC:

CERCLA/EPCRA:

Section 313 Toxic Chemicals: None

SARA Section 311/312:

ACUTE: YES CHRONIC: NO FIRE: NO REACTIVITY: NO

SUDDEN RELEASE OF PRESSURE: NO

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 3 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: D

NFPA RATING: HEALTH: 3 FIRE: 0 REACTIVITY: 0 SPECIAL: ACID

STATE RIGHT-TO-KNOW INFORMATION:

Water - CAS #7732-18-4

Sulfuric acid CAS# 7764-93-9

Linear alcohol ethoxylate - CAS #68439-46-3

Sodium sulfooctadeconate - CAS #67998-94-1

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.