
MATERIAL SAFETY DATA SHEET

Page 1 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

FELT KLEEN 206CS**MSDS ID: 02006**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: FELT KLEEN 206CS
Product Descriptor: ACID PAPER MACHINE SYSTEM CLEANER.
MANUFACTURER: JOHNSON DIVERSEY, INC. EMERGENCY PHONE NUMBER: (800) 851-7145
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
-----	-----	-----	-----	-----
ACETIC ACID	64-19-7	5 - 15%	TWA 25 C 37	MG/M3

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

WARNING-Product contains irritating or harmful chemicals which may cause eye or skin irritation or burns. May be harmful if swallowed. Do not get product in eyes, on skin or clothing. Wear eye protection and rubber gloves to prevent skin contact when handling product. Wash after handling. Avoid breathing dust, vapors or product spray. Contain spill and runoff to prevent direct discharge to soil or surface waters.

POSSIBLE ROUTES OF ENTRY: Ingestion, Skin and Inhalation.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Severe burns or irritation with pain, redness, swelling, and blurred sight. SKIN: Burns, blisters or rash with pain and swelling. INGESTION: Burns or irritation to mouth, throat with pain, nausea and vomiting. INHALATION: Spray or mist causes pain, choking, and breathing difficulty.

CHRONIC: Same as Acute Effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis and sensitive skin.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes and skin.

IV. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for 15 minutes. Get medical attention.

SKIN: Flush thoroughly with plenty of water. Wash with soap and water. Remove contaminated clothes and shoes and clean before reuse. Get medical attention for any painful, red or injured skin.

INGESTION: Do not take internally. If swallowed, drink several glasses of water. Do not induce vomiting. Contact a physician or poison control center.

INHALATION: Remove to fresh air. If breathing difficulties arise, get medical attention.

MATERIAL SAFETY DATA SHEET

Page 2 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

FELT KLEEN 206CS**MSDS ID: 02006**

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F):NONE LEL:N/A UEL:N/A
UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Toxic fumes or vapor may form during fire.
EXTINGUISHING MEDIA: Water, water spray, CO2, foam or dry powder.
FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus (SCBA) in fire area.
SPECIAL INSTRUCTIONS: Contain runoff. Prevent from entering sewer or storm drain.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:
Contain spill. Absorb with sand or clay. Collect material and place in suitable waste container. Neutralize solids and spill area with dilute mineral acids or bicarbonate of soda. Dispose of by environmental regulations.
The Reportable Quantity (RQ) of Acetic Acid, CAS #64-19-7 is 4,311 gallons or 37,036 lbs.

VII. HANDLING AND STORAGE

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Chemical goggles and face shield if contact or splash hazard exists. Eye wash in use area.
PROTECTIVE GLOVES: Acid resistant.
OTHER PROTECTIVE CLOTHING/EQUIPMENT: Rubber boots and chemical resistant apron if contact or splash hazard exists.
ENGINEERING CONTROLS:
MECHANICAL VENTILATION: Normal room ventilation should be sufficient to control airborne levels.
LOCAL VENTILATION: Not usually required.

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear red solution with vinegar odor.

BOILING POINT (DEG F): 212°F	FREEZING POINT: Not determined
VAPOR PRESSURE(mmHg): 17.5 at 20 C	VAPOR DENSITY: ND
pH: 3.2	pH 1% SOLUTION: 3.6
VOLATILE BY VOLUME: ND	WEIGHT % SOLIDS: 19.6
SOLUBILITY IN WATER: Soluble	
SPECIFIC GRAVITY/BULK DENSITY: 1.03	

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.
INCOMPATIBILITY WITH OTHER MATERIALS: Alkalis, carbonates and chlorinated compounds.
HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms oxides of carbon.

MATERIAL SAFETY DATA SHEET

Page 3 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

FELT KLEEN 206CS

MSDS ID: 02006

X. STABILITY AND REACTIVITY (Cont.)

HAZARDOUS POLYMERIZATION: None known.

XI. TOXICOLOGICAL INFORMATION

Any hazardous effects of the product mixture are based on information for each chemical part. See Section II for amounts of hazardous materials.

TOXICITY TEST DATA:

No data available.

XII. ECOLOGICAL INFORMATION

ECOTOXICITY DATA: No data available.

ECOTOXICITY TEST DATA: No data available.

ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA CLASS: Not Regulated.

DISPOSAL: Adjust pH of diluted product and discharge to industrial sewer.
Use product in container until empty. Triple rinse container with water and add to process. Recycle or dispose of container by product labeling or governmental regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: Contains no hazardous air pollutants.

VOC CONTENT (PER 40 CFR PART 59): % VOC: 12.2 Lb/Gal VOC:

CERCLA/EPCRA:

SECTION 313 TOXIC CHEMICALS: None

SARA SECTION 311/312:

ACUTE: YES CHRONIC: NO FIRE: NO REACTIVITY: NO

SUDDEN RELEASE OF PRESSURE: NO

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATING: HEALTH: 2 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: D

NFPA RATING: HEALTH: 2 FIRE: 0 REACTIVITY: 0 SPECIAL:

STATE RIGHT-TO-KNOW INFORMATION:

WATER - CAS #7732-18-5

ACETIC ACID - CAS #64-19-7

POLYACRYLIC ACID - CAS #9003-01-4

CITRIC ACID - CAS #77-92-9

TETRASODIUM ETHYLENEDIAMINETETRAACETATE - CAS #64-02-8

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

FELT KLEEN 206CS

MSDS ID: 02006

XV. REGULATORY INFORMATION (Cont.)

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the applicability of this information for their particular conditions of storage, handling, and use.