
MATERIAL SAFETY DATA SHEET

Page 1 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

FG0-32**MSDS ID: 02060**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: FG0-32
PRODUCT DESCRIPTOR: FOOD GRADE HYDRAULIC LUBRICANT
MANUFACTURER: JOHNSON DIVERSEY, INC. EMERGENCY PHONE NUMBER: (800) 851-7145
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

II. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME(CAS NUMBER)	%	EXPOSURE LIMITS	UNITS
PETROLEUM DISTILLATES (8042-47-5)	<65	TLV 5; PEL 5; ST 10 (OIL MIST)	MG/M3

III. HAZARDS IDENTIFICATION

ROUTES OF ENTRY: INHALATION: YES
SKIN: NO
INGESTION: YES
SIGNS AND SYMPTOMS OF EXPOSURE:
ACUTE: DEFATS SKIN; MAY IRRITATE EYES.
CHRONIC: SAME AS ACUTE
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
Sensitive skin

IV. FIRST AID MEASURES

EYES: FLUSH THOROUGHLY WITH FRESH WATER. GET MEDICAL ATTENTION.
SKIN: FLUSH WITH FRESH WATER, WASH WITH SOAP AND WATER. REMOVE
CONTAMINATED CLOTHES AND SHOES. GET MEDICAL ATTENTION.
INGESTION: GIVE WATER, DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION. NEVER
GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
INHALATION: REMOVE TO FRESH AIR AND SEEK MEDICAL ATTENTION.

V. FIRE FIGHTING MEASURES

FLASH POINT: 360	DEG F	FLAME EXTENSION: N/A	IN.
FLAMMABLE LIMITS IN AIR BY VOLUME:		LEL: 1	UEL: 6
UNUSUAL FIRE OR EXPLOSION HAZARDS:	DO NOT STORE OR MIX WITH STRONG OXIDANTS.		
EXTINGUISHING MEDIA:	FOAM, DRY CHEMICAL, CO2		
FIRE FIGHTING INSTRUCTIONS:	USE AIR-SUPPLIED BREATHING EQUIPMENT IN ENCLOSED AREAS WEAR PROTECTIVE GEAR AND SELF CONTAINED BREATHING APPARATUS IN FIRE AREA.		

MATERIAL SAFETY DATA SHEET

Page 2 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

FGO-32**MSDS ID: 02060**

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED: CONTAIN THE SPILL. PREVENT SPILL FROM ENTERING SEWER. RECOVER FREE LIQUID AND/OR COLLECT WITH INERT OIL ABSORBENT. PLACE ABSORBENT INTO METAL CONTAINER FOR DISPOSAL. CLEAN SPILL AREA WITH DETERGENT OR SOLVENTIZED CLEANER.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: STORE CONTAINERS CLOSED IN A CLEAN, DRY AREA. KEEP AWAY FROM HEAT, OPEN FLAME, AND OXIDIZING AGENTS. DO NOT PRESSURIZE CONTAINER TO EMPTY.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: SAFETY GLASSES
PROTECTIVE GLOVES: RUBBER OR NEOPRENE FOR PROLONGED CONTACT
RESPIRATORY PROTECTION: NORMALLY NOT NEEDED
OTHER PROTECTIVE CLOTHING/EQUIPMENT: OIL-IMPERVIOUS APRON IF NEEDED
EXPOSURE GUIDELINES: SEE SECTION II FOR DETAILED INFORMATION.

IX. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (F): N/A SPECIFIC GRAVITY: 0.8500
VOLATILE BY VOLUME: N/A SOLUBILITY IN WATER: NONE
VAPOR PRESSURE (MMHG): <1 AT 20 C
APPEARANCE AND ODOR: CLEAR, WATER-WHITE LIQUID WITH MILD ODOR

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE
INCOMPATIBILITY WITH OTHER MATERIALS: STRONG OXIDANTS LIKE LIQUID O2
HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE IN CASE OF INCOMPLETE COMBUSTION.
HAZARDOUS POLYMERIZATION: NONE

XI. TOXICOLOGICAL INFORMATION

NO DATA AVAILABLE

XII. ECOLOGICAL INFORMATION

NO DATA AVAILABLE

XIII. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: INCINERATE ABSORBED MATERIAL. USE UNTIL LESS THAN 1 INCH REMAINS IN CONTAINER, EMPTY CONTAINER TRIPLE RINSE WITH KEROSENE OR AVAILABLE SOLVENT, BURN LIQUID REMOVE OR DEFACE LABEL BEFORE SELLING CONTAINER OR DISPOSAL

MATERIAL SAFETY DATA SHEET

Page 3 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

FGO-32

MSDS ID: 02060

XIV. TRANSPORT INFORMATION

HAZARDOUS MATERIALS DESCRIPTION/PROPER SHIPPING NAME:

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CERCLA/EPCRA:SECTION 313 TOXIC CHEMICALS:

ALL CHEMICAL INGREDIENTS ARE LISTED ON THE TSCA INVENTORY.

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 1 FIRE: 1 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: B

STATE RIGHT-TO-KNOW INFORMATION:

WHITE MINERAL OIL - CAS #8042-47-5

TRADE SECRET REGISTRATION: 694954-00-1-5120P

XVI. OTHER INFORMATION

THE INFORMATION IN THIS MSDS RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED OTHER THAN AS RECOMMENDED BY DIVERSEY LEVER OR IN COMBINATION WITH OTHER MATERIALS. IT IS THE USER'S RESPONSIBILITY TO EVALUATE THE APPLICABILITY OF THIS INFORMATION FOR HIS PARTICULAR CONDITIONS OF STORAGE, HANDLING AND USE.