
MATERIAL SAFETY DATA SHEET

Page 1 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

PEEL FILMITE**MSDS ID: 02165**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: PEEL FILMITE
PRODUCT DESCRIPTOR: VINYL RESIN IN SOLVENT
MANUFACTURER: JOHNSON DIVERSEY, INC. EMERGENCY PHONE NUMBER: (800) 851-7145
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

II. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME(CAS NUMBER)	%	EXPOSURE LIMITS	UNITS
TOLUENE (108-88-3)	<40	TLV 100; PEL 200; C 300; MP 500; ST 150	PPM
METHYLENE CHLORIDE (75-09-2)	<45	TLV 50; PEL 500; C 1000; MP 2000	PPM

III. HAZARDS IDENTIFICATION

ROUTES OF ENTRY: INHALATION: YES
SKIN: YES
INGESTION: YES
SIGNS AND SYMPTOMS OF EXPOSURE:
ACUTE: MAY IRRITATE SKIN AND EYES. BREATHING VAPORS MAY CAUSE
DIZZINESS.
CHRONIC: SAME AS ACUTE
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
SENSITIVE SKIN, EYES

IV. FIRST AID MEASURES

EYES: FLUSH THOROUGHLY WITH FRESH WATER. GET MEDICAL ATTENTION.
SKIN: FLUSH WITH FRESH WATER, WASH WITH SOAP AND WATER GET MEDICAL
ATTENTION. REMOVE CONTAMINATED CLOTHES AND SHOES.
INGESTION: GIVE MILK, WATER OR EGG WHITES DO NOT INDUCE VOMITING, GET MEDICAL
ATTENTION
INHALATION: Remove to fresh air.

V. FIRE FIGHTING MEASURES

FLASH POINT: 143 DEG F	FLAME EXTENSION: N/A IN.
FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: 14% UEL: 22%	
UNUSUAL FIRE OR EXPLOSION HAZARDS: EXTREME HEAT MAY PRODUCE HYDROCHLORIC ACID	
EXTINGUISHING MEDIA: CO2, DRY CHEMICALS, WATER FOG	
FIRE FIGHTING INSTRUCTIONS: WEAR SELF-CONTAINED POSITIVE PRESSURE BREATHING APPARATUS	

MATERIAL SAFETY DATA SHEET

Page 2 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

PEEL FILMITE

MSDS ID: 02165

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED: COLLECT WITH FLOOR DRY MATERIAL, ALLOW SOLVENTS TO EVAPORATE AND DISPOSE OF FILM FORMED.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: DO NOT PRESSURE CONTAINER TO EMPTY. AVOID FREEZING; STORE IN COOL PLACE; OPEN BUNGS SLOWLY TO RELEASE ANY PRESSURE. VAPORS ARE HEAVIER THAN AIR.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: FACE SHIELD
PROTECTIVE GLOVES: SOLVENT RESISTANT
RESPIRATORY PROTECTION: PAINT SPRAYING TYPE.
OTHER PROTECTIVE CLOTHING/EQUIPMENT: NONE
EXPOSURE GUIDELINES: SEE SECTION II FOR DETAILED INFORMATION.

IX. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (F): 105 SPECIFIC GRAVITY: 1.0660
VOLATILE BY VOLUME: 70 SOLUBILITY IN WATER: <0.1
VAPOR PRESSURE (MMHG): <300 AT 20 C
APPEARANCE AND ODOR: OPAQUE WHITE SLIGHTLY VISCOUS LIQUID; SOLVENT ODOR.

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE
INCOMPATIBILITY WITH OTHER MATERIALS: SOFT METALS, STRONG ACIDS, OXIDIZERS
HAZARDOUS DECOMPOSITION PRODUCTS: HCL AND PHOSGENE WITH INCOMPLETE COMBUSTION
HAZARDOUS POLYMERIZATION: NONE

XI. TOXICOLOGICAL INFORMATION

NO DATA AVAILABLE

XII. ECOLOGICAL INFORMATION

NO DATA AVAILABLE

XIII. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: USE UNTIL LESS THAN 1 INCH REMAINS IN CONTAINER, EMPTY CONTAINER HAVE RESIDUE HAULED BY QUALIFIED WASTE HAULER REMOVE OR DEFACE LABEL BEFORE SELLING CONTAINER OR DISPOSAL F001

MATERIAL SAFETY DATA SHEET

Page 3 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

PEEL FILMITE

MSDS ID: 02165

XIV. TRANSPORT INFORMATION

HAZARDOUS MATERIALS DESCRIPTION/PROPER SHIPPING NAME:

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CERCLA/EPCRA:SECTION 313 TOXIC CHEMICALS:

PEEL FILMITE CONTAINS THESE SARA TITLE III SECTION 313 CHEMICALS AS INGREDIENTS IN THE FOLLOWING CONCENTRATIONS: DICHLOROMETHANE (METHYLENE CHLORIDE) CAS #75-09-2 AT 43% AND TOLUENE CAS #108-88-3 AT 35%.

LISTED CARCINOGEN: METHYLENE CHLORIDE

NTP: NO IARC: YES OSHA: NO

HMIS RATINGS: HEALTH: 2 FIRE: 2 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: D

STATE RIGHT-TO-KNOW INFORMATION:

METHYLENE CHLORIDE - CAS #75-09-2

TOLUENE - CAS #108-88-3

VINYL RESIN - CAS #9003-22-9

DIOCTYL TEREPHTHALATE - CAS #6422-86-2

XVI. OTHER INFORMATION

THE INFORMATION IN THIS MSDS RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED OTHER THAN AS RECOMMENDED BY DIVERSEY LEVER OR IN COMBINATION WITH OTHER MATERIALS. IT IS THE USER'S RESPONSIBILITY TO EVALUATE THE APPLICABILITY OF THIS INFORMATION FOR HIS PARTICULAR CONDITIONS OF STORAGE, HANDLING AND USE.