
MATERIAL SAFETY DATA SHEET

Page 1 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

PIGMENTED FILMITE**MSDS ID: 02168**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: PIGMENTED FILMITE
PRODUCT DESCRIPTOR: BOOTH COATING COMPOUND
MANUFACTURER: JOHNSON DIVERSEY, INC. EMERGENCY PHONE NUMBER: (800) 851-7145
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

II. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME(CAS NUMBER)	%	EXPOSURE LIMITS	UNITS
KAOLIN (1318-74-7)	<50	PEL 5, TLV 10	MG/M3

III. HAZARDS IDENTIFICATION

ROUTES OF ENTRY: INHALATION: NO
SKIN: NO
INGESTION: NO
SIGNS AND SYMPTOMS OF EXPOSURE:
ACUTE: MAY IRRITATE EYES
CHRONIC: SAME AS ACUTE
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
Sensitive skin

IV. FIRST AID MEASURES

EYES: FLUSH THOROUGHLY WITH FRESH WATER. GET MEDICAL ATTENTION.
SKIN: FLUSH WITH FRESH WATER, WASH WITH SOAP AND WATER. REMOVE
CONTAMINATED CLOTHES AND SHOES. GET MEDICAL ATTENTION.
INGESTION: GIVE MILK OR WATER, INDUCE VOMITING. GET MEDICAL ATTENTION. NEVER
GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
INHALATION: N/A IN NORMAL OPERATION

V. FIRE FIGHTING MEASURES

FLASH POINT: NONE	DEG F	FLAME EXTENSION: N/A	IN.
FLAMMABLE LIMITS IN AIR BY VOLUME:		LEL: NONE	UEL: NONE
UNUSUAL FIRE OR EXPLOSION HAZARDS:		NONE KNOWN	
EXTINGUISHING MEDIA:		CO2, FOAM, DRY CHEMICALS	
FIRE FIGHTING INSTRUCTIONS:		NONE	

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED: COLLECT AND DISPOSE SMALL AMOUNTS TO SOLID WASTE; COLLECT AND RETURN LARGE AMOUNTS TO CONTAINER.

MATERIAL SAFETY DATA SHEET

Page 2 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

PIGMENTED FILMITE**MSDS ID: 02168**

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: KEEP FROM FREEZING. KEEP DRUM COVERED. DO NOT PRESSURE CONTAINER TO EMPTY.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: NONE
PROTECTIVE GLOVES: NONE
RESPIRATORY PROTECTION: NONE
OTHER PROTECTIVE CLOTHING/EQUIPMENT: NONE
EXPOSURE GUIDELINES: SEE SECTION II FOR DETAILED INFORMATION.

IX. PHYSICAL AND CHEMICAL PROPERTIES

BOILIING POINT (F): 200 SPECIFIC GRAVITY: 1.2000
VOLATILE BY VOLUME: 40 SOLUBILITY IN WATER: <1
VAPOR PRESSURE (MMHG): 17.5 AT 20 C
APPEARANCE AND ODOR: OPAQUE VISCOUS LIQUID; MILD ODOR

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE
INCOMPATIBILITY WITH OTHER MATERIALS: UNK
HAZARDOUS DECOMPOSITION PRODUCTS: CO WITH INCOMPLETE COMBUSTION
HAZARDOUS POLYMERIZATION: NONE

XI. TOXICOLOGICAL INFORMATION

NO DATA AVAILABLE

XII. ECOLOGICAL INFORMATION

NO DATA AVAILABLE

XIII. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: PH ADJUSTMENT; SEPARATION OF INSOLUBLES; NO PHOSPHATES. USE UNTIL LESS THAN 1 INCH REMAINS IN CONTAINER, EMPTY CONTAINER TRIPLE RINSE WITH WATER, ADD TO OPERATION REMOVE OR DEFACE LABEL BEFORE SELLING CONTAINER OR DISPOSAL

XIV. TRANSPORT INFORMATION

HAZARDOUS MATERIALS DESCRIPTION/PROPER SHIPPING NAME:
Please refer to the Bill of Lading/receiving documents for up to date shipping information.

MATERIAL SAFETY DATA SHEET

Page 3 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

PIGMENTED FILMITE

MSDS ID: 02168

XV. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CERCLA/EPCRA:SECTION 313 TOXIC CHEMICALS:

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 1 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: B

STATE RIGHT-TO-KNOW INFORMATION:

WATER - CAS #7732-18-5

KAOLIN - CAS #1318-74-7

PROPYLENE GLYCOL - CAS #57-55-6

SODIUM PETROLEUM SULFONATE - CAS #68608-26-4

XVI. OTHER INFORMATION

THE INFORMATION IN THIS MSDS RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED OTHER THAN AS RECOMMENDED BY DIVERSEY LEVER OR IN COMBINATION WITH OTHER MATERIALS. IT IS THE USER'S RESPONSIBILITY TO EVALUATE THE APPLICABILITY OF THIS INFORMATION FOR HIS PARTICULAR CONDITIONS OF STORAGE, HANDLING AND USE.