

INSTANT 911

MSDS ID: 02438

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: INSTANT 911
PRODUCT DESCRIPTOR: ABSORBING AGENT
MANUFACTURER: JOHNSON DIVERSEY, INC. EMERGENCY PHONE NUMBER: (800) 851-7145
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

II. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME(CAS NUMBER)	%	EXPOSURE LIMITS	UNITS
SILICA-CRYSTALLINE QUARTZ (14808-60-7)	<10	TLV 0.1; PEL 0.1 (RESPIRABLE DUST)	MG/M3

NOTE: ACTIVE OXIDIZING AGENTS
MAY IMPAIR GELLING
AND IMPEDE CLEAN UP
CAPABILITIES.

III. HAZARDS IDENTIFICATION

ROUTES OF ENTRY: INHALATION: YES
SKIN: NO
INGESTION: NO

SIGNS AND SYMPTOMS OF EXPOSURE:
ACUTE: DUSTS MAY CAUSE SKIN OR EYE IRRITATION; MAY CAUSE RESPIRATORY DISCOMFORT.
CHRONIC: PROLONGED DUST INHALATION MAY CAUSE DELAYED RESPIRATORY DISEASE. IARC DETERMINED THAT THERE IS SUFFICIENT EVIDENCE OF CARCINOGENICITY OF CRYSTALLINE SILICA TO EXPERIMENTAL ANIMALS. THERE IS LIMITED EVIDENCE OF THE CARCINOGENICITY OF CRYSTALLINE SILICA TO HUMANS.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
Sensitive skin

IV. FIRST AID MEASURES

EYES: FLUSH THOROUGHLY WITH FRESH WATER. IF IRRITATION CONTINUES, GET MEDICAL ATTENTION.

SKIN: FLUSH WITH FRESH WATER. REMOVE CONTAMINATED CLOTHES AND SHOES.

INGESTION: GIVE MILK OR WATER. INDUCE VOMITING. GET MEDICAL ATTENTION.

INHALATION: REMOVE TO FRESH AIR AND SEEK MEDICAL ATTENTION.

V. FIRE FIGHTING MEASURES

FLASH POINT: N/A DEG F FLAME EXTENSION: N/A IN.

FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: N/A UEL: N/A

UNUSUAL FIRE OR EXPLOSION HAZARDS: USE STANDARD PROCEDURES FOR POLYMERS WHICH MAY MELT IF EXPOSED TO HEAT OR FLAME.

MATERIAL SAFETY DATA SHEET

Page 2 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

INSTANT 911**MSDS ID: 02438**

V. FIRE FIGHTING MEASURES (Cont.)

EXTINGUISHING MEDIA: CO2, FOAM, WATER, DRY CHEMICAL
FIRE FIGHTING INSTRUCTIONS: BECOMES SLIPPERY WHEN WET.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED: AVOID BREATHING DUST. WET DOWN AND COLLECT SMALL AMOUNTS FOR DISPOSAL. VACUUM OR SHOVEL UP LARGE AMOUNTS; RETURN TO CONTAINER. ADDING WATER TO RAW HYDROFLUORIC/SULFURIC ACIDS, CAUSTIC SODA OR OXIDIZING MATERIALS WILL RESULT IN A VIOLENT REACTION.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: STORE AWAY FROM MOISTURE. KEEP CONTAINER CLOSED IN STORAGE. AVOID BREATHING DUST. KEEP AWAY FROM CHILDREN.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: GOGGLES WHEN HANDLING VOLUME
PROTECTIVE GLOVES: WHEN HANDLING VOLUME
RESPIRATORY PROTECTION: USE NIOSH/MSHA-APPROVED RESPIRATORY WHERE TLV/PEL FOR CRYSTALLINE SILICA MAY BE EXCEEDED.
OTHER PROTECTIVE CLOTHING/EQUIPMENT: WHEN APPLYING LARGE AMOUNTS, WEAR GOGGLES, DUST MASKS AND GLOVES.
EXPOSURE GUIDELINES: SEE SECTION II FOR DETAILED INFORMATION.

IX. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (F): N/A SPECIFIC GRAVITY: 0.3100
VOLATILE BY VOLUME: N/A SOLUBILITY IN WATER: <1
VAPOR PRESSURE (MMHG): N/A AT
APPEARANCE AND ODOR: WHITE, FREE-FLOWING POWDER

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE
INCOMPATIBILITY WITH OTHER MATERIALS: OPTIONALLY WATER-ACTIVATED: *IF WATER IS TO BE ADDED, AVOID MIXING WITH RAW CHEMICALS THAT REACT ADVERSELY WITH WATER.
HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF CARBON AND HYDROGEN
HAZARDOUS POLYMERIZATION: *SEE BELOW

XI. TOXICOLOGICAL INFORMATION

NO DATA AVAILABLE

MATERIAL SAFETY DATA SHEET

Page 3 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

INSTANT 911

MSDS ID: 02438

XII. ECOLOGICAL INFORMATION

NO DATA AVAILABLE

XIII. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: IF CONTAINS TOXIC OR HAZARDOUS SPILL MATERIALS, SHIP IN CLOSED LABELED CONTAINER APPLICABLE TO THE SPILLED TOXIC OR HAZARDOUS MATERIAL AND IN COMPLIANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

XIV. TRANSPORT INFORMATION

HAZARDOUS MATERIALS DESCRIPTION/PROPER SHIPPING NAME:
Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:
CERCLA/EPCRA:SECTION 313 TOXIC CHEMICALS:
NONE
LISTED CARCINOGEN: SILICA-CRYSTALLINE QUARTZ
NTP: NO IARC: YES OSHA: NO
HMIS RATINGS: HEALTH: 1 FIRE: 0 REACTIVITY: 0
PERSONAL PROTECTIVE EQUIPMENT: E
STATE RIGHT-TO-KNOW INFORMATION:
FLUX CALCINED DIATOMACEOUS EARTH - CAS #68855-54-9
SILICA-CRYSTALLINE QUARTZ - CAS #14808-60-7
TRADE SECRET REGISTRATION: 694954-00-1-5163P

XVI. OTHER INFORMATION

THE INFORMATION IN THIS MSDS RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED OTHER THAN AS RECOMMENDED BY DIVERSEY LEVER OR IN COMBINATION WITH OTHER MATERIALS. IT IS THE USER'S RESPONSIBILITY TO EVALUATE THE APPLICABILITY OF THIS INFORMATION FOR HIS PARTICULAR CONDITIONS OF STORAGE, HANDLING AND USE.