

MATERIAL SAFETY DATA SHEET

Page 1 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

JAO - 6 AEROSOL

MSDS ID: 02506

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: JAO - 6 AEROSOL
PRODUCT DESCRIPTOR: RUST INHIBITOR/LUBRICANT/DEMOISTURANT/PENETRANT
MANUFACTURER: JOHNSON DIVERSEY, INC. EMERGENCY PHONE NUMBER: (800) 851-7145
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

II. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME(CAS NUMBER)	%	EXPOSURE LIMITS	UNITS
PETROLEUM DISTILLATE (8008-20-6)	<90	TLV 400; PEL 400	PPM
CARBON DIOXIDE (124-38-9)	<3	TLV 5,000; PEL 10,000 ST 30,000	PPM

III. HAZARDS IDENTIFICATION

ROUTES OF ENTRY: INHALATION: YES
SKIN: NO
INGESTION: YES
SIGNS AND SYMPTOMS OF EXPOSURE:
ACUTE: DEFATS SKIN; MAY IRRITATE EYES. OVEREXPOSURE TO VAPOR OR
MIST MAY CAUSE DIZZINESS OR HEADACHE.
CHRONIC: SAME AS ACUTE
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
Sensitive skin

IV. FIRST AID MEASURES

EYES: FLUSH THOROUGHLY WITH FRESH WATER, FOR AT LEAST 15 MINUTES. GET
MEDICAL ATTENTION.
SKIN: FLUSH WITH FRESH WATER, WASH WITH SOAP AND WATER. REMOVE
CONTAMINATED CLOTHES AND SHOES. GET MEDICAL ATTENTION.
INGESTION: GIVE WATER. DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION. NEVER
GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
INHALATION: Remove to fresh air.

V. FIRE FIGHTING MEASURES

FLASH POINT: 140 DEG F FLAME EXTENSION: >18 IN.
FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: 1.0 UEL: 6.0
UNUSUAL FIRE OR EXPLOSION HAZARDS: NONE KNOWN
EXTINGUISHING MEDIA: CO2, FOAM, DRY CHEMICALS
FIRE FIGHTING INSTRUCTIONS: SAME AS FOR KEROSENE TYPE SOLVENTS

MATERIAL SAFETY DATA SHEET

Page 2 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

JAO - 6 AEROSOL

MSDS ID: 02506

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED: COLLECT WITH FLOOR DRYING MATERIAL AND DISPOSE TO SOLID WASTES.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: NO SPECIAL SEPARATION; STORE INSIDE OR OUTSIDE; DO NOT STORE NEAR HEAT OR OPEN FLAMES. DO NOT PRESSURE CONTAINER TO EMPTY.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: FACE SHIELD
PROTECTIVE GLOVES: SOLVENT RESISTANT
RESPIRATORY PROTECTION: NONE
OTHER PROTECTIVE CLOTHING/EQUIPMENT: NONE
EXPOSURE GUIDELINES: SEE SECTION II FOR DETAILED INFORMATION.

IX. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (F): 400 SPECIFIC GRAVITY: 0.8240
VOLATILE BY VOLUME: UNK SOLUBILITY IN WATER: <1
VAPOR PRESSURE (MMHG): N/A AT
APPEARANCE AND ODOR: BROWN LIQUID, MILD ODOR

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE
INCOMPATIBILITY WITH OTHER MATERIALS: NONE KNOWN
HAZARDOUS DECOMPOSITION PRODUCTS: CO, SO2 INCOMPLETE COMBUSTION
HAZARDOUS POLYMERIZATION: NONE

XI. TOXICOLOGICAL INFORMATION

NO DATA AVAILABLE

XII. ECOLOGICAL INFORMATION

NO DATA AVAILABLE

XIII. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: DO NOT INCINERATE. DISCHARGE PROPELLANT BEFORE DISPOSAL. DISPOSE AS AN AEROSOL.

XIV. TRANSPORT INFORMATION

HAZARDOUS MATERIALS DESCRIPTION/PROPER SHIPPING NAME:
Please refer to the Bill of Lading/receiving documents for up to date shipping information.

MATERIAL SAFETY DATA SHEET

Page 3 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

JAO - 6 AEROSOL

MSDS ID: 02506

XV. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CERCLA/EPCRA:SECTION 313 TOXIC CHEMICALS:

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 2 FIRE: 3 REACTIVITY: 1

PERSONAL PROTECTIVE EQUIPMENT: A

STATE RIGHT-TO-KNOW INFORMATION:

KEROSENE - CAS #8008-20-6

PETROLEUM OIL - CAS #64742-65-0

CARBON DIOXIDE - CAS #124-38-9

XVI. OTHER INFORMATION

THE INFORMATION IN THIS MSDS RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED OTHER THAN AS RECOMMENDED BY DIVERSEY LEVER OR IN COMBINATION WITH OTHER MATERIALS. IT IS THE USER'S RESPONSIBILITY TO EVALUATE THE APPLICABILITY OF THIS INFORMATION FOR HIS PARTICULAR CONDITIONS OF STORAGE, HANDLING AND USE.