

SUPER LIFT

MSDS ID: 02554

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: SUPER LIFT

Product Descriptor: Cleaner

MANUFACTURER: JOHNSON DIVERSEY, INC.
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

EMERGENCY PHONE NUMBER: (800) 851-7145

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
LINEAR ALCOHOL ETHOXYLATE	68439-46-3	1 - 5%	None est.	
SODIUM HYDROXIDE	1310-73-2	1 - 5%	TLV-C 2	MG/M3
SODIUM METASILICATE	6834-92-0	1 - 5%	None established	

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

CORROSIVE-Contains strong alkali. Causes severe burns to skin and eyes. May be fatal if swallowed. Do not contact eyes, skin or clothing. Wear goggles, face shield, rubber gloves, and protective clothing and boots when handling product. Avoid breathing dust or spray mist. Contain spill or runoff which may cause environmental damage. Contact with aluminum or soft metals may release hydrogen gas.

POSSIBLE ROUTES OF ENTRY: Ingestion, Skin and Inhalation.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Severe burns or irritation with pain, redness, swelling, and blurred sight. SKIN: Burns, blisters or rash with pain and swelling. INGESTION: Burns or irritation to mouth, throat with pain, nausea and vomiting. INHALATION: Spray or mist causes pain, choking, and breathing difficulty.

CHRONIC: Same as Acute Effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis and sensitive skin.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes, skin and respiratory tract.

IV. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for 15 minutes. Get medical attention.

SKIN: Flush thoroughly with plenty of water. Wash with soap and water. Remove contaminated clothes and shoes and clean before reuse. Get medical attention for any painful, red or injured skin.

INGESTION: If swallowed, rinse mouth with water. Dilute by drinking several glasses of water. DO NOT induce vomiting. If patient vomits, rerinse mouth with water. Get prompt medical attention. NOTE: Never give fluids by mouth to an unconscious person.

Page	2 of 4
Revised	2/02/04
Replaces	8/12/03
Printed	2/03/04

MSDS ID: 02554

INHALATION: Remove to fresh air. If breathing difficulties continue, get medical attention.

FLASH POINT (degrees F): NONE FLAME EXTENSION: NONE
FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: N/A UEL: N/A
UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Liquid produces hydrogen on contact with soft, active metals.
EXTINGUISHING MEDIA: Water spray, CO2, foam or dry powder.
FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus (SCBA) in fire area.
SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

IF MATERIAL IS RELEASED OR SPILLED:
Contain spill. Absorb with sand or clay. Collect material and place in suitable waste container. Neutralize solids and spill area with soda ash or lime. Dispose of by environmental regulations.
This product does not contain a reportable quantity (RQ) under CERCLA.

HANDLING AND STORAGE PRECAUTIONS: Store in a cool, dry area. Keep from freezing. If frozen, return to producing plant. Keep container closed when not in use. Wear protective gear when handling or using. Do not pressurize container to empty.

EYE/FACE PROTECTION: Face shield if contact or splash hazard exists. Eye wash in use area.

PROTECTIVE GLOVES: Alkali resistant.

RESPIRATORY PROTECTION: Not normally required.

OTHER PROTECTIVE CLOTHING/EQUIPMENT: Rubber boots, chemical apron and safety shower in use area if contact or splash hazard exists.

ENGINEERING CONTROLS:

MECHANICAL VENTILATION: Normal room ventilation should be sufficient to control airborne levels.

LOCAL VENTILATION: Not usually required.

APPEARANCE AND ODOR: Clear purple liquid with mild citrus odor.

BOILING POINT (DEG F): 210
SPECIFIC GRAVITY/BULK DENSITY: 1.07
pH: 13.8

FREEZING POINT: ND

pH 1% SOLUTION: 11.9

MATERIAL SAFETY DATA SHEET

Page 3 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

SUPER LIFT

MSDS ID: 02554

IX. PHYSICAL AND CHEMICAL PROPERTIES (Cont.)

VOLATILE BY VOLUME: ND
SOLUBILITY IN WATER: Soluble
VAPOR PRESSURE(mmHg): 17.5 at 20 C VAPOR DENSITY: >AIR

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.
INCOMPATIBILITY WITH OTHER MATERIALS: Strong acids, strong oxidizers.
HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms oxides of carbon.
HAZARDOUS POLYMERIZATION: None known.

XI. TOXICOLOGICAL INFORMATION

Contains Corrosive and Irritating alkaline chemicals. See Section II for amounts and identity. Acute toxicology tests are listed below.
TOXICITY TEST DATA:
Sodium hydroxide: Acute Oral LD50 (rat) - 500 mg/kg (RTECS)
Acute Skin LD50 (rabbit) - 1350 mg/kg (MSI)
Sodium metasilicate: Acute Oral LD50 (rat) - 1153 mg/kg (RTECS)

XII. ECOLOGICAL INFORMATION

ECOTOXICITY DATA: Product and waste are harmful to fish and aquatic forms. Discharge process waste and overflow to a sanitary sewer or on-site treatment process.
ECOTOXICITY TEST DATA: No data available.
ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Concentrated product would be considered D002- corrosive if declared hazardous waste.
Contains phosphates. Adjust pH of diluted product and discharge to industrial sewer. Use product in container until empty. Triple rinse container with water and add to process. Recycle or dispose of container by product labeling or governmental regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:
TSCA: All ingredients in this product are on TSCA inventory.
HAPS: Contains no hazardous air pollutants.
VOC CONTENT (EPA Method 24A): % VOC: 4.15 Lb/Gal VOC: 0.37
CERCLA/EPCRA:

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

SUPER LIFT**MSDS ID: 02554**

XV. REGULATORY INFORMATION (Cont.)

Section 313 Toxic Chemicals: None

SARA Section 311/312:

ACUTE: YES CHRONIC: NO FIRE: NO REACTIVITY: NO
SUDDEN RELEASE OF PRESSURE: NO

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 3 FIRE: 0 REACTIVITY: 0
PERSONAL PROTECTIVE EQUIPMENT: D

NFPA RATING: HEALTH: 3 FIRE: 0 REACTIVITY: 0 SPECIAL: CORROSIVE

STATE RIGHT-TO-KNOW INFORMATION:

WATER - CAS #7732-18-5

3-METHOXY-3-METHYL-1-BUTANOL - CAS #56539-66-3

LINEAR ALCOHOL ETHOXYLATE - CAS #68439-46-3

DODECYL BENZENE SULFONIC ACID, SODIUM SALT - CAS #25155-30-0

SODIUM METASILICATE - CAS #6834-92-0

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.