
MATERIAL SAFETY DATA SHEET

Page 1 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

LUBRICOOLANT EP**MSDS ID: 02796**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: LUBRICOOLANT EP
PRODUCT DESCRIPTOR: OIL BASED CUTTING FLUID
MANUFACTURER: JOHNSON DIVERSEY, INC. EMERGENCY PHONE NUMBER: (800) 851-7145
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

II. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME(CAS NUMBER)	%	EXPOSURE LIMITS	UNITS
NAPHTHENIC OIL (64782-52-5)	<65	TLV 5; PEL 5; STEL 10 (OIL MIST)	MG/M3

III. HAZARDS IDENTIFICATION

ROUTES OF ENTRY: INHALATION: NO
SKIN: NO
INGESTION: NO
SIGNS AND SYMPTOMS OF EXPOSURE:
ACUTE: DEFATS SKIN; MAY IRRITATE EYES
CHRONIC: SAME AS ACUTE
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
Sensitive skin

IV. FIRST AID MEASURES

EYES: FLUSH THOROUGHLY WITH FRESH WATER. GET MEDICAL ATTENTION.
SKIN: FLUSH WITH FRESH WATER, WASH WITH SOAP AND WATER. REMOVE
CONTAMINATED CLOTHES AND SHOES. GET MEDICAL ATTENTION.
INGESTION: GIVE WATER. DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION. NEVER
GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
INHALATION: N/A IN NORMAL OPERATION

V. FIRE FIGHTING MEASURES

FLASH POINT: 315 DEG F	FLAME EXTENSION: N/A	IN.
FLAMMABLE LIMITS IN AIR BY VOLUME:	LEL: 1.0 UEL: 7.0	
UNUSUAL FIRE OR EXPLOSION HAZARDS:	NONE KNOWN	
EXTINGUISHING MEDIA:	CO2, DRY CHEMICALS	
FIRE FIGHTING INSTRUCTIONS:	NONE	

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED: WIPE UP SMALL AMOUNTS AND DISCARD TO SOLID WASTE OR BURN. COLLECT AND RETURN LARGE AMOUNTS TO CONTAINER.

MATERIAL SAFETY DATA SHEET

Page 2 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

LUBRICOOLANT EP**MSDS ID: 02796**

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: NO SPECIAL SEPARATION; STORE INSIDE OR OUTSIDE. DO NOT PRESSURE CONTAINER TO EMPTY.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: FACE SHIELD, SAFETY GLASSES OR GOGGLES
PROTECTIVE GLOVES: OIL RESISTANT
RESPIRATORY PROTECTION: NONE
OTHER PROTECTIVE CLOTHING/EQUIPMENT: NONE
EXPOSURE GUIDELINES: SEE SECTION II FOR DETAILED INFORMATION.

IX. PHYSICAL AND CHEMICAL PROPERTIES

BOILIING POINT (F): 365 SPECIFIC GRAVITY: 0.9620
VOLATILE BY VOLUME: 0 SOLUBILITY IN WATER: 2.5
VAPOR PRESSURE (MMHG): N/A AT
APPEARANCE AND ODOR: BROWN LIQUID; MILD ODOR

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE
INCOMPATIBILITY WITH OTHER MATERIALS: STRONG OXIDIZERS
HAZARDOUS DECOMPOSITION PRODUCTS: CO WITH INCOMPLETE COMBUSTION; CHLORINE
RELEASE ABOUT 600F
HAZARDOUS POLYMERIZATION: NONE

XI. TOXICOLOGICAL INFORMATION

NO DATA AVAILABLE

XII. ECOLOGICAL INFORMATION

NO DATA AVAILABLE

XIII. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: EMULSION BREAKING AND SEPARATION OF INSOLUBLES. DOES NOT CONTAIN PHOSPHOROUS. USE UNTIL LESS THAN 1 INCH REMAINS IN CONTAINER, EMPTY CONTAINER TRIPLE RINSE WITH WATER, ADD TO OPERATION REMOVE OR DEFACE LABEL BEFORE SELLING CONTAINER OR DISPOSAL

XIV. TRANSPORT INFORMATION

HAZARDOUS MATERIALS DESCRIPTION/PROPER SHIPPING NAME:
Please refer to the Bill of Lading/receiving documents for up to date shipping information.

MATERIAL SAFETY DATA SHEET

Page 3 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

LUBRICOLANT EP

MSDS ID: 02796

XV. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CERCLA/EPCRA:SECTION 313 TOXIC CHEMICALS:

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 1 FIRE: 1 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: B

STATE RIGHT-TO-KNOW INFORMATION:

NAPTHENIC OIL - CAS #64782-52-5

ALKENES, C12-24, CHLORO - CAS #68527-02-6

SODIUM SULFONATE - CAS #68608-26-4

TALL OIL FATTY ACID - CAS #67790-12-3

OXAZOLIDINE 4,4-DIMETHYL - CAS #

XVI. OTHER INFORMATION

THE INFORMATION IN THIS MSDS RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED OTHER THAN AS RECOMMENDED BY DIVERSEY LEVER OR IN COMBINATION WITH OTHER MATERIALS. IT IS THE USER'S RESPONSIBILITY TO EVALUATE THE APPLICABILITY OF THIS INFORMATION FOR HIS PARTICULAR CONDITIONS OF STORAGE, HANDLING AND USE.