



I - PRODUCT IDENTIFICATION AND USE

MSDS ID: 2666

PRODUCT NAME: WSM-205

USE: Acid Cleaner

SUPPLIER:

JohnsonDiversey Canada, Inc.
2401 Bristol Circle
Oakville Ontario, L6H 6P1, Canada

EMERGENCY PHONE:

1-800-668-7171

WHMIS CLASSIFICATION: D1A E

CHEMICAL FAMILY: mineral acid

TRADE NAME / SYNONYMS: not applicable

CHEMICAL NAME: not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS #	LD50 / LC50	Route / Species
Sulphuric acid	15-40	007664-93-9	LD50 2140 mg/kg	oral/rat
Phosphoric acid	7-13	007664-38-2	LD50 1530mg/kg	oral/rat
Alkyl polyoxyethylene glycol ether	3-7	066455-14-9	LD50 4600 mg/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: Neoprene or PVC

Eye: safety goggles

Footwear: rubber boots

Respiratory: NIOSH acid mist mask required in absence of
adequate ventilation

Other: rubber apron

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Do not breathe mist, spray or vapours. If spraying, wear NIOSH approved respirator for acid mist. Avoid eye and skin contact.

VENTILATION REQUIREMENTS: Mechanical exhaust. Wear NIOSH respirator for acid mist.

INCOMPATIBILITY (Material to Avoid): Alkaline and chlorinated materials. Organic materials.

SPILL PROCEDURES: Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal. Wash spill area with large volumes of water.

WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.

STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container. UN1760

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Clear, colourless liquid

S.G. / BULK DENSITY(g/cc): 1.25 ± 0.01

pH: 0.5 ± 0.4

VAPOUR PRESSURE (mmHg): not applicable

VAPOUR DENSITY (air=1): not applicable

ODOUR THRESHOLD: not available

BOILING POINT: 111°C

FREEZING POINT: not available

PERCENT VOLATILE: 60%

SOLUBILITY IN WATER: soluble

EVAPORATION RATE (water=1): not applicable

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:

EYES: Corrosive. May cause severe irritation. May cause permanent damage if not treated promptly.

SKIN: Corrosive. May cause severe irritation. May cause temporary or permanent damage if not treated promptly.

INGESTION: Corrosive. May cause severe irritation of the digestive tract. May cause temporary or permanent damage if not treated promptly.

INHALATION: May cause irritation of respiratory tract.

LD50 (calculated): 5300 mg/kg		LC50 (calculated): Not available	
OTHER TOXIC EFFECTS: TLV-TWA 1 mg/m3 as Sulphuric Acid. IARC has classified "occupational exposure to strong acid mists containing sulphuric acid" as being carcinogenic to humans. The route of entry is inhalation of these mists resulting in respiratory (Laryngeal) cancers. There is no evidence that the liquid is in any way a carcinogen. Phosphoric Acid TLV-STEL 3 mg/m3, TWA 1 mg/m3			
EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: Not available.			
VI - FIRST AID MEASURES			
EYES:	Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.		
SKIN:	Flush affected area thoroughly with water. If irritation develops, contact a physician.		
INGESTION:	Drink large volumes of water. Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately.		
INHALATION:	Remove patient to fresh air. Get medical attention for any breathing difficulty.		
VII - FIRE AND EXPLOSION DATA			
FLAMMABLE: Contact with metals forms flammable hydrogen gas.			
FLASH POINT, °C: not applicable		AUTO IGNITION TEMPERATURE, °C: N/Ap	
EXTINGUISHING MEDIA: Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []			
SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus.			
HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon.			
EXPLOSIVE SENSITIVITY TO: not applicable			
VIII - REACTIVITY DATA			
STABILITY: Stable [x] Unstable []			
CONDITIONS TO AVOID: not applicable.			
INCOMPATIBILITY (Material to Avoid) : Alkaline and chlorinated materials. Aluminum, brass, copper, iron, mild steel. Organic materials.			
HAZARDOUS DECOMPOSITION PRODUCTS: Contact with chlorinated materials will release chlorine gas. Contact with alkali will generate heat. Contact with soft metals forms flammable hydrogen gas. Contact with organic materials will generate heat.			
REACTIVITY: not applicable.			
IX - MSDS PREPARATION			
SOURCES USED: RTECS, Industrial Chemicals Safety Manual.		PREPARED BY: JohnsonDiversey Canada. Inc. Regulatory Department Industrial Division Phone (905) 829-1200	
PREPARATION DATE: April 15, 2003			
Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.			