

NON-SKID COATING, LT GRAY

MSDS ID: 03105

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: NON-SKID COATING, LT GRAY

PRODUCT DESCRIPTOR: EPOXY RESIN

MANUFACTURER: JOHNSON DIVERSEY, INC.
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

EMERGENCY PHONE NUMBER: (800) 851-7145

II. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME(CAS NUMBER)	%	EXPOSURE LIMITS	UNITS
AROMATIC NAPHTHA (64742-95-6)	<30	TLV 100	PPM
2-PROPOXYETHANOL (2807-30-9)	<10	NONE ESTABLISHED	
SPGR 1.43; 35% VOLATILE			
EPOXY HARDENER			
AROMATIC NAPHTHA (64742-95-6)	<65	TLV 100	PPM
SPGR 0.91; 60% VOLATILE			

III. HAZARDS IDENTIFICATION

ROUTES OF ENTRY: INHALATION: YES
SKIN: YES
INGESTION: YES

SIGNS AND SYMPTOMS OF EXPOSURE:

ACUTE: DEFATS SKIN; IRRITATES EYES; MAY CAUSE EYE BURNS. NARCOTIC
EFFECTS (DIZZINESS) OCCUR AT HIGHER VAPOR CONCENTRATIONS.

CHRONIC: PROLONGED SKIN CONTACT WITH LIQUID MAY PRODUCE IRRITATION.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Sensitive skin

IV. FIRST AID MEASURES

EYES: FLUSH THOROUGHLY WITH FRESH WATER FOR AT LEAST 15 MINUTES, GET
MEDICAL ATTENTION.SKIN: FLUSH WITH FRESH WATER, WASH WITH SOAP AND WATER. REMOVE
CONTAMINATED CLOTHES AND SHOES. GET MEDICAL ATTENTION.INGESTION: GIVE WATER, DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION. NEVER
GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

INHALATION: Remove to fresh air.

V. FIRE FIGHTING MEASURES

FLASH POINT: 110 DEG F FLAME EXTENSION: N/A IN.

FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: N/A UEL: N/A

UNUSUAL FIRE OR EXPLOSION HAZARDS: FLAMMABLE VAPORS MAY FORM EXPLOSIVE
MIXTURES WITH AIR.EXTINGUISHING MEDIA: CARBON DIOXIDE OR WATER FOG, FOAM, DRY
CHEMICAL

MATERIAL SAFETY DATA SHEET

Page 2 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

NON-SKID COATING, LT GRAY

MSDS ID: 03105

V. FIRE FIGHTING MEASURES (Cont.)

FIRE FIGHTING INSTRUCTIONS: POLYMER FOAM FOR LARGE FIRES. AVOID SOLID STREAM OF WATER, USE FOG FOR COOLING.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED: ELIMINATE ALL IGNITION SOURCES. RECOVER FREE LIQUID ADD ABSORBENT TO SMALL SPILLS. FLUSH SPILL AWAY WITH WATER SPRAY. VENTILATION AREA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: AVOID CONTACT WITH EYES, SKIN OR CLOTHING. MAY CAUSE EYE INJURY. KEEP CONTAINER CLOSED. KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: SIDE SHIELD SAFETY GLASSES OR CHEMICAL GOGGLES
PROTECTIVE GLOVES: RUBBER GLOVES
RESPIRATORY PROTECTION: WEAR A NIOSH APPROVED ORGANIC VAPOR RESPIRATOR IF TLV LIMIT IS EXCEEDED.
OTHER PROTECTIVE CLOTHING/EQUIPMENT: SAFETY SHOWER AND EYE WASH IN WORK AREA
EXPOSURE GUIDELINES: SEE SECTION II FOR DETAILED INFORMATION.

IX. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (F): 300 SPECIFIC GRAVITY: 1.0000
VOLATILE BY VOLUME: SOLUBILITY IN WATER: 0
VAPOR PRESSURE (MMHG): 3 AT 20 C
APPEARANCE AND ODOR: OPAQUE LIQUID WITH ODOR OF PETROLEUM.

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE
INCOMPATIBILITY WITH OTHER MATERIALS: STRONG ACID CONTAMINATION, OXIDIZING MATERIALS.
HAZARDOUS DECOMPOSITION PRODUCTS: THERMAL DECOMPOSITION MAY PRODUCE OXIDES OF CARBON.
HAZARDOUS POLYMERIZATION: NONE

XI. TOXICOLOGICAL INFORMATION

NO DATA AVAILABLE

XII. ECOLOGICAL INFORMATION

NO DATA AVAILABLE

MATERIAL SAFETY DATA SHEET

Page 3 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

NON-SKID COATING, LT GRAY

MSDS ID: 03105

XIII. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: USE UNTIL LESS THAN 1 INCH REMAINS IN CONTAINER, EMPTY CONTAINER HAVE RESIDUE HAULED BY QUALIFIED WASTE HAULER REMOVE OR DEFACE LABEL BEFORE SELLING CONTAINER OR DISPOSAL INCINERATE AT AN APPROVED FACILITY.

XIV. TRANSPORT INFORMATION

HAZARDOUS MATERIALS DESCRIPTION/PROPER SHIPPING NAME:

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CERCLA/EPCRA:SECTION 313 TOXIC CHEMICALS:

NONE ALL CHEMICAL INGREDIENTS ARE LISTED ON THE TSCA INVENTORY.

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 2 FIRE: 2 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: C

STATE RIGHT-TO-KNOW INFORMATION:

AROMATIC NAPHTHA SOLVENT - CAS #64741-41-9, SILICA SAND - CAS #

7631-86-9, MAGNESIUM SILICATE - CAS #1343-88-0, EPOXY RESIN

- CAS #25068-38-6, ETHYLENE GLYCOL PROPYL-ETHER - CAS #2807-30-9,

POLYAMIDE RESIN - CAS #68071-65-8, PUMICE - CAS #1332-09-8

TITANIUM DIOXIDE - CAS #13463-67-7

XVI. OTHER INFORMATION

THE INFORMATION IN THIS MSDS RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED OTHER THAN AS RECOMMENDED BY DIVERSEY LEVER OR IN COMBINATION WITH OTHER MATERIALS. IT IS THE USER'S RESPONSIBILITY TO EVALUATE THE APPLICABILITY OF THIS INFORMATION FOR HIS PARTICULAR CONDITIONS OF STORAGE, HANDLING AND USE.