
MATERIAL SAFETY DATA SHEET

Page 1 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

PELLET LUBE**MSDS ID: 03201**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: PELLET LUBE
PRODUCT DESCRIPTOR: ANTI-TACK COATING
MANUFACTURER: JOHNSON DIVERSEY, INC.
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

EMERGENCY PHONE NUMBER: (800) 851-7145

II. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME(CAS NUMBER)	%	EXPOSURE LIMITS	UNITS
ALUMINUM SILICATE (1318-74-7)	<50	NOT ESTABLISHED	
STEARIC ACID (57-11-4)	< 2	NOT ESTABLISHED	

III. HAZARDS IDENTIFICATION

ROUTES OF ENTRY: INHALATION: NO
SKIN: NO
INGESTION: NO
SIGNS AND SYMPTOMS OF EXPOSURE:
ACUTE: MAY IRRITATE SKIN AND EYES
CHRONIC: SAME AS ACUTE
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
Sensitive skin

IV. FIRST AID MEASURES

EYES: FLUSH THOROUGHLY WITH FRESH WATER. GET MEDICAL ATTENTION.
SKIN: FLUSH WITH FRESH WATER, WASH WITH SOAP AND WATER. REMOVE
CONTAMINATED CLOTHES AND SHOES. GET MEDICAL ATTENTION.
INGESTION: GET MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN
UNCONSCIOUS PERSON.
INHALATION: REMOVE TO FRESH AIR, GET MEDICAL ATTENTION IF IRRITATION PERSISTS

V. FIRE FIGHTING MEASURES

FLASH POINT: NONE	DEG F	FLAME EXTENSION: N/A	IN.
FLAMMABLE LIMITS IN AIR BY VOLUME:		LEL: NONE	UEL: NONE
UNUSUAL FIRE OR EXPLOSION HAZARDS:		NONE KNOWN	
EXTINGUISHING MEDIA:		CO2, FOAM, DRY CHEMICALS	
FIRE FIGHTING INSTRUCTIONS:		NONE	

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED: WIPE UP; COLLECT LARGE AMOUNTS AND RETURN
TO CONTAINER.

MATERIAL SAFETY DATA SHEET

Page 2 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

PELLET LUBE

MSDS ID: 03201

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: DO NOT PRESSURE CONTAINER TO EMPTY. KEEP FROM FREEZING. KEEP CONTAINER CLOSED. IF FROZEN, RETURN TO PRODUCING PLANT.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: SAFETY GLASSES
PROTECTIVE GLOVES: NON-ABSORBENT
RESPIRATORY PROTECTION: NONE
OTHER PROTECTIVE CLOTHING/EQUIPMENT: CLOTHING TO PREVENT PROLONGED SKIN CONTACT.
EXPOSURE GUIDELINES: SEE SECTION II FOR DETAILED INFORMATION.

IX. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (F): 215 SPECIFIC GRAVITY: 1.2000
VOLATILE BY VOLUME: 50 SOLUBILITY IN WATER: 5
VAPOR PRESSURE (MMHG): 17.5 AT 20 C
APPEARANCE AND ODOR: CREAM COLORED VISCOUS SLURRY; MILD ODOR

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE
INCOMPATIBILITY WITH OTHER MATERIALS: STRONG OXIDIZERS
HAZARDOUS DECOMPOSITION PRODUCTS: CO WITH INCOMPLETE COMBUSTION
HAZARDOUS POLYMERIZATION: NONE

XI. TOXICOLOGICAL INFORMATION

NO DATA AVAILABLE

XII. ECOLOGICAL INFORMATION

NO DATA AVAILABLE

XIII. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: USE UNTIL LESS THAN 1 INCH REMAINS IN CONTAINER, EMPTY CONTAINER TRIPLE RINSE WITH WATER, ADD TO OPERATION REMOVE OR DEFACE LABEL BEFORE SELLING CONTAINER OR DISPOSAL. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

XIV. TRANSPORT INFORMATION

HAZARDOUS MATERIALS DESCRIPTION/PROPER SHIPPING NAME:
Please refer to the Bill of Lading/receiving documents for up to date shipping information.

MATERIAL SAFETY DATA SHEET

Page 3 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

PELLET LUBE

MSDS ID: 03201

XV. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CERCLA/EPCRA:SECTION 313 TOXIC CHEMICALS:

ALL CHEMICAL INGREDIENTS ARE LISTED ON THE TSCA INVENTORY.

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 1 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: B

STATE RIGHT-TO-KNOW INFORMATION:

ALUMINUM SILICATE - CAS #1318-74-7

WATER - CAS #7732-18-5

STEARIC ACID - CAS #57-11-4

SODIUM NITRITE - CAS #7632-00-00

XVI. OTHER INFORMATION

THE INFORMATION IN THIS MSDS RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED OTHER THAN AS RECOMMENDED BY DIVERSEY LEVER OR IN COMBINATION WITH OTHER MATERIALS. IT IS THE USER'S RESPONSIBILITY TO EVALUATE THE APPLICABILITY OF THIS INFORMATION FOR HIS PARTICULAR CONDITIONS OF STORAGE, HANDLING AND USE.