

POLY D-TAC

MSDS ID: 03254

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: POLY D-TAC

Product Descriptor: Paint Booth Treatment Compound

MANUFACTURER: JOHNSON DIVERSEY, INC.

EMERGENCY PHONE NUMBER: (800) 851-7145

3630 E. KEMPER ROAD

CINCINNATI, OH. 45241

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
FORMALDEHYDE	50-00-0	< 1.0 %	TLV 0.3C PEL 0.75C STEL 2	PPM PPM
HYDROCHLORIC ACID	7647-01-0	1 - 5%	5 (ceiling)	PPM

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

CORROSIVE MATERIAL-Causes severe burns to skin and eyes. Harmful if swallowed. Do not contact eyes, skin or clothing. Avoid breathing any dust, spray mist or vapors in spill area. Wash thoroughly after handling product. Wear eye protection, clothing and footwear to prevent skin contact.

POSSIBLE ROUTES OF ENTRY: Ingestion and Inhalation.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Severe irritation with redness, pain and swelling. SKIN: Dryness or itching may develop with pain and redness. INGESTION: If swallowed, gastric distress, diarrhea and vomiting may occur.

CHRONIC: Formaldehyde inhalation has been shown to cause cancer in laboratory animals. Studies do not provide adequate evidence for assessing carcinogenicity in man.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis, sensitive skin, pulmonary function and asthma.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes, skin and respiratory tract.

IV. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for 15 minutes. Get medical attention.

SKIN: Flush thoroughly with plenty of water. Wash with soap and water. Remove contaminated clothes and shoes and clean before reuse. Get medical attention for any painful, red or injured skin.

INGESTION: If swallowed, rinse mouth with water. Dilute by drinking several glasses of water. DO NOT induce vomiting. If patient vomits, rerinse mouth with water. Get prompt medical attention. NOTE: Never give fluids by mouth to an unconscious person.

INHALATION: Remove to fresh air. If breathing difficulties arise, get medical attention.

MATERIAL SAFETY DATA SHEET

Page 2 of 4
Revised 2/02/04
Replaces 1/15/04
Printed 2/03/04

POLY D-TAC**MSDS ID: 03254**

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): >200 FLAME EXTENSION: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: ND UEL: ND
UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Toxic fumes or vapor may form during fire.
EXTINGUISHING MEDIA: Water spray, CO2, foam or dry powder.
FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus (SCBA) in fire area.
SPECIAL INSTRUCTIONS: Contain runoff. Prevent from entering sewer or storm drain.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:
Contain spill. Absorb with sand or clay. Collect material and place in suitable waste container. Neutralize solids and spill area with soda ash or lime. Dispose of by environmental regulations.
The Reportable Quantity (RQ) of Formaldehyde, CAS #50-00-0 is 3918 gallons or 33,333 lbs.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Store in a cool, dry area. Keep from freezing. If frozen, return to producing plant. Keep container closed when not in use. Wear protective gear when handling or using. Do not pressurize container to empty.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Face shield if contact or splash hazard exists. Eye wash in use area.
PROTECTIVE GLOVES: Acid resistant.
RESPIRATORY PROTECTION: Respirator protection required if PEL is exceeded. See Section II for information.
OTHER PROTECTIVE CLOTHING/EQUIPMENT: Rubber boots, chemical apron and safety shower in use area if contact or splash hazard exists.
ENGINEERING CONTROLS:
MECHANICAL VENTILATION: Normal room ventilation should be sufficient to control airborne levels.
LOCAL VENTILATION: Not usually required.

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Light blue liquid with mild odor.

BOILING POINT (DEG F): 212	FREEZING POINT: 32
SPECIFIC GRAVITY/BULK DENSITY: 1.02	
pH: 1.5	pH 1% SOLUTION: 3.0
VOLATILE BY VOLUME: 93	
SOLUBILITY IN WATER: Soluble	
VAPOR PRESSURE(mmHg): 17.5 at 20 C	VAPOR DENSITY: NDA

MATERIAL SAFETY DATA SHEET

Page 3 of 4
Revised 2/02/04
Replaces 1/15/04
Printed 2/03/04

POLY D-TAC

MSDS ID: 03254

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: Oils, greases and strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms oxides of carbon and nitrogen.

HAZARDOUS POLYMERIZATION: None known.

XI. TOXICOLOGICAL INFORMATION

Any hazardous effects of the product mixture are based on information for each chemical part. See Section II for amounts of hazardous materials.

TOXICITY TEST DATA:

No data available.

XII. ECOLOGICAL INFORMATION

ECOTOXICITY DATA: Product and waste are harmful to fish and aquatic forms. Discharge process waste and overflow to a sanitary sewer or on-site treatment process.

ECOTOXICITY TEST DATA: No data available.

ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: RCRA Regulated Hazardous Waste: Corrosivity Characteristic - D002.

Adjust pH of diluted product and discharge to industrial sewer. Use product in container until empty. Triple rinse container with water and add to process. Recycle or dispose of container by product labeling or governmental regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: Contains no hazardous air pollutants.

VOC CONTENT (EPA Method 24A): % VOC: NONE Lb/Gal VOC:

CERCLA/EPCRA:

Section 313 Toxic Chemicals: FORMALDEHYDE (50-00-0) AT <0.3%.

SARA Section 311/312:

ACUTE: YES CHRONIC: YES FIRE: NO REACTIVITY: NO

SUDDEN RELEASE OF PRESSURE: NO

LISTED CARCINOGEN: YES

NTP: YES IARC: YES OSHA: YES

HMIS RATINGS: HEALTH: 3 FIRE: 1 REACTIVITY: 0

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 1/15/04
Printed 2/03/04

POLY D-TAC

MSDS ID: 03254

XV. REGULATORY INFORMATION (Cont.)

PERSONAL PROTECTIVE EQUIPMENT: D

NFPA RATING: HEALTH: 2 FIRE: 1 REACTIVITY:0 SPECIAL:

STATE RIGHT-TO-KNOW INFORMATION:

WATER - CAS #7732-18-5

FORMALDEHYDE - CAS #50-00-0

CATIONIC POLYMER - CAS #PROPRIETARY

HYDROCHLORIC ACID - CAS #7647-01-0

CALIFORNIA PROPOSITION 65:

WARNING: This product contains Formaldehyde known to the State of California to cause cancer.

XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.