
MATERIAL SAFETY DATA SHEET

Page 1 of 4
Revised 2/02/04
Replaces 10/28/03
Printed 2/03/04

POLY D-TAC 200**MSDS ID: 03280**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: POLY-D-TAC 200

Product Descriptor: PAINT BOOTH COMPOUND

MANUFACTURER: JOHNSON DIVERSEY, INC.

EMERGENCY PHONE NUMBER: (800) 851-7145

3630 E. KEMPER ROAD

CINCINNATI, OH. 45241

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
-----	-----	-----	-----	-----
ALUMINUM CHLORHYDRATE		5 - 15%	None established	

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

CAUTION - Contains cleaning agents that may cause eye irritation. May be harmful if swallowed. Do not get in eyes. Do not take internally.

POSSIBLE ROUTES OF ENTRY: Skin contact/absorption and inhalation.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: May cause eye irritation. SKIN: May cause skin irritation.
INGESTION: None known. INHALATION: May cause irritation of respiratory tract.

CHRONIC: Same as acute effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis, sensitive skin, pulmonary function and asthma.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes and skin.

IV. FIRST AID MEASURES

EYES: Immediately flush with plenty of water. Get medical attention.
SKIN: Flush skin with plenty of water and wash with mild soap. If irritation develops, get medical attention.
INGESTION: Do not take internally. If swallowed, drink several glasses of water. Do not induce vomiting. Contact a physician or Poison Control Center. NOTE: Never give fluids by mouth to an unconscious person.
INHALATION: Remove to fresh air and seek medical attention.

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): NONE

FLAME EXTENSION: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME:

LEL: N/A

UEL: N/A

UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Toxic fumes or vapor may form during fire.

EXTINGUISHING MEDIA: Water, water spray, CO2, foam or dry powder.

FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus (SCBA) in fire area.

MATERIAL SAFETY DATA SHEET

Page 2 of 4
Revised 2/02/04
Replaces 10/28/03
Printed 2/03/04

POLY D-TAC 200

MSDS ID: 03280

V. FIRE FIGHTING MEASURES (Cont.)

SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:

Contain spill. Wear protective clothing. Soak up or absorb liquid on suitable absorbent material. Collect and place in chemical waste container. Dispose of in accordance with local, State and Federal regulations. Flush spill area with water.

This product does not contain a reportable quantity (RQ) under CERCLA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Keep container closed. If frozen, thaw and mix to make usable. Do not pressure container to empty. Keep away from alkalis and chlorinated products.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Safety glasses with side shields.

PROTECTIVE GLOVES: Acid resistant.

RESPIRATORY PROTECTION: Product does not have any established exposure limits. NIOSH/MSHA approved respirator recommended in enclosed or confined spaces where high air concentration or long exposure may occur.

OTHER PROTECTIVE CLOTHING/EQUIPMENT: Eyewash and safety shower in area if contact or splash hazard exists.

ENGINEERING CONTROLS:

VENTILATION: Good general ventilation should be sufficient to control airborne levels.

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear colorless liquid, mild organic odor.

BOILING POINT (DEG F): 212

FREEZING POINT: 0 C

SPECIFIC GRAVITY/BULK DENSITY: 1.08

pH: 4.45

pH 1% SOLUTION: 4.81

VOLATILE BY VOLUME: 82.5%

SOLUBILITY IN WATER: Soluble

VAPOR PRESSURE(mmHg): 17.5 at 20 C

VAPOR DENSITY: 17.3

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: oxides of nitrogen

HAZARDOUS POLYMERIZATION: None known.

MATERIAL SAFETY DATA SHEET

Page 3 of 4
Revised 2/02/04
Replaces 10/28/03
Printed 2/03/04

POLY D-TAC 200

MSDS ID: 03280

XI. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL TESTING: No data available.
TOXICITY TEST DATA:
No data available.

XII. ECOLOGICAL INFORMATION

ECOTOXICITY TEST DATA:
No data available.
ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Not Regulated.
Discharge diluted product to industrial sewer in accordance with discharge permit or local POTW regulations. Use product in container until empty. Rinse container with water. Recycle or dispose of container according to product labeling or governmental regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:
TSCA: All ingredients in this product are on TSCA inventory.
HAPS: NONE
VOC CONTENT (EPA Method 24A): % VOC: 0 Lb/Gal VOC: 0
CERCLA/EPCRA:
Section 313 Toxic Chemicals:
NONE
SARA Section 311/312:
ACUTE:NO CHRONIC:NO FIRE:NO REACTIVITY:NO
SUDDEN RELEASE OF PRESSURE:NO
LISTED CARCINOGEN: NONE
NTP: NO IARC: NO OSHA: NO
HMIS RATINGS: HEALTH: 1 FIRE: 0 REACTIVITY: 0
PERSONAL PROTECTIVE EQUIPMENT: B
NFPA RATING: HEALTH: 1 FIRE: 0 REACTIVITY:0 SPECIAL:Acidic
STATE RIGHT-TO-KNOW INFORMATION:
WATER - CAS #7732-18-5
ALUMINUM CHLORHYDRATE - CAS #1327-41-9
TRADE SECRET REGISTRATION: 694954-00-1-5180P
CALIFORNIA PROPOSITION 65:
None of the ingredients are on the California proposition 65 list.

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 10/28/03
Printed 2/03/04

POLY D-TAC 200

MSDS ID: 03280

XVI. OTHER INFORMATION

Disclaimer: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.