
MATERIAL SAFETY DATA SHEET

Page 1 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

NEXUS DC 1000**MSDS ID: 03522**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: NEXUS DC 1000
Product Descriptor: POLYAMINE
MANUFACTURER:
JOHNSON DIVERSEY, INC.
3630 E. KEMPER RD.
CINCINNATI, OH 45241

EMERGENCY PHONE NUMBER: (800) 851-7145

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
----------------	------------	---	-----------------	-------

NONE

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

CAUTION-Contains cleaning agents that cause eye irritation. May be harmful if swallowed. Avoid contact with eyes or clothing. Prolonged contact with undiluted product may cause skin irritation. Wear eye and skin protection when handling. Contain spills and runoff which may harm the environment.

POSSIBLE ROUTES OF ENTRY: Ingestion and Inhalation.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Irritation with pain, swelling and redness may develop. SKIN: Irritation or dryness develop with long contact. INGESTION: If swallowed, diarrhea, nausea and vomiting may occur. INHALATION: Irritation of respiratory tract may develop.

CHRONIC: None known.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None known.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes

IV. FIRST AID MEASURES

EYES: IF IN EYES: Hold eyelids open and flush with a steady, gentle stream of water for 15 minutes. Get medical attention.

SKIN: Flush skin with plenty of water. If irritation develops, get medical attention.

INGESTION: Do not take internally. If swallowed, drink several glasses of water. Do not induce vomiting. Contact a physician or poison control center.

INHALATION: Remove to fresh air. If breathing difficulties arise, get medical attention.

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): >212

FLAME EXTENSION: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME:

LEL: ND

UEL: ND

UNUSUAL FIRE OR EXPLOSIVE HAZARDS: None known.

EXTINGUISHING MEDIA: Water spray, CO2, foam or dry powder.

FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure

MATERIAL SAFETY DATA SHEET

Page 2 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

NEXUS DC 1000

MSDS ID: 03522

V. FIRE FIGHTING MEASURES (Cont.)

breathing apparatus (SCBA) in fire area.

SPECIAL INSTRUCTIONS: Contain runoff. Prevent from entering sewer or storm drain.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:

Contain spill. Wear protective clothing. Soak up or absorb liquid on sand or clay. Collect and place in chemical waste container. Dispose of in accordance with governmental regulations. Flush spill area with water.

This product does not contain a reportable quantity (RQ) under CERCLA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Store in a cool, dry area. Keep from freezing. If frozen, warm to thaw and mix for use. Keep container closed when not in use. Wear protective gear when handling or using. Do not pressurize container to empty.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Safety glasses with side shields. Eye wash in use area if contact or splash hazard exists.

PROTECTIVE GLOVES: Chemical resistant.

RESPIRATORY PROTECTION: Product does not have any established exposure limits. Wear a positive pressure air supplied respirator in enclosed or confined spaces where high air concentration or long exposure may occur.

OTHER PROTECTIVE CLOTHING/EQUIPMENT: Eyewash and safety shower in area if contact or splash hazard exists.

ENGINEERING CONTROLS:

MECHANICAL VENTILATION: Normal room ventilation should be sufficient to control airborne levels.

LOCAL VENTILATION: Local exhaust ventilation may be necessary to control any air contaminants to within their Threshold Limit Values (TLV's) during the use of this product.

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear colorless liquid; mild odor.

BOILING POINT (DEG F): ND

FREEZING POINT: ND

SPECIFIC GRAVITY/BULK DENSITY: 1.19

pH: 2-5

pH 1% SOLUTION: ND

VOLATILE BY VOLUME: ND

SOLUBILITY IN WATER: Soluble

VAPOR PRESSURE(mmHg): ND at ND

VAPOR DENSITY: Heavier than air.

MATERIAL SAFETY DATA SHEET

Page 3 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

NEXUS DC 1000

MSDS ID: 03522

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: Oxidizing agents including chlorinated products.

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms oxides of carbon.

HAZARDOUS POLYMERIZATION: None known.

XI. TOXICOLOGICAL INFORMATION

No data available.

TOXICITY TEST DATA:

No data available.

XII. ECOLOGICAL INFORMATION

ECOTOXICITY DATA: No data available.

ECOTOXICITY TEST DATA: No data available.

ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Not Regulated.

Discharge diluted product to industrial sewer. Use product in container until empty. Triple rinse container with water and add to process. Recycle or dispose of container by product labeling or governmental regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: None

VOC CONTENT (EPA Method 24A): % VOC: ND Lb/Gal VOC: ND

CERCLA/EPCRA:

Section 313 Toxic Chemicals: None

SARA Section 311/312:

ACUTE: YES CHRONIC: NO FIRE: NO REACTIVITY: NO

SUDDEN RELEASE OF PRESSURE: NO

LISTED CARCINOGEN: None

NTP: No IARC: No OSHA: No

HMIS RATINGS: HEALTH: 1 FIRE: 1 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: B

NFPA RATING: HEALTH: 1 FIRE: 1 REACTIVITY: 0 SPECIAL: -

STATE RIGHT-TO-KNOW INFORMATION:

PROPRIETARY INFORMATION

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

NEXUS DC 1000

MSDS ID: 03522

XV. REGULATORY INFORMATION (Cont.)

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.