
MATERIAL SAFETY DATA SHEET

Page 1 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

PD-7656-0**MSDS ID: 03606**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: PD-7656-0

Product Descriptor: CONVEYOR LUBRICANT

MANUFACTURER: JOHNSON DIVERSEY, INC.

EMERGENCY PHONE NUMBER: (800) 851-7145

3630 E. KEMPER ROAD

CINCINNATI, OH. 45241

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
ALCOHOL ETHOXYLATE	68131-39-5	5 - 15%	Not Established	
HYDROGEN PEROXIDE	7722-84-1	1 - 5%	TWA 1.4	MG/M3
XYLENE SULPHONIC ACID	25321-41-9	1 - 5%	None established	

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

CORROSIVE MATERIAL-Causes severe burns to skin and eyes. Harmful if swallowed. Do not contact eyes, skin or clothing. Avoid breathing any dust, spray mist or vapors in spill area. Wash thoroughly after handling product. Wear eye protection, clothing and footwear to prevent skin contact.

POSSIBLE ROUTES OF ENTRY: Ingestion, Skin and Inhalation.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Burns or severe irritation with pain, redness and swelling.
SKIN: Severe irritation or burns with rash, redness, pain or itching. **INGESTION:** If swallowed, pain, nausea and vomiting may result.

CHRONIC: Same as Acute Effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis and sensitive skin.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes, skin and respiratory tract.

IV. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for 15 minutes. Get medical attention.

SKIN: Flush thoroughly with plenty of water. Wash with soap and water. Remove contaminated clothes and shoes and clean before reuse. Get medical attention for any painful, red or injured skin.

INGESTION: If swallowed, drink several glasses of water. Do not induce vomiting. Consult a physician or poison control center. **NOTE:** Never give fluids by mouth to an unconscious person.

INHALATION: Remove to fresh air. If breathing difficulties continue, get medical attention.

MATERIAL SAFETY DATA SHEET

Page 2 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

PD-7656-0**MSDS ID: 03606**

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F):N/A FLAME EXTENSION: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: N/A UEL: N/A
UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Toxic fumes or vapor may form during fire.
EXTINGUISHING MEDIA: Water spray, CO2, foam or dry powder.
FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus (SCBA) in fire area.
SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:
Small spills - Absorb with neutral materials or mop up liquid. Large spills - Collect materials with neutral absorbent. Return to container. Dispose of in accordance with local, state, and federal regulations.
This product does not contain a reportable quantity (RQ) under CERCLA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Keep container closed. If frozen, thaw and mix to make usable. Do not pressure container to empty. Keep away from alkalis and chlorinated products.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Chemical goggles if contact or splash hazard exists. Eye wash in use area.
PROTECTIVE GLOVES: Acid resistant.
RESPIRATORY PROTECTION: Respirator protection required if PEL is exceeded. See Section II for information.
OTHER PROTECTIVE CLOTHING/EQUIPMENT: Protective clothing to cover exposed skin if contact or splash hazard exists.
ENGINEERING CONTROLS:
MECHANICAL VENTILATION: Normal room ventilation should be sufficient to control airborne levels.
LOCAL VENTILATION: Not usually required.

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear, light amber liquid with no odor.

BOILING POINT (DEG F): ND	FREEZING POINT: ND
SPECIFIC GRAVITY/BULK DENSITY: 1.02	pH: 2.97
pH 1% SOLUTION: 3.9	
VOLATILE BY VOLUME: 84.3	Weight % solids: 15.7
SOLUBILITY IN WATER: Soluble	
VAPOR PRESSURE(mmHg): ND at	VAPOR DENSITY: ND

MATERIAL SAFETY DATA SHEET

Page 3 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

PD-7656-0

MSDS ID: 03606

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable. If frozen, thaw and mix.
INCOMPATIBILITY WITH OTHER MATERIALS: Alkalis, carbonates and chlorinated compounds.
HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms oxides of carbon, nitrogen and sulfur.
HAZARDOUS POLYMERIZATION: None known.

XI. TOXICOLOGICAL INFORMATION

Any hazardous effects of the product mixture are based on information for each chemical part. See Section II for amounts of hazardous materials.
TOXICITY TEST DATA:
No data available.

XII. ECOLOGICAL INFORMATION

ECOTOXICITY DATA: Contains biodegradable, synthetic detergents that may be toxic to aquatic forms. Discharge waste product only to sanitary sewer or on-site waste treatment.
ECOTOXICITY TEST DATA: No data available.
ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: RCRA Regulated Hazardous Waste: Corrosivity Characteristic - D002.
Discharge diluted product to industrial sewer. Use product in container until empty. Triple rinse container with water and add to process. Recycle or dispose of container by product labeling or governmental regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:
TSCA: All ingredients in this product are on TSCA inventory.
HAPS: Contains no hazardous air pollutants.
VOC CONTENT (EPA Method 24A): % VOC: N/A Lb/Gal VOC:
CERCLA/EPCRA:
Section 313 Toxic Chemicals: None
SARA Section 311/312:
ACUTE: YES CHRONIC: NO FIRE: NO REACTIVITY: NO
SUDDEN RELEASE OF PRESSURE: NO
LISTED CARCINOGEN: NONE
NTP: NO IARC: NO OSHA: NO
HMIS RATINGS: HEALTH: 3 FIRE: 0 REACTIVITY: 0
PERSONAL PROTECTIVE EQUIPMENT: D

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

PD-7656-0

MSDS ID: 03606

XV. REGULATORY INFORMATION (Cont.)

NFPA RATING: HEALTH: 3 FIRE: 0 REACTIVITY:0 SPECIAL:CORROSIVE

STATE RIGHT-TO-KNOW INFORMATION:

WATER - CAS #7732-18-5

XYLENE SULPHONIC ACID - CAS #25321-41-9

HYDROGEN PEROXIDE - CAS #7722-84-1

ALCOHOL ETHOXYLATE - CAS #68131-39-5

SODIUM LAURYL SARCOSINATE - CAS #2052-81-5

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the applicability of this information for his particular conditions of storage, handling, and use.