

SECURE SEAL

MSDS ID: 03946

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: SECURE SEAL
PRODUCT DESCRIPTOR: PHOSPHATE COATING SEALANT
MANUFACTURER: JOHNSON DIVERSEY, INC. EMERGENCY PHONE NUMBER: (800) 851-7145
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

II. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME(CAS NUMBER)	% EXPOSURE LIMITS	UNITS
PHOSPHORIC ACID (7664-38-2)	<25 TLV 1; PEL 1; ST 3	MG/M3
soluble molybdate salt (27546-07-2)	<3 TLV 5; PEL 5	MG/M3

III. HAZARDS IDENTIFICATION

ROUTES OF ENTRY: INHALATION: YES
SKIN: NO
INGESTION: YES
SIGNS AND SYMPTOMS OF EXPOSURE:
ACUTE: CONTACT WITH SKIN OR EYES MAY CAUSE SEVERE IRRITATION OR BURNS. INHALATION OF MISTS OR VAPORS MAY CAUSE RESPIRATORY TRACT IRRITATION.
CHRONIC: SAME AS ABOVE
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
SENSITIVE SKIN AND EYES

IV. FIRST AID MEASURES

EYES: FLUSH THOROUGHLY WITH FRESH FOR AT LEAST 15 MINUTES, GET MEDICAL ATTENTION.
SKIN: FLUSH WITH FRESH WATER, WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHES AND SHOES.
INGESTION: GIVE WATER. DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
INHALATION: N/A IN NORMAL OPERATION

V. FIRE FIGHTING MEASURES

FLASH POINT: NONE DEG F FLAME EXTENSION: N/A IN.
FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: NODATA UEL: NO DATA
UNUSUAL FIRE OR EXPLOSION HAZARDS: LIQUID PRODUCES HYDROGEN IN CONTACT WITH METALS.
EXTINGUISHING MEDIA: CO2, FOAM
FIRE FIGHTING INSTRUCTIONS: OVERALL PROTECTION OF PERSONNEL IF VAPORS ARE ENCOUNTERED.

MATERIAL SAFETY DATA SHEET

Page 2 of 3
Revised 2/02/04
Replaces 12/23/03
Printed 2/03/04

SECURE SEAL**MSDS ID: 03946**

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED: FLUSH SMALL AMOUNTS TO DRAIN; COLLECT AND RETURN LARGE AMOUNTS TO CONTAINER.

REPORTABLE QUANTITY (R.Q.) OF PRODUCT: 21,556 LBS. OR 2041 GALLON.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: DO NOT PRESSURE CONTAINER TO EMPTY. KEEP CONTAINER CLOSED. IF FROZEN, THAW AND MIX TO MAKE USABLE.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: FACE SHIELD
PROTECTIVE GLOVES: ACID RESISTANT
RESPIRATORY PROTECTION: WEAR NIOSH APPROVED APPROVED RESPIRATOR IF TLV AND PEL EXCEEDED.
OTHER PROTECTIVE CLOTHING/EQUIPMENT: WEAR APRON WHEN HANDLING.
EXPOSURE GUIDELINES: SEE SECTION II FOR DETAILED INFORMATION.

IX. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (F):	215	SPECIFIC GRAVITY:	1.2660
VOLATILE BY VOLUME:	48	SOLUBILITY IN WATER:	100
VAPOR PRESSURE (MMHG):	17.5	AT 20 C	
APPEARANCE AND ODOR:	BLUE LIQUID; MILD ODOR		

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY:	STABLE
INCOMPATIBILITY WITH OTHER MATERIALS:	CONCENTRATED ALKALINE PRODUCTS
HAZARDOUS DECOMPOSITION PRODUCTS:	OXIDES OF PHOSPHORUS AT EXTREMELY HIGH TEMPERATURES.
HAZARDOUS POLYMERIZATION:	None known.

XI. TOXICOLOGICAL INFORMATION

NO DATA AVAILABLE

XII. ECOLOGICAL INFORMATION

NO DATA AVAILABLE

XIII. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: PH ADJUSTMENT; CONTAINS PHOSPHATES. USE UNTIL LESS THAN ONE INCH REMAINS IN CONTAINER, EMPTY CONTAINER. TRIPLE RINSE WITH WATER, ADD TO OPERATION. REMOVE OR DEFACE LABEL BEFORE SELLING CONTAINER OR DISPOSAL.

MATERIAL SAFETY DATA SHEET

Page 3 of 3
Revised 2/02/04
Replaces 12/23/03
Printed 2/03/04

SECURE SEAL

MSDS ID: 03946

XIV. TRANSPORT INFORMATION

HAZARDOUS MATERIALS DESCRIPTION/PROPER SHIPPING NAME:

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CERCLA/EPCRA:SECTION 313 TOXIC CHEMICALS:

PRODUCT CONTAINS THESE SARA TITLE III SECTION 313 CHEMICALS AS
INGREDIENTS IN THE FOLLOWING CONCENTRATIONS: PHOSPHORIC ACID CAS
#7664-38-2 AT 22%.

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 3 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: D

STATE RIGHT-TO-KNOW INFORMATION:

PHOSPHORIC ACID - CAS #7664-38-2

PHOSPHORIC ACID, TRIETHANOLAMINE SALT - CAS #10017-56-8

WATER - CAS #7732-18-5

AMMONIUM DIMOLYBDATE - CAS #27546-07-2

XVI. OTHER INFORMATION

THE INFORMATION IN THIS MSDS RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED OTHER THAN AS RECOMMENDED BY DIVERSEY LEVER OR IN COMBINATION WITH OTHER MATERIALS. IT IS THE USER'S RESPONSIBILITY TO EVALUATE THE APPLICABILITY OF THIS INFORMATION FOR HIS PARTICULAR CONDITIONS OF STORAGE, HANDLING AND USE.