
MATERIAL SAFETY DATA SHEET

Page 1 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

SPIRIT

MSDS ID: 03991

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name:

Product Discriptor:

MANUFACTURER: JOHNSON DIVERSEY, INC.
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

EMERGENCY PHONE NUMBER: (800)851-7145

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
SPIRIT		>30%	None established	

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: DIZZINESS, CORROSIVE TO SKIN AND EYES

CHRONIC: SAME AS FOR ACUTE

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: SENSITIVE SKIN AND EYES, IMPAIRED PULMONARY FUNCTION.

IV. FIRST AID MEASURES

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): NONE

FLAME EXTENSION: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME:

LEL: NONE

UEL: NONE

EXTINGUISHING MEDIA: CO2, FOAM DRY CHEMICALS

FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus (SCBA) in fire area.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:

ABSORB ON FLOOR DRY MATERIAL AND ALLOW SOLVENT TO EVAPORATE; DISPOSE TO SOLID WASTE.

This product does not contain a reportable quantity (RQ) under CERCLA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: DO NOT PRESSURE DRUMS TO EMPTY. STORE BELOW 100 F - OPEN BUNGS SLOWLY TO DISSIPATE ANY SOLVENT PRESSURE.

MATERIAL SAFETY DATA SHEET

Page 2 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

SPIRIT

MSDS ID: 03991

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: FACE SHIELD WHEN HANDLING
PROTECTIVE GLOVES: SOLVENT RESISTANT
OTHER PROTECTIVE CLOTHING/EQUIPMENT: BOOTS AND APRON WHEN WORKING WITH SPIRIT
ENGINEERING CONTROLS:
MECHANICAL VENTILATION: Not usually required.
LOCAL VENTILATION: YES

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR:

BOILING POINT (DEG F): 110	FREEZING POINT: Not determined
SPECIFIC GRAVITY/BULK DENSITY:	
pH:	pH 1% SOLUTION: Not Determined
VOLATILE BY VOLUME: 66	
VAPOR PRESSURE(mmHg): >300 at 20 C	VAPOR DENSITY: 2.93

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE
INCOMPATIBILITY WITH OTHER MATERIALS: CO, HCL, PHOSGENE WITH INCOMPLETE COMBUSTION.
HAZARDOUS DECOMPOSITION PRODUCTS: None known.
HAZARDOUS POLYMERIZATION: NONE

XI. TOXICOLOGICAL INFORMATION

No data available.
TOXICITY TEST DATA:
No data available.

XII. ECOLOGICAL INFORMATION

ECOTOXICITY TEST DATA: No data available.
ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Not Regulated.
CONTAINS SOLVENTS AND CRESOLS. HAUL AWAY BY QUALIFIED SERVICE. USE UNTIL LESS THAN 1 INCH REMAINS IN CONTAINER, EMPTY CONTAINER REMOVE OR DEFACE LABEL BEFORE SELLING CONTAINER OR DISPOSAL

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

MATERIAL SAFETY DATA SHEET

Page 3 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

SPIRIT**MSDS ID: 03991**

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: Contains no hazardous air pollutants.

VOC CONTENT (EPA Method 24A): % VOC: Lb/Gal VOC:

CERCLA/EPCRA:

Section 313 Toxic Chemicals: None

SARA Section 311/312:

ACUTE:NO CHRONIC:NO FIRE:NO REACTIVITY:NO

SUDDEN RELEASE OF PRESSURE:NO

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 3 FIRE: 1 REACTIVITY: 1

PERSONAL PROTECTIVE EQUIPMENT: D

NFPA RATING: HEALTH: FIRE: REACTIVITY: SPECIAL:

STATE RIGHT-TO-KNOW INFORMATION:

DICHLOROMETHANE - CAS #75-09-2

ISOPROPY ALCOHOL - CAS #67-63-0

FORMIC ACID - CAS #64-18-6

CRESYLIC ACID - CAS #1319-77-3

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.