SPREX AC

Page 1 of 4 Revised 2/02/04 Replaces 8/12/03 Printed 2/03/04

MSDS ID: 04020

## I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: SPREX AC

Product Descriptor: Spray Wash Cleaner

MANUFACTURER: JOHNSONDIVERSEY, INC.

3630 E. KEMPER ROAD CINCINNATI, OH. 45241

EMERGENCY PHONE NUMBER: (800)851-7145

II. HAZARDOUS COMPONENTS			
Component Name	CAS Number	%	Exposure Limits Units
LINEAR ALCOHOL ETHOXYLATE SODIUM METASILICATE	68439-46-3 6834-92-0	_	None established

#### III. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW:

CORROSIVE MATERIAL - Causes severe burns to skin and eyes. Harmful if swallowed. Do not contact eyes, skin or clothing. Avoid breathing any dust, spray mist or vapors in spill area. Wash thoroughly after handling product. Wear eye protection, clothing and footwear to prevent skin contact. POSSIBLE ROUTES OF ENTRY: Inhalation and ingestion.

#### SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE:

EYES: Severe burns, tissue damage, or irritation with pain, swelling, blurred or impaired vision, blindness. SKIN: Severe burns, tissue destruction, blisters or rash with swelling and pain. If swallowed, may cause gastric distress, diarrhea, vomiting and possible depression of the central nervous system (CNS). May be fatal. Severe burns to mouth and throat may result with pain, gastric perforation and difficulty in swallowing or breathing. None known. Dust causes burns or severe irritation to nose, throat, and respiratory tract with pain, choking, and breathing difficulty.

CHRONIC: Same as acute effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis, sensitive skin, pulmonary function and asthma.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes, skin, respiratory tract, and gastrointestinal tract.

# IV. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15

minutes. Hold eyelids apart to completely flush all chemicals from

entire eye surface. Get immediate medical attention.

SKIN: Promptly flush skin with plenty of water for at least 15 minutes

while removing contaminated clothing and footwear. Launder

contaminated clothing and discard or thoroughly clean shoes before

SPREX AC

2 of 4 Page Revised 2/02/04 Replaces 8/12/03 2/03/04 Printed

MSDS ID: 04020

## IV. FIRST AID MEASURES (Cont.)

reuse. Get medical attention for painful, red or injured skin

If swallowed, rinse mouth with water. Dilute by drinking several INGESTION:

glasses of water. DO NOT induce vomiting. If patient vomits, rerinse mouth. Get immediate medical attention. NOTE: Never

give fluids by mouth to an unconscious person.

INHALATION: If inhaled, move to fresh air. If patient is not breathing, give

artificial respiration. If breathing is difficult, give oxygen under the direction of trained personnel or a physician. Get

immediate medical attention.

#### V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): NONE FLAME EXTENSION: N/A FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: N/A UEL: N/A

UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Toxic fumes or vapor may form during fire.

EXTINGUISHING MEDIA: Water spray, CO2, foam or dry powder.

FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure

breathing apparatus SCBA) in fire area.

SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

## VI. ACCIDENTAL RELEASE MEASURES

## IF MATERIAL IS RELEASED OR SPILLED:

Contain spilled solids. Wear protective clothing. Sweep or shovel solids or powder into a non-reactive chemical waste container. Dispose of materials in accordance with local, State and Federal regulations. Flush spill area with water.

This product does not contain a reportable quantity (RQ) under CERCLA.

## VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Store in a cool, dry area, keep away from acids. Keep container closed when not in use. Wear protective gear when handling or using. Do not pressurize container to empty.

## VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Chemical goggles if contact or splash hazard exists. PROTECTIVE GLOVES: Alkali resistant.

RESPIRATORY PROTECTION: Product does not have any established exposure limits. NIOSH/MSHA approved respirator recommended in enclosed or confined spaces where high air concentration or long exposure may occur.

OTHER PROTECTIVE CLOTHING/EQUIPMENT: Long sleeved shirt and clothing to cover exposed skin if contact hazard exists. Eyewash and safety shower in area if contact or splash hazard exists.

ENGINEERING CONTROLS:

VENTILATION: Good general ventilation should be sufficient to control airborne levels.

MSDS ID: 04020

SPREX AC

3 of 4 Page Revised 2/02/04 Replaces 8/12/03

Printed

2/03/04

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: White powder with mild odor.

BOILING POINT (DEG F): N/A FREEZING POINT: N/A

SPECIFIC GRAVITY/BULK DENSITY: 1.15

pH: N/A pH 1% SOLUTION: 12.6

VOLATILE BY VOLUME: 0

SOLUBILITY IN WATER: Soluble

VAPOR PRESSURE(mmHq): N/A at NA VAPOR DENSITY: N/A

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: Acids; Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms; oxides of

carbon; oxides of sulfur; oxides of nitrogen

HAZARDOUS POLYMERIZATION: None known.

XI. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL TESTING: Toxicological testing has not been performed on the

product. Listed below is the available toxicology test

data for components of the product.

TOXICITY TEST DATA:

Sodium Metasilicate:

Acute Oral LD50 (rat) - 1153 mg/kg (RTECS)

SODIUM CARBONATE:

Acute Oral LD50 (rat) - 4090 mg/kg (RTECS)

Acute Inhalation LC50 (rat, 2 hr.) - 2.3 mg/l (Env. Res. 31:138 (1983))

Alcohol Ethoxylates (CAS# 68439-46-3):

1.4 gm/kgAcute Oral LD50 (rat) Acute Dermal LD50 (rabbit) 5 gm/kg

Eye Irritation (rabbit) Severe

Skin Irritation (rabbit) Draize 1.2 (4 hrs.)

## XII. ECOLOGICAL INFORMATION

Toxicological testing has not been performed on the product. Listed below is the available toxicology test data for components of the product.

ECOTOXICITY TEST DATA:

Sodium Carbonate:

Acute LC50 (48 Hr.) (Daphnia magna) 265-565 mg/lAcute LC50 (96 Hr.) (Lepomis macrochirus) 300-325 mg/l

Sodium Metasilicate:

530 mg/lAcute LC50 (96 hr) Gambusia affinis Daphnia magna 113 mg/1 160 mg/1 Acute LC50 (48 hr) Acute LC50 (96 hr) Gammarus sp. 160 mg/l Acute LC50 (28 day) Polychaete 210-250 mg/l Acute LC50 (96 hr)

ENVIRONMENTAL FATE: No data available.

4 of 4 Page Revised 2/02/04 Replaces 8/12/03 Printed 2/03/04

MSDS ID: 04020

SPREX AC

# XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Not Regulated.

Adjust pH of diluted product and discharge to industrial sewer in accordance with discharge permit or local POTW regulations. Use product in container until empty. Triple rinse container with water and add to process. or dispose of container according to product labeling or Federal, State or local regulations.

#### XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

#### XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: NONE

VOC CONTENT (EPA Method 24A): % VOC: 0 Lb/Gal VOC: 0

CERCLA/EPCRA:

Section 313 Toxic Chemicals:

NONE

SARA Section 311/312:

CHRONIC:NO FIRE:NO ACUTE: YES REACTIVITY: NO

SUDDEN RELEASE OF PRESSURE: NO

LISTED CARCINOGEN: NONE

NTP: NO OSHA: NO IARC: NO

HMIS RATINGS: HEALTH: 3 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: D

NFPA RATING: HEALTH: 3 FIRE: 0 REACTIVITY:0 SPECIAL:ALKALI

STATE RIGHT-TO-KNOW INFORMATION: SODIUM CARBONATE - CAS# 497-19-8

SODIUM METASILICATE - CAS #6834-92-0

LINEAR ALCOHOL ETHOXYLATE - CAS #68439-46-3

SODIUM DODECYLBENZENE SULFONATE - CAS #25155-30-0

SODIUM BICARBONATE - CAS# 144-55-8

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

#### XVI. OTHER INFORMATION

Disclaimer: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.