
MATERIAL SAFETY DATA SHEET

Page 1 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

WSM-220**MSDS ID: 04220**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: WSM-220

Product Descriptor: Papermill Natural Solvent Cleaner

MANUFACTURER: JOHNSON DIVERSEY, INC.

EMERGENCY PHONE NUMBER: (800) 851-7145

3630 E. KEMPER ROAD

CINCINNATI, OH. 45241

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
-----	-----	-----	-----	-----
LINEAR ALCOHOL ETHOXYLATE	68439-46-3	1 - 5%	None est.	
SODIUM METASILICATE	6834-92-0	1 - 5%	None established	

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

WARNING-Product contains irritating or harmful chemicals which may cause eye or skin irritation or burns. May be harmful if swallowed. Do not get product in eyes, on skin or clothing. Wear eye protection and rubber gloves to prevent skin contact when handling product. Wash after handling. Avoid breathing dust, vapors or product spray. Contain spill and runoff to prevent direct discharge to soil or surface waters.

POSSIBLE ROUTES OF ENTRY: Ingestion, Skin and Inhalation.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Burns or severe irritation with pain, redness and swelling.
SKIN: Severe irritation or burns with rash, redness, pain or itching. INGESTION: If swallowed, pain, nausea and vomiting may result.

CHRONIC: Same as Acute Effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis and sensitive skin.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes, skin and respiratory tract.

IV. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for 15 minutes. Get medical attention.

SKIN: Flush thoroughly with plenty of water. Wash with soap and water. Remove contaminated clothes and shoes and clean before reuse. Get medical attention for any painful, red or injured skin.

INGESTION: If swallowed, rinse mouth with water. Dilute by drinking several glasses of water. DO NOT induce vomiting. If patient vomits, rerinse mouth with water. Get prompt medical attention. NOTE: Never give fluids by mouth to an unconscious person.

INHALATION: Remove to fresh air. If breathing difficulties arise, get medical attention.

MATERIAL SAFETY DATA SHEET

Page 2 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

WSM-220**MSDS ID: 04220**

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): NONE FLAME EXTENSION: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: N/A UEL: N/A
UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Toxic fumes or vapor may form during fire.
EXTINGUISHING MEDIA: Water spray, CO2, foam or dry powder.
FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus (SCBA) in fire area.
SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:
Contain spill. Absorb with sand or clay. Collect material and place in suitable waste container. Neutralize solids and spill area with dilute mineral acids or bicarbonate of soda. Dispose of by environmental regulations. This product does not contain a reportable quantity (RQ) under CERCLA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Store in a cool, dry area. Keep from freezing. If frozen, warm to thaw and mix for use. Keep container closed when not in use. Wear protective gear when handling or using. Do not pressurize container to empty.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Face shield if contact or splash hazard exists. Eye wash in use area.
PROTECTIVE GLOVES: Alkali resistant.
RESPIRATORY PROTECTION: Not normally required.
OTHER PROTECTIVE CLOTHING/EQUIPMENT: Protective clothing to cover exposed skin if contact or splash hazard exists.
ENGINEERING CONTROLS:
MECHANICAL VENTILATION: Normal room ventilation should be sufficient to control airborne levels.
LOCAL VENTILATION: Not usually required.

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear yellow liquid

BOILING POINT (DEG F): 212	FREEZING POINT: 32
SPECIFIC GRAVITY/BULK DENSITY: 1.03	
pH: 12.8	pH 1% SOLUTION: 11
VOLATILE BY VOLUME: ND	
SOLUBILITY IN WATER: Soluble	
VAPOR PRESSURE(mmHg): 17.5 at 20 C	VAPOR DENSITY: ND

MATERIAL SAFETY DATA SHEET

Page 3 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

WSM-220

MSDS ID: 04220

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: Strong acids, strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms oxides of carbon and nitrogen.

HAZARDOUS POLYMERIZATION: None known.

XI. TOXICOLOGICAL INFORMATION

Contains Corrosive and Irritating alkaline chemicals. See Section II for amounts and identity. Acute toxicology tests are listed below.

TOXICITY TEST DATA:

Sodium metasilicate: Acute Oral LD50 (rat) - 1153 mg/kg (RTECS)

XII. ECOLOGICAL INFORMATION

ECOTOXICITY DATA: Product and waste are harmful to fish and aquatic forms. Discharge process waste and overflow to a sanitary sewer or on-site treatment process.

ECOTOXICITY TEST DATA: No data available.

ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Concentrated product would be considered D002- corrosive if declared hazardous waste.

Adjust pH of diluted product and discharge to industrial sewer. Use product in container until empty. Triple rinse container with water and add to process. Recycle or dispose of container by product labeling or governmental regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: Contains no hazardous air pollutants.

VOC CONTENT (EPA Method 24A): % VOC: 5 Lb/Gal VOC: 0.429

CERCLA/EPCRA:

Section 313 Toxic Chemicals: None

SARA Section 311/312:

ACUTE: YES CHRONIC: NO FIRE: NO REACTIVITY: NO

SUDDEN RELEASE OF PRESSURE: NO

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 2 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: B

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

WSM-220

MSDS ID: 04220

XV. REGULATORY INFORMATION (Cont.)

NFPA RATING: HEALTH: 2 FIRE: 0 REACTIVITY:0 SPECIAL:
STATE RIGHT-TO-KNOW INFORMATION:
WATER - CAS #7732-18-5
3-METHOXY-3-METHYL-1-BUTANOL - CAS #56539-66-3
LINEAR ALCOHOL (C9-11) ETHOXYLATE - CAS #68439-46-3
SODIUM DODECYLBENZENE SULFONATE - CAS #25155-30-0
SODIUM METASILICATE - CAS #6834-92-0
CALIFORNIA PROPOSITION 65:
None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.