

SPIRIT 221

MSDS ID: 04221

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: SPIRIT 221

Product Descriptor: Solvent Cleaner

MANUFACTURER: JOHNSON DIVERSEY, INC.
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

EMERGENCY PHONE NUMBER: (800)851-7145

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
PETROLEUM DISTILLATE HYDROTREATED LIGHT	64742-47-8	>30%	PEL 400	PPM

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

CAUTION-Contains petroleum distillates that may cause eye irritation. May be harmful if swallowed. Avoid contact with eyes or clothing. Prolonged contact with undiluted product may cause defatting of skin. Avoid breathing mists which may cause respiratory irritation. Contain spill and runoff to prevent any environmental damage.

POSSIBLE ROUTES OF ENTRY: Ingestion, Skin and Inhalation.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Irritation with pain, swelling and redness may develop. SKIN: Irritation or dryness develop with long contact. INGESTION: If swallowed, gastric distress, diarrhea, nausea or vomiting may occur. If vomiting occurs, petroleum distillates may be inhaled into the lungs and cause chemical pneumonia. INHALATION: Overexposure to vapors may cause dizziness, headache, fatigue and respiratory irritation.

CHRONIC: Same as Acute Effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis and sensitive skin.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes and skin.

IV. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Hold eyelids apart to completely flush all chemicals from entire eye surface. Get immediate medical attention.

SKIN: Rinse off product and wash with mild soap and water.

INGESTION: Contains petroleum distillates. Do not induce vomiting because of aspiration hazard. Do not give liquids by mouth except by order of a physician. Contact a physician or Poison Center.

INHALATION: Remove to fresh air. If breathing difficulties arise, get medical attention.

MATERIAL SAFETY DATA SHEET

Page 2 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

SPIRIT 221**MSDS ID: 04221**

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): 234 FLAME EXTENSION: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: 0.6 UEL: 7.0
UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Product may burn if liquid is evaporated by heat or fire.
EXTINGUISHING MEDIA: Water spray, CO2, foam or dry powder.
FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus (SCBA) in fire area.
SPECIAL INSTRUCTIONS: Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back to the container causing a possible fire or explosion.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:
Turn off ignition sources. Contain spill. Absorb onto clay or sand. Place in covered metal container. Wash spill area with soap and water. Dispose of waste in accordance with environmental regulations.
This product does not contain a reportable quantity (RQ) under CERCLA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Product may burn if heated above ignition point temperature. Do not store near heat, sparks or open flames. Keep container closed when not in use. Do not pressurize container to empty.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Safety glasses with side shields. Eye wash in use area if contact or splash hazard exists.
PROTECTIVE GLOVES: Nitrile, Neoprene, or other oil resistant materials.
RESPIRATORY PROTECTION: Respirator protection required if PEL is exceeded. See Section II for information.
OTHER PROTECTIVE CLOTHING/EQUIPMENT: Not normally required.
ENGINEERING CONTROLS:
MECHANICAL VENTILATION: Normal room ventilation should be sufficient to control airborne levels.
LOCAL VENTILATION: Not usually required.

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear liquid with solvent odor.

BOILING POINT (DEG F): 500	FREEZING POINT: Not determined
SPECIFIC GRAVITY/BULK DENSITY: 0.82	
pH: N/A	pH 1% SOLUTION: N/A
VOLATILE BY VOLUME: TRACE	
SOLUBILITY IN WATER: Insoluble	
VAPOR PRESSURE(mmHg): 0.4 at 20 C	VAPOR DENSITY: >AIR

MATERIAL SAFETY DATA SHEET

Page 3 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

SPIRIT 221**MSDS ID: 04221**

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: Oxidizing agents including chlorinated products.

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms oxides of carbon.

HAZARDOUS POLYMERIZATION: None known.

XI. TOXICOLOGICAL INFORMATION

Any hazardous effects of the product mixture are based on information for each chemical part. See Section II for amounts of hazardous materials.

TOXICITY TEST DATA:

No data available.

XII. ECOLOGICAL INFORMATION

ECOTOXICITY DATA: Contains petroleum chemicals which are water insoluble. Do not discharge waste or unused product to sanitary sewer, ponds, waterways or the environment. Dispose of by label or governmental regulations.

ECOTOXICITY TEST DATA: No data available.

ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Not Regulated.

Contains petroleum products. Do not discharge to water or sewer. Arrange waste disposal through a licensed disposal company. Dispose of or recycle empty container by product labeling or governmental regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: Contains no hazardous air pollutants.

VOC CONTENT (EPA Method 24A): % VOC: 0 Lb/Gal VOC: 0

CERCLA/EPCRA:

Section 313 Toxic Chemicals: None

SARA Section 311/312:

ACUTE: YES CHRONIC: NO FIRE: NO REACTIVITY: NO

SUDDEN RELEASE OF PRESSURE: NO

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 1 FIRE: 1 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: B

NFPA RATING: HEALTH: 1 FIRE: 1 REACTIVITY: 0 SPECIAL:

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

SPIRIT 221

MSDS ID: 04221

XV. REGULATORY INFORMATION (Cont.)

STATE RIGHT-TO-KNOW INFORMATION:

PETROLEUM DISTILLATE HYDROTREATED LIGHT - CAS #64742-47-8

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.