
MATERIAL SAFETY DATA SHEET

Page 1 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

SECURE SEAL 5000**MSDS ID: 04312**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: SECURE SEAL 5000
PRODUCT DESCRIPTOR: NON-CHROME FINAL SEAL
MANUFACTURER: JOHNSON DIVERSEY, INC. EMERGENCY PHONE NUMBER: (800) 851-7145
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

II. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME(CAS NUMBER)	%	EXPOSURE LIMITS	UNITS
-----	-----	-----	-----
PHOSPHORIC ACID (7664-38-2)	53	TLV 1; PEL 1; STEL 3	MG/M3

III. HAZARDS IDENTIFICATION

ROUTES OF ENTRY: INHALATION: YES
SKIN: YES
INGESTION: YES
SIGNS AND SYMPTOMS OF EXPOSURE:
ACUTE: CORROSIVE TO SKIN AND EYES. MISTS ARE CORROSIVE TO SKIN, EYES
AND RESPIRATORY TRACT
CHRONIC: None Known.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
Sensitive skin

IV. FIRST AID MEASURES

EYES: FLUSH THOROUGHLY WITH FRESH WATER, FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.
SKIN: FLUSH WITH FRESH WATER, WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHES AND SHOES. GET MEDICAL ATTENTION.
INGESTION: GIVE WATER, DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
INHALATION: REMOVE TO FRESH AIR. GET MEDICAL ATTENTION

V. FIRE FIGHTING MEASURES

FLASH POINT: NONE	DEG F	FLAME EXTENSION: N/A	IN.
FLAMMABLE LIMITS IN AIR BY VOLUME:		LEL: NONE	UEL: NONE
UNUSUAL FIRE OR EXPLOSION HAZARDS:		LIQUID PRODUCES HYDROGEN IN CONTACT WITH METALS.	
EXTINGUISHING MEDIA:		CO2, FOAM	
FIRE FIGHTING INSTRUCTIONS:		WEAR PROTECTIVE GEAR AND SELF CONTAINED BREATHING APPARATUS IN FIRE AREA.	

MATERIAL SAFETY DATA SHEET

Page 2 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

SECURE SEAL 5000

MSDS ID: 04312

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED: ABSORB SMALL AMOUNTS ON FLOOR DRY MATERIAL; COLLECT AND RETURN LARGE AMOUNTS TO CONTAINER OR NEUTRALIZE WITH SODIUM BICARBONATE REPORTABLE QUANTITY (R.Q.) OF PRODUCT: 9524 LBS. OR 853 GAL.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: DO NOT PRESSURE CONTAINER TO EMPTY. KEEP FROM FREEZING. KEEP CONTAINER CLOSED. IF FROZEN, THAW AND MIX TO MAKE USABLE.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: FACE SHIELD
PROTECTIVE GLOVES: ACID RESISTANT
RESPIRATORY PROTECTION: NIOSH APPROVED RESPIRATOR WHERE TLV/PEL MAY BE EXCEEDED.
OTHER PROTECTIVE CLOTHING/EQUIPMENT: NONE
EXPOSURE GUIDELINES: SEE SECTION II FOR DETAILED INFORMATION.

IX. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (F): 215 SPECIFIC GRAVITY: 1.3400
VOLATILE BY VOLUME: 40 SOLUBILITY IN WATER: 100
VAPOR PRESSURE (MMHG): 17.5 AT 20 C
APPEARANCE AND ODOR: CLEAR LIQUID; MILD ODOR

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE
INCOMPATIBILITY WITH OTHER MATERIALS: CONCENTRATED ALKALINE PRODUCTS
HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF PHOSPHOROUS AT EXTREMELY HIGH TEMPERATURES
HAZARDOUS POLYMERIZATION: NONE

XI. TOXICOLOGICAL INFORMATION

NO DATA AVAILABLE

XII. ECOLOGICAL INFORMATION

NO DATA AVAILABLE

XIII. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: USE UNTIL LESS THAN 1 INCH REMAINS IN CONTAINER, EMPTY CONTAINER TRIPLE RINSE WITH WATER, ADD TO OPERATION REMOVE OR DEFACE LABEL BEFORE SELLING CONTAINER OR DISPOSAL CONTAINS PHOSPHATES

MATERIAL SAFETY DATA SHEET

Page 3 of 3
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

SECURE SEAL 5000

MSDS ID: 04312

XIV. TRANSPORT INFORMATION

HAZARDOUS MATERIALS DESCRIPTION/PROPER SHIPPING NAME:

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CERCLA/EPCRA:SECTION 313 TOXIC CHEMICALS:

PHOSPHORIC ACID - CAS #7664-38-2 AT 53%. ALL CHEMICAL INGREDIENTS ARE LISTED ON THE TSCA INVENTORY.

LISTED CARCINOGEN: NONE

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 3 FIRE: 0 REACTIVITY: 1

PERSONAL PROTECTIVE EQUIPMENT: D

STATE RIGHT-TO-KNOW INFORMATION:

PHOSPHORIC ACID - CAS #7664-38-2

WATER - CAS #7732-18-5

XVI. OTHER INFORMATION

THE INFORMATION IN THIS MSDS RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED OTHER THAN AS RECOMMENDED BY DIVERSEY LEVER OR IN COMBINATION WITH OTHER MATERIALS. IT IS THE USER'S RESPONSIBILITY TO EVALUATE THE APPLICABILITY OF THIS INFORMATION FOR HIS PARTICULAR CONDITIONS OF STORAGE, HANDLING AND USE.